NFS: Network File System Version 3 Protocol Specification

Comments to:
sun!eng!nfs3
nfs3@Eng.sun.com

June 25, 1993

ONC™ Technologies
2550 Garcia Avenue
Mountain View, CA 94043 USA

Copyright 1993 Sun Microsystems, Inc. Printed in the United States of America. All rights reserved.

This specification is protected by copyright and is distributed under the following conditions:

The NFS Version 3 Protocol Specification is made available for your use provided that you include this provision and copyright notice on all copies made.

Without express written consent of Sun Microsystems, Inc. (“Sun”), the names of Sun and any of its subsidiaries and affiliates may not be used in advertising or publicity pertaining to the distribution or use of this Specification as permitted herein.

THIS SPECIFICATION IS PROVIDED AS IS WITH NO WARRANTIES OF ANY KIND INCLUDING, BUT NOT LIMITED TO, THE WARRANTIES OF DESIGN, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE OR TRADE PRACTICE. THIS SPECIFICATION IS NOT PROVIDED WITH ANY SUPPORT, AND SUN IS UNDER NO OBLIGATION TO ASSIST IN ITS USE, MODIFICATION, OR ENHANCEMENT.

SUN OR ANY OF ITS SUBSIDIARIES OR AFFILIATES SHALL HAVE NO LIABILITY WITH RESPECT TO THE INFRINGEMENT OF COPYRIGHTS, TRADE SECRETS, OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS OF ANY THIRD PARTIES BY THIS SPECIFICATION OR ITS USE THEREOF, NOR SHALL SUN OR ANY OF ITS SUBSIDIARIES OR AFFILIATES BE LIABLE FOR ANY LOST REVENUE OR PROFITS OR OTHER SPECIAL, INDIRECT AND CONSEQUENTIAL DAMAGES, EVEN IF SUN HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013 and FAR 52.227-19.

Table of Contents

Introduction **1**
Scope of the NFS version 3 protocol 1
Useful terms 1
Remote Procedure Call 2
External Data Representation 2
Authentication and Permission Checking 3
Philosophy 3
Changes from the NFS version 2 protocol 4
RPC Information **7**
Authentication 7
Constants 7
Transport address 7
Sizes 7
Basic Data Types 7
Defined Error Numbers 9
Server Procedures **16**
NULL: Do nothing 18
GETATTR: Get file attributes 19
SETATTR: Set file attributes 20
LOOKUP: Lookup file name 22
ACCESS: Check Access Permission 24
READLINK: Read from symbolic link 26
READ: Read From file 28
WRITE: Write to file 30
CREATE: Create a file 33
MKDIR: Create a directory 36
SYMLINK: Create a symbolic link 38
MKNOD: Create a special device 40
REMOVE: Remove a File 42
RMDIR: Remove a Directory 44
RENAME: Rename a File or Directory 46
LINK: Create Link to an object 48
READDIR: Read From Directory 50
READDIRPLUS: Read from directory extended 53
FSSTAT: Get dynamic file system information 56
FSINFO: Get static file system Information 58
PATHCONF: Retrieve POSIX information 61
COMMIT: Commit cached data on a server to stable storage 63
Implementation issues **67**
Multiple version support 67
Server/client relationship 67
Pathname interpretation 67
Permission issues 67

Duplicate request cache 68
File name component handling 69
Synchronous modifying operations 69
Lookups and name resolution 69
Adaptive retransmission 70
Caching policies 70
Stable versus unstable writes 70
32 bit clients/servers and 64 bit clients/servers 70
Appendix I: Mount protocol 73
RPC Information 74
Authentication 74
Constants 74
Transport address 74
Sizes 74
Basic Data Types 74
Server Procedures 75
Null: Do nothing 76
Mount: Add mount entry 77
Dump: Return mount entries 78
Unmount: Remove mount entry 79
Unmount all: Remove all mount entries 80
Export: Return export list 81
Appendix II: Lock manager protocol 83
Basic Data Types for Locking 83
NLM Procedures 86
NULL: Do nothing 87
Implementation issues 88
Appendix III: Bibliography 89
Index 91

Introduction

The Sun Network File System (NFS™) protocol provides transparent remote access to shared file systems across networks. The NFS protocol is designed to be machine, operating system, network architecture, and transport protocol independent. This independence is achieved through the use of Remote Procedure Call (RPC) primitives built on top of an eXternal Data Representation (XDR). Implementations of the NFS version 2 protocol exist for a variety of machines, from personal computers to supercomputers. The initial version of NFS is specified in the Network File System specification *[RFC1094]*. A description of the initial implementation can be found in *[Sandberg]*.

The supporting MOUNT protocol performs the operating system-specific functions that allow clients to attach remote directory trees to a point within the local file system. The mount process also allows the server to grant remote access privileges to a restricted set of clients via export control.

The Lock Manager provides support for file locking when used in conjunction with NFS. The Lock Manager protocol isolates the inherently stateful aspects of file locking into a separate protocol.

A more complete description of the above protocols and their implementation is to be found in *[X/OpenNFS]*.

The purpose of this document is to:

- specify the NFS version 3 protocol, and to
- describe semantics of the protocol through annotation and description of intended implementation.

The normative text is the description of the RPC procedures and arguments and results, which defines the over-the-wire protocol, and the semantics of those procedures. The material describing implementation practice is intended to aid the understanding of the protocol specification and describes some possible implementation issues and solutions. It is not possible to describe all implementations, and the UNIX® operating system implementation of NFS is most often used to provide examples. Given that, the implementation discussion does not bear the authority of the description of the over-the wire protocol itself.

Scope of the NFS version 3 protocol

This revision of the NFS protocol addresses new requirements. The need to support larger files and file systems has prompted extensions to allow 64 bit sizes and offsets. The revision enhances security by adding support for an access check to be done on the server. Performance modifications are of three types. First, the number of over-the-wire packets for a given set of file operations is reduced by returning file attributes on every operation, thus decreasing the number of calls to get modified attributes. Second, the write throughput bottleneck caused by the synchronous definition of write in the original protocol specification has been addressed by adding support so that the NFS server can do unsafe writes. Unsafe writes are writes which have not been committed to stable storage before the operation returns. This specification defines a method for committing these unsafe writes to stable storage in a reliable way. Third, limitations on transfer sizes have been relaxed.

The ability to support multiple versions of a protocol in RPC will allow implementors of the NFS version 3 protocol to define clients and servers that provide backwards compatibility with the existing installed base of NFS version 2 protocol implementations.

The extensions described here represent an evolution of the existing NFS protocol and most of the design features of NFS described in *[Sandberg]* persist. See *Changes from the NFS version 2 protocol* on page 4 for a more detailed summary of the changes introduced by this revision.

Useful terms

In this specification the term *server* refers to a machine that provides resources to the network; a *client* is a machine that accesses resources over the network; a *user* is a person logged in on a client; an *application* is a program that executes on a client.

™ NFS is a trademark of Sun Microsystems, Inc.

® UNIX is a registered trademark of Bell Laboratories, UNIX System Laboratories, or AT&T.

Remote Procedure Call

The Sun Remote Procedure Call specification provides a procedure-oriented interface to remote services. Each server supplies a *program* which is a set of procedures. NFS is one such program. The combination of host address, program number, version number, and procedure number specify one remote service procedure. Servers can support multiple versions of a program by using different protocol version numbers.

A goal of NFS was to not require any specific level of reliability from its lower levels so it could potentially be used on many underlying transport protocols. RPC provides the abstraction above lower level network and transport protocols on which NFS is based.

For ease of discussion, the rest of this document assumes NFS is implemented on top of Sun RPC, which is specified in *[RFC1057]*. A more complete discussion is found in *[Corbin]*.

External Data Representation

The Sun eXternal Data Representation (XDR) specification provides a standard way of representing a set of data types on a network. This takes care of the problem of different byte orders, structure alignment, and data type representation on different, communicating machines.

In this document we use the RPC Data Description Language to specify the XDR format parameters and results to each of the RPC service procedures that a NFS server provides. The RPC Data Description Language is similar to declarations in the C programming language. A few new constructs have been added. The notation:

```
string name[SIZE];
string data<DSIZE>;
```

defines **name**, which is a fixed size block of SIZE bytes, and **data**, which is a variable size block of up to DSIZE bytes. This same notation is used to indicate fixed length arrays and arrays with a variable number of elements up to a fixed maximum. A variable length definition with no size specified means there is no maximum size for the field.

The discriminated union definition:

```
union example switch (enum status) {
case OK:
   struct {
      filename    file1;
      filename    file2;
      integer     count;
   }
case ERROR:
   struct {
      errstat     error;
      integer     errno;
   }
default:
   void;
}
```

defines a structure where the first thing over the network is an enumeration type called **status**. If the value of **status** is OK, the next thing on the network will be the structure containing **file1**, **file2**, and **count**. Else if the value of **status** is ERROR, the next thing on the network will be a structure containing **error** and **errno**. If the value of **status** is neither OK nor ERROR then there is no more data in the structure.

The XDR type **hyper** is an 8 byte (64 bit) quantity. It is used in the same way as the integer type. For example:

```
hyper             foo;
unsigned hyper    bar;
```

foo is an 8 byte signed value, while **bar** is an 8 byte unsigned value.

Although RPC/XDR compilers exist to generate client and server "stubs" from RPC Data Description Language input, NFS does not require their use. Any software that provides equivalent encoding and decoding functionality to the canonical network order of data defined by XDR can be used to interoperate with other implementations of NFS.

XDR is described in *[RFC1014].*

Authentication and Permission Checking

The RPC protocol includes a slot for authentication parameters on every call. The contents of the authentication parameters are determined by the "flavor" of authentication used by the server and client. A server may support several different flavors of authentication at once. The flavor called `AUTH_NONE` provides null authentication, that is, no authentication information is passed. The `AUTH_UNIX` flavor passes UNIX-style user id, group id, and groups with each call. The `AUTH_DES` flavor provides DES encrypted authentication parameters based on a network-wide name, with session keys exchanged via a public key scheme. The `AUTH_KERB` flavor provides DES encrypted authentication parameters based on a network-wide name with session keys exchanged via Kerberos secret keys.

The NFS server does permission checking by taking the credentials from the RPC authentication information in each remote request. For example, using `AUTH_UNIX` flavor authentication the server gets the user's effective user id, effective group id and groups on each call, and uses them to check access. Using user ids and group ids implies that the client and server either share the same id list or do local user and group id mapping. Servers and clients must agree on the mapping from user to uid and from group to gid, for those sites that do not implement a consistent user id and group id space. In practice, such mapping is typically performed on the server, following a static mapping scheme or a mapping established by the user from a client at mount time.

The `AUTH_DES` and `AUTH_KERB` style of authentication is based on a network-wide name. It provides greater security through the use of DES encryption and public keys in the case of `AUTH_DES`, and DES encryption and Kerberos secret keys (and tickets) in the `AUTH_KERB` case. Again, the server and client must agree on the identity of a particular name on the network, but the name to identity mapping is more operating system independent than the uid and gid mapping in `AUTH_UNIX`. Also, because the authentication parameters are encrypted, a malicious user must know another users network password or private key to masquerade as that user. Similarly, the server returns a verifier that is also encrypted so that masquerading as a server requires knowing a network password.

The `NULL` procedure requires no authentication.

Philosophy

This specification defines the NFS version 3 protocol, that is the over-the-wire protocol by which a client accesses a server. The protocol provides a well-defined interface to a server's file resources. A client or server *implements* the protocol, and provides a mapping of the local file system semantics and actions into those defined in NFS. Implementations may differ to varying degrees, depending on the extent to which a given environment can support all the operations and semantics defined in the NFS version 3 protocol. Though implementations exist and are used to illustrate various aspects of the NFS version 3 protocol, the protocol specification itself is the final description of how clients access server resources.

Because NFS is designed to be operating system independent it does not necessarily match the semantics of any existing system. Server implementations are expected to make a "best effort" at supporting the protocol. If a server cannot support a particular protocol procedure it may return the `NFS3ERR_NOTSUP` error that indicates that the operation is not supported. For example, many operating systems do not support the notion of a *hard link* A server that cannot support hard links should return `NFS3ERR_NOTSUP` in response to a `LINK` request. `FSINFO` describes the most commonly unsupported procedures in the **`properties`** bit map. Alternatively, a server may not natively support a given operation, but may choose to emulate it in the NFS implementation to provide greater functionality.

In some cases, a server can support most of the semantics described by the protocol but not all. For example, the **`ctime`** field in the **`fattr`** structure gives the time that a file's attributes were last modified. Many systems do not keep this information. In this case, rather than not support the `GETATTR` operation, a server should simulate it by returning the last modified time in place of **`ctime`**. Servers must be careful when simulating attribute information because of possible side effects on clients. For example, many clients use file modification times as a basis for their cache consistency scheme.

NFS servers are dumb and NFS clients are smart. It is the clients that do the work required to convert the generalized file access that servers provide into a file access method which is useful to applications and users. In the LINK example given above, a UNIX client that received an NFS3ERR_NOTSUP from a server would do the recovery necessary to either make it look to the application like the link request had succeeded or return a reasonable error. In general, it is the burden of the client to implement recovery.

The NFS protocol assumes a stateless server implementation. Statelessness means that the server does not need to maintain state about any of its clients in order to function correctly. Stateless servers have a distinct advantage over stateful servers in the event of failure recovery (a. k. a. crash). With stateless servers, a client need only retry a request until the server responds; the client does not even need to know that the server has crashed. See additional comments in *Duplicate request cache* on page 68.

Obviously for a server to be useful it holds nonvolatile state: data stored in the file system. Design assumptions in NFS regarding flushing of modified data to stable storage reduce the number of failure modes in which data loss can occur. In this way, NFS can tolerate transient failures, including transient failures of the network. NFS cannot tolerate a non-transient failure of the stable storage itself.

That is not to say that an NFS server can't maintain noncritical state. In many cases servers will maintain state (cache) about previous operations to increase performance. For example, a client READ request might trigger a read–ahead of the next block of the file into the server's data cache in the anticipation that the client is doing a sequential read and the next client READ request will be satisfied from the cache instead of from the disk. Read-ahead on the server increases performance by overlapping server disk I/O with client requests. The important point here though is: the read–ahead block is not necessary for correct server behavior. If the server crashes and loses it memory cache of read buffers, recovery is simple on reboot—clients will continue read operations retrieving data from the server disk.

Most data modifying operations in the NFS protocol are synchronous. That is, when a data modifying procedure returns to the client, the client can assume that the operation has completed and any modified data associated with the request is now on stable storage. For example, a synchronous client WRITE request may cause the server to update data blocks, file system information blocks, and file attribute information (size and modify times)—the latter information is usually referred to as *metadata*. When the WRITE operation completes, the client can assume that the write data is safe and discard it. This is a very important part of the statelessness of the server. If the server did not flush dirty data before returning to the client, the client would have no way of knowing when it was safe to discard modified data. The following data modifying procedures are synchronous: WRITE (with **stable** flag set TRUE), CREATE, MKDIR, SYMLINK, MKNOD, REMOVE, RMDIR, RENAME, LINK, and COMMIT.

The NFS version 3 protocol introduces *safe asynchronous writes* in NFS, when the WRITE procedure is used in conjunction with the COMMIT procedure. The COMMIT procedure provides a way for the client to flush data from previous asynchronous WRITE requests on the server to stable storage and to detect whether it is necessary to retransmit the data. See the descriptions of the WRITE and COMMIT procedures.

The LOOKUP procedure is used by the client to traverse multicomponent file names (pathnames). Each call to LOOKUP is used to resolve one segment of a pathname. There are two reasons for restricting LOOKUP to a single segment: it is hard to standardize a common format for hierarchical file names and the client and server may have different mappings of pathnames to file systems. This would imply that either the client must break the path name at file system attachment points, or the server must know about the client's file system attachment points. In NFS, it is the client that constructs the hierarchical file name space using mounts to build a hierarchy. Support utilities, such as the Automounter, provide a way to manage a shared, consistent image of the file name space while still being driven by the client mount process.

Clients can do as much or as little caching as they want. The general practice with the NFS version 2 protocol was to implement a time-based client-server cache consistency mechanism. It is expected NFS version 3 protocol implementations will use a similar mechanism. The NFS version 3 protocol has some explicit support, in the form of additional attribute information to eliminate explicit attribute checks. However, caching is not required, nor is any caching policy defined by the protocol. Neither NFS version 2 protocol nor NFS version 3 protocol provide a means of maintaining strict client-server consistency (and, by implication, consistency across client caches).

Changes from the NFS version 2 protocol

The ROOT and WRITECACHE procedures have been removed. A MKNOD procedure has been defined to allow creating

special files, eliminating the overloading of CREATE. Caching on the client is **not** defined nor dictated by the NFS version 3 protocol, but additional information and hints have been added to the protocol to allow clients wishing to cache additional information to manage their cache more effectively. Procedures that affect the attributes of a file or directory may now return the new attributes after the operation has completed to optimize out a subsequent GETATTR used in validating attribute caches. In addition, operations that modify the directory in which the target object resides return the old and new attributes of the directory to allow clients to implement more intelligent cache invalidation procedures. An ACCESS procedure provides access permission checking, the FSSTAT procedure returns dynamic information about a file system, the FSINFO procedure returns static information about a file system and server, the READDIRPLUS procedure returns a file handle and attributes in addition to names, and the PATHCONF procedure returns POSIX pathconf information about a file.

Below is a list of the important changes between version 2 and version 3 of the protocol.

File handle size
: The file handle has been increased to a variable length array of 64 bytes maximum from a fixed array of 32 bytes. This addresses some known requirements for a slightly larger file handle size. The file handle was converted from fixed length to variable length to reduce local storage and network bandwidth requirements for systems which do not utilize the full 64 bytes of length.

Maximum data sizes
: The maximum size of a data transfer used in the READ, WRITE, READDIR, and READDIRPLUS procedures is now set by values in the FSINFO return structure. In addition, preferred transfer values are returned via FSINFO. File names and pathnames are now specified as strings of variable length. The actual length restrictions are determined by the client and server implementation as appropriate. The protocol does not place any artificial limits on the length. The error return, NFS3ERR_NAMETOOLONG, is provided to allow the server to return an indication to the client that it received a pathname that was too long for it to handle.

Error return
: Error returns in some instances now return data (*e.g.* attributes). **nfsstat3** now defines the full set of errors that can be returned by a server. No others are allowed.

File type
: The file type now includes NF3CHR and NF3BLK for special files. Attributes for these types include subfields for UNIX major and minor devices numbers. NF3SOCK and NF3FIFO are now defined.

File attributes
: The **blocksize** (the size in bytes of a block in the file) field has been removed. The **mode** field no longer contains file type information. The **size** and **fileid** fields have been widened to eight byte unsigned integers from four byte integers. Major and minor device information is now presented in a distinct structure. The **blocks** field name has been changed to **used**, and it now returns the total number of bytes used by the file. It is also an eight byte unsigned integer.

Set file attributes
: In the NFS version 2 protocol, the settable attributes were represented by a subset of the file attributes structure; the client indicated those attributes which were **not** to be modified by setting the corresponding field to −1, overloading some unsigned fields. The set file attributes structure now uses a discriminated union for each field to tell whether or how to set that field. The time fields can be set to either the server's current time or a time supplied by the client.

LOOKUP
: The LOOKUP return structure now includes the attributes for the directory searched.

ACCESS
: An ACCESS procedure has been added to allow an explicit over-the-wire permissions check. This allows fixing known problems with the super-user id mapping feature in many implementations (where, due to mapping of root user, unexpected *permission denied* errors could occur on reading or writing a file).

READ
: The reply structure includes a boolean that is TRUE if end–of–file was encountered on the READ. This allows the client to correctly detect end-of-file.

WRITE

The **beginoffset** and **totalcount** fields were removed from the WRITE arguments. The reply now includes a count so that the server can write less than the requested amount of data.

CREATE

An exclusive flag was added for the exclusive creation of regular files, with the exclusive create verifier.

MKNOD

This procedure was added to support the creation of special files. This avoids overloading fields of CREATE as was done in some NFS version 2 protocol implementations.

READDIR

The READDIR arguments now include a verifier to allow the server to validate a **cookie**.

READDIRPLUS

This procedure was added to return file handles and attributes in an extended directory list.

FSINFO

FSINFO was added to provide nonvolatile information about a file system. The reply includes preferred and maximum read transfer size, preferred and maximum write transfer size, and flags stating whether links or symbolic links are supported. Also returned are preferred transfer size for READDIR and READDIRPLUS procedure replies, server time granularity, and whether or not times can be set in a SETATTR request.

FSSTAT

FSSTAT was added to provide volatile information about a file system, for use by utilities such as *df(1)*. The reply includes the total size and free space in the file system specified in bytes, the total number of files and number of free file slots in the file system, and an estimate of time between file system modifications (for use in cache consistency checking algorithms).

COMMIT

The COMMIT procedure provides the synchronization mechanism to be used with asynchronous WRITE operations.

RPC Information

Authentication

The NFS service uses AUTH_NONE in the NULL procedure. AUTH_UNIX, AUTH_DES, or AUTH_KERB are used for all other procedures. Other authentication types may be supported in the future.

Constants

These are the RPC constants needed to call the NFS service. They are given in decimal.

```
PROGRAM 100003
VERSION 3
```

Transport address

NFS is normally supported over the UDP protocol. It uses port 2049, the same as the NFS version 2 protocol.

Sizes

These are the sizes, given in decimal bytes, of various XDR structures used in the NFS version 3 protocol:

NFS3_FHSIZE 64
: The maximum size in bytes of the opaque file handle.

NFS3_COOKIEVERFSIZE 8
: The size in bytes of the opaque cookie verifier passed by READDIR and READDIRPLUS.

NFS3_CREATEVERFSIZE 8
: The size in bytes of the opaque verifier for use in implementing exclusive CREATE.

NFS3_WRITEVERFSIZE 8
: The size in bytes of the opaque verifier for use in implementing asynchronous WRITE.

Basic Data Types

The following XDR definitions are basic definitions that are used in other structures later on.

uint64
```
typedef unsigned hyper  uint64;
```

int64
```
typedef hyper     int64;
```

uint32
```
typedef unsigned long   uint32;
```

int32
```
typedef long      int32;
```

filename3
```
typedef string    filename3<>;
```

nfspath3
```
typedef string    nfspath3<>;
```

fileid3
```
typedef uint64    fileid3;
```

cookie3
```
typedef uint64    cookie3;
```

cookieverf3
```
typedef opaque    cookieverf3[NFS3_COOKIEVERFSIZE];
```

createverf3

```
   typedef opaque    createverf3[NFS3_CREATEVERFSIZE];
```

writeverf3

```
   typedef opaque    writeverf3[NFS3_WRITEVERFSIZE];
```

uid3

```
   typedef uint32    uid3;
```

gid3

```
   typedef uint32    gid3;
```

size3

```
   typedef uint64    size3;
```

offset3

```
   typedef uint64    offset3;
```

mode3

```
   typedef uint32    mode3;
```

count3

```
   typedef uint32    count3;
```

nfsstat3

```
   enum nfsstat3 {
      NFS3_OK              = 0,
      NFS3ERR_PERM         = 1,
      NFS3ERR_NOENT        = 2,
      NFS3ERR_IO           = 5,
      NFS3ERR_NXIO         = 6,
      NFS3ERR_ACCES        = 13,
      NFS3ERR_EXIST        = 17,
      NFS3ERR_XDEV         = 18,
      NFS3ERR_NODEV        = 19,
      NFS3ERR_NOTDIR       = 20,
      NFS3ERR_ISDIR        = 21,
      NFS3ERR_INVAL        = 22,
      NFS3ERR_FBIG         = 27,
      NFS3ERR_NOSPC        = 28,
      NFS3ERR_ROFS         = 30,
      NFS3ERR_MLINK        = 31,
      NFS3ERR_NAMETOOLONG  = 63,
      NFS3ERR_NOTEMPTY     = 66,
      NFS3ERR_DQUOT        = 69,
      NFS3ERR_STALE        = 70,
      NFS3ERR_REMOTE       = 71,
      NFS3ERR_BADHANDLE    = 10001,
      NFS3ERR_NOT_SYNC     = 10002,
      NFS3ERR_BAD_COOKIE   = 10003,
      NFS3ERR_NOTSUPP      = 10004,
      NFS3ERR_TOOSMALL     = 10005,
      NFS3ERR_SERVERFAULT  = 10006,
      NFS3ERR_BADTYPE      = 10007,
      NFS3ERR_JUKEBOX      = 10008
   };
```

The **nfsstat3** type is returned with every procedure's results. A value of NFS3_OK indicates that the call completed

successfully and the results are valid. Any other value indicates that some error occurred on the call, as identified by the error code. Note that the precise numeric encoding must be followed. No other values may be returned by a server. Servers are expected to make a best effort mapping of error conditions to the set of error codes defined.

A description of each defined error follows.

Defined Error Numbers

NFS3_OK
: Indicates the call completed successfully and the results are valid.

NFS3ERR_PERM
: Not owner. The operation was not allowed because the caller is either not a privileged user (root) or not the owner of the target of the operation.

NFS3ERR_NOENT
: No such file or directory. The file or directory name specified does not exist.

NFS3ERR_IO
: I/O error. A hard error (*e.g.* disk error) occurred when the operation was in progress.

NFS3ERR_NXIO
: I/O error. No such device or address.

NFS3ERR_ACCES
: Permission denied. The caller does not have the correct permission to perform the requested operation. Contrast this with NFS3ERR_PERM which restricts itself to owner or super-user permission failures.

NFS3ERR_EXIST
: File exists. The file specified already exists.

NFS3ERR_XDEV
: Attempt to do a cross device hard link.

NFS3ERR_NODEV
: No such device.

NFS3ERR_NOTDIR
: Not a directory. The caller specified a non-directory in a directory operation.

NFS3ERR_ISDIR
: Is a directory. The caller specified a directory in a non-directory operation.

NFS3ERR_INVAL
: Invalid argument or unsupported argument for an operation. Such as attempting a READLINK on an object other than a symbolic link, or attempting to SETATTR a time field on a server that does not support this operation.

NFS3ERR_FBIG
: File too large. The operation caused a file to grow beyond the server's limit.

NFS3ERR_NOSPC
: No space left on device. The operation caused the server's file system to reach its limit.

NFS3ERR_ROFS
: Read-only file system. Modifying operation attempted on a read-only file system.

NFS3ERR_MLINK
: Too many links.

NFS3ERR_NAMETOOLONG
: File name too long. The file name in an operation was too long.

NFS3ERR_NOTEMPTY
: Directory not empty. Attempt to remove a directory that was not empty.

NFS3ERR_DQUOT
: Resource (quota) hard limit exceeded. The user's resource limit on the server has been exceeded.

NFS3ERR_STALE
: Invalid file handle. The file handle given in the arguments was invalid. The file referred to by that file handle

no longer exists or access to it has been revoked.

NFS3ERR_REMOTE
: Too many levels of remote in path. The file handle given in the arguments referred to a file on a non-local file system on the server.

NFS3ERR_BADHANDLE
: Illegal NFS file handle. The file handle failed internal consistency checks.

NFS3ERR_NOT_SYNC
: Update synchronization mismatch (on SETATTR).

NFS3ERR_BAD_COOKIE
: READDIR or READDIRPLUS cookie is stale.

NFS3ERR_NOTSUPP
: Operation is not supported.

NFS3ERR_TOOSMALL
: Buffer or request is too small.

NFS3ERR_SERVERFAULT
: An I/O or similar failure caused the server to abandon the request. No attributes can be returned. The client should translate this into an appropriate error. UNIX clients may translate this to EIO.

NFS3ERR_BADTYPE
: An attempt was made to create an object of a type not supported by the server.

NFS3ERR_JUKEBOX
: The server initiated the request, but was not able to complete it in a timely fashion. The client should wait and then try the request with a new RPC transaction id. For example, this error should be returned from a server which supports hierarchical storage and receives a request to process a file that has been migrated. In this case, the server should start the immigration process and respond to client with this error.

ftype3

```
enum ftype3 {
   NF3REG =    1,
   NF3DIR =    2,
   NF3BLK =    3,
   NF3CHR =    4,
   NF3LNK =    5,
   NF3SOCK =   6,
   NF3FIFO =   7
};
```

The enum **ftype3** gives the type of a file. The type NF3REG is a regular file, NF3DIR is a directory, NF3BLK is a block special device file, NF3CHR is a character special device file, NF3LNK is a symbolic link, NF3SOCK is a socket, and NF3FIFO is a named pipe. Note that the precise enum encoding must be followed.

specdata3

```
struct specdata3 {
   uint32   specdata1;
   uint32   specdata2;
};
```

The interpretation of the two words depends on the type of file system object. For a block special (NF3BLK) or character special (NF3CHR) **specdata1** and **specdata2** are the major and minor device numbers, respectively. (This is obviously a UNIX-specific interpretation.) For all other file types, these two words should either be set to 0 or the values should be agreed upon by the client and server. If the client and server do not agree upon the values, the client should treat these fields as if they are set to 0. This data field is returned as part of the **fattr3** structure and so is available from all replies returning attributes.

nfs_fh3

```
struct nfs_fh3 {
   opaque   data<NFS3_FHSIZE>;
};
```

The **nfs_fh3** is the variable length opaque object returned by the server on LOOKUP, CREATE, SYMLINK, MKNOD, LINK, or READDIRPLUS which is used by the client on subsequent operations to reference the file. The file handle contains all the information the server needs to distinguish an individual file. To the client, the file handle is opaque. The client stores file handles for use in a later request, and can compare two file handles from the same server for equality by doing a byte-by-byte comparison, but cannot otherwise interpret the contents of file handles. If two file handles from the same server are equal they must refer to the same file, but if they are not equal no conclusions can be drawn. Servers should try to maintain a one–to–one correspondence between file handles and files, but this is not required. Clients should use file handle comparisons only to improve performance, not for correct behavior.

Servers can revoke the access provided by a file handle at any time. If the file handle passed in a call refers to a file system object that no longer exists on the server, or access for that file handle has been revoked, the NFS3ERR_STALE error will be returned.

nfstime3

```
struct nfstime3 {
   uint32   seconds;
   uint32   nseconds;
};
```

The **nfstime3** structure gives the number of seconds and nanoseconds since midnight January 1, 1970 Greenwich Mean Time. It is used to pass time and date information. The times associated with files are all server times except in the case of a SETATTR operation where the client can explicitly set the file time. A server converts to and from local time when processing time values, preserving as much accuracy as possible. If the precision of time stamps stored for a file is less than that defined by NFS version 3 protocol, loss of precision can occur. An adjunct time maintenance protocol is recommended to reduce client and server time skew.

fattr3

```
struct fattr3 {
   ftype3      type;
   mode3       mode;
   uint32      nlink;
   uid3        uid;
   gid3        gid;
   size3       size;
   size3       used;
   specdata3   rdev;
   uint64      fsid;
   fileid3     fileid;
   nfstime3    atime;
   nfstime3    mtime;
   nfstime3    ctime;
};
```

This structure defines the attributes of a file system object. It is returned by most operations on an object; in the case of operations which affect two objects (*e.g.*, a MKDIR which modifies the target directory attributes and defines new attributes for the newly created directory), the attributes for both may be returned. In some cases, the attributes are returned in the structure **wcc_data** defined below; in other cases the attributes are returned alone. The main changes from the NFS version 2 protocol are that many of the fields have been widened, and the major/minor device information is now presented in a distinct structure rather than being packed into a word.

The **fattr3** structure contains the basic attributes of a file. All servers should support this set of attributes even if they have to simulate some of the fields. **Type** is the type of the file. **Mode** is the protection mode bits. **Nlink** is the

number of hard links to the file—that is, the number of different names for the same file. **Uid** is the user id of the owner of the file. **Gid** is the group id of the group of the file. **Size** is the size in bytes of the file. **Used** is the number of bytes of disk space that the file actually uses (which can be smaller than the **size** because the file may have *holes*, or it may be larger). **Rdev** describes the device file if the file type is NF3CHR or NF3BLK—see the **specdata3** discussion. **Fsid** is the file system identifier for the file system. **Fileid** is a number which uniquely identifies the file within its file system (on UNIX this would be the inumber). **Atime** is the time when the file data was last accessed. **Mtime** is the time when the file data was last modified (written). **Ctime** is the time when the attributes of the file were last changed. Writing to the file changes the **ctime** in addition to the **mtime**.

The **mode** bits are defined as follows:

0x00800	Set user id on execution.
0x00400	Set group id on execution.
0x00200	Save swapped text (not defined in POSIX).
0x00100	Read permission for owner.
0x00080	Write permission for owner.
0x00040	Execute permission for owner on a file. Or lookup (search) permission for owner in directory.
0x00020	Read permission for group.
0x00010	Write permission for group.
0x00008	Execute permission for group on a file. Or lookup (search) permission for group in directory.
0x00004	Read permission for others.
0x00002	Write permission for others.
0x00001	Execute permission for others on a file. Or lookup (search) permission for others in directory.

post_op_attr

```
union post_op_attr switch (bool attributes_follow){
case TRUE:
   fattr3   attributes;
case FALSE:
   void;
};
```

The structure used for returning attributes for those operations that are not directly involved with manipulating attributes. A general notion for this version of the protocol is to return the attributes on every operation. This is designed to help clients that choose to cache attributes by reducing the number of calls to GETATTR which are only done to validate cached attributes.

This appears to make returning attributes optional. However, server implementors are **strongly** encouraged to make best effort to return attributes. However, for some error returns, it is not possible to return the attributes because they weren't available to the server. It also possible for the real operation to either succeed or fail, but the attributes for some reason weren't available to the server.

wcc_attr

```
struct wcc_attr {
   size3       size;
   nfstime3    mtime;
   nfstime3    ctime;
};
```

This is a subset of pre-operation attributes needed to better support NFS weak cache consistency semantics. **Size** is the file size in bytes of the object before the operation. **Mtime** is the time of last modification of the object before the operation. **Ctime** is the time of last change to the attributes of the object before the operation. See discussion in **wcc_data** below.

The use of **mtime** by clients to detect changes to file system objects residing on a server is dependent on the granularity of the time base on the server.

pre_op_attr

```
union pre_op_attr switch (bool attributes_follow){
case TRUE:
   wcc_attr    attributes;
case FALSE:
   void;
};
```

wcc_data

```
struct wcc_data {
   pre_op_attr    before;
   post_op_attr   after;
};
```

When a client performs an operation that modifies the state of a file or directory on the server, it cannot immediately determine from the post-operation attributes whether the operation just performed was the only operation on the object since the last time it received the attributes for the object. This is important, since if an intervening operation **has** changed the object, the client will need to invalidate any cached data for the object (except for the data that it just wrote).

To deal with this, we introduce the notion of *weak cache consistency data*, or **wcc_data**. A **wcc_data** structure consists of certain key fields from the object attributes **before** the operation, together with the object attributes **after** the operation. This information allows the client to manage its cache more accurately than in the NFS version 2 protocol. (The term *weak cache consistency* is used to emphasize the fact that this mechanism does not provide the strict server-client consistency which a cache consistency protocol would provide.)

post_op_fh3

```
union post_op_fh3 switch (bool handle_follows){
case TRUE:
   nfs_fh3     handle;
case FALSE:
   void;
};
```

One of the principles of this revision of the NFS protocol is to return the real value from the indicated operation and not an error from an incidental operation. The **post_op_attr** structure was designed to allow the server to recover from errors associated with getting attributes or from errors encountered when trying to construct a file handle.

This structure is used to return a file handle from the CREATE, MKDIR, SYMLINK, MKNOD, and READDIRPLUS requests. In each case, the client can get the file handle by issuing a LOOKUP request after a successful return from one of the above operations. Returning the file handle is an optimization to not force the client to immediately issue a LOOKUP request.

sattr3

```
enum time_how {
   DONT_CHANGE          = 0,
   SET_TO_SERVER_TIME   = 1,
   SET_TO_CLIENT_TIME   = 2
};
union set_mode3 switch (bool set_it) {
case TRUE:
   mode3    mode;
default:
   void;
};
union set_uid3 switch (bool set_it) {
case TRUE:
   uid3     uid;
default:
   void;
};
union set_gid3 switch (bool set_it) {
case TRUE:
   gid3     gid;
default:
   void;
};
union set_size3 switch (bool set_it) {
case TRUE:
   size3    size;
default:
   void;
};
union set_atime switch (time_how set_it) {
case SET_TO_CLIENT_TIME:
   nfstime3 atime;
default:
   void;
};
union set_mtime switch (time_how set_it) {
case SET_TO_CLIENT_TIME:
   nfstime3 mtime;
default:
   void;
};

struct sattr3 {
   set_mode3   mode;
   set_uid3    uid;
   set_gid3    gid;
   set_size3   size;
   set_atime   atime;
   set_mtime   mtime;
};
```

The **sattr3** structure contains the file attributes that can be set from the client. The fields are the same as the similarly named fields in the **fattr3** structure above. In the NFS version 3 protocol, the settable attributes are described by a

structure containing a set of discriminated unions. Each union indicates whether the corresponding attribute is to be updated, and if so how.

There are two forms of discriminated unions used. In setting the **mode**, **uid**, **gid**, or **size**, the discriminated union is switched on a boolean **set_it**; if this is TRUE, a value of the appropriate type is then encoded.

In setting the **atime** or **mtime**, the union is switched on an enum **set_it**. If **set_it** has the value DONT_CHANGE, the corresponding attribute is left unchanged. If it has the value SET_TO_SERVER_TIME, the corresponding attribute is set by the server to its local time; no data is provided by the client. Finally, if **set_it** has the value SET_TO_CLIENT_TIME, the attribute is set to the time passed by the client in a structure **nfstime3**. (See the description of the FSINFO procedure, which addresses the issue of time granularity).

diropargs3

```
struct diropargs3 {
   nfs_fh3     dir;
   filename3   name;
};
```

The **diropargs3** structure is used in directory operations. The file handle, **dir**, identifies the directory in which to manipulate or access the file, **name**. See additional comments in *File name component handling* on page 69.

Server Procedures

The following sections define the RPC procedures that are supplied by a NFS version 3 protocol server. The RPC procedure number is given at the top of the page along with the name and version. The SYNOPSIS provides the name of the procedure, the list of the names of the arguments, the list of the names of the results, followed by the XDR argument declarations and results declarations. The information in the SYNOPSIS is specified in RPC Data Description Language as defined in *[RFC1014]*. The DESCRIPTION section tells what the procedure is expected to do and how its arguments and results are used. The ERRORS section lists the errors returned for specific types of failures. The IMPLEMENTATION field gives information about how the procedure is expected to work and how it should be used by clients.

```
program NFS_PROGRAM {
   version NFS_V3 {
      void
       NFSPROC3_NULL(void)                    = 0;
      GETATTR3res
       NFSPROC3_GETATTR(GETATTR3args)         = 1;
      SETATTR3res
       NFSPROC3_SETATTR(SETATTR3args)         = 2;
      LOOKUP3res
       NFSPROC3_LOOKUP(LOOKUP3args)           = 3;
      ACCESS3res
       NFSPROC3_ACCESS(ACCESS3args)           = 4;
      READLINK3res
       NFSPROC3_READLINK(READLINK3args)       = 5;
      READ3res
       NFSPROC3_READ(READ3args)               = 6;
      WRITE3res
       NFSPROC3_WRITE(WRITE3args)             = 7;
      CREATE3res
       NFSPROC3_CREATE(CREATE3args)           = 8;
      MKDIR3res
       NFSPROC3_MKDIR(MKDIR3args)             = 9;
      SYMLINK3res
       NFSPROC3_SYMLINK(SYMLINK3args)         = 10;
      MKNOD3res
       NFSPROC3_MKNOD(MKNOD3args)             = 11;
      REMOVE3res
       NFSPROC3_REMOVE(REMOVE3args)           = 12;
      RMDIR3res
       NFSPROC3_RMDIR(RMDIR3args)             = 13;
      RENAME3res
       NFSPROC3_RENAME(RENAME3args)           = 14;
      LINK3res
       NFSPROC3_LINK(LINK3args)               = 15;
      READDIR3res
       NFSPROC3_READDIR(READDIR3args)         = 16;
      READDIRPLUS3res
       NFSPROC3_READDIRPLUS(READDIRPLUS3args)= 17;
      FSSTAT3res
       NFSPROC3_FSSTAT(FSSTAT3args)           = 18;
      FSINFO3res
       NFSPROC3_FSINFO(FSINFO3args)           = 19;
      PATHCONF3res
       NFSPROC3_PATHCONF(PATHCONF3args)       = 20;
      COMMIT3res
       NFSPROC3_COMMIT(COMMIT3args)           = 21;
   } = 3;
} = 100003;
```

Out of range (undefined) procedure numbers result in error. Refer to *[RFC1057]* for more detail.

General comments on attributes and consistency data on failure

For those procedures which return either **post_op_attr** or **wcc_data** structures on failure, note that the discriminated union may or may not contain the pre-operation attributes of the object or object parent directory. This depends on the error encountered and may also depend on the particular server implementation. Implementors are strongly encouraged to return as much attribute data as possible upon failure, but client implementors need to be aware that their implementation must correctly handle the variant return instance where no attributes or consistency data is returned.

General comments on file names

The following comments apply to all NFS version 3 protocol procedures in which the client provides one or more file names in the arguments: LOOKUP, CREATE, MKDIR, SYMLINK, MKNOD, REMOVE, RMDIR, RENAME, and LINK.

1. The file name must not be null, nor may it have the value "**.**" or "**..**".
2. If the file name is longer than the maximum for the file system (see PATHCONF **name_max**), the result depends on the value of the PATHCONF flag **no_trunc**. If **no_trunc** is FALSE, the file name will be truncated to **name_max** bytes. If **no_trunc** is TRUE, and the file name exceeds the server's file system maximum file name length the operation will fail with NFS3ERR_NAMETOOLONG.

See also comments in *File name component handling* on page 69.

Procedure 0 NULL

NULL: Do nothing

SYNOPSIS

```
void
NFSPROC3_NULL(void) = 0;
```

DESCRIPTION

Procedure `NULL` does not do any work. It is made available in all RPC services to allow server response testing and timing.

IMPLEMENTATION

It is important that this procedure do no work at all so that it can be used to measure the overhead of processing a service request. By convention, procedure 0 should never require any authentication. A server may choose to ignore this convention, in a more secure implementation, where responding to a procedure `0` call acknowledges the existence of a resource to an unauthenticated client.

ERRORS

Procedure 1 GETATTR

GETATTR: Get file attributes

SYNOPSIS

```
GETATTR3res
NFSPROC3_GETATTR(GETATTR3args) = 1;

struct GETATTR3args {
   nfs_fh3  object;
};

struct GETATTR3resok {
   fattr3   obj_attributes;
};

union GETATTR3res switch (nfsstat3 status) {
case NFS3_OK:
   GETATTR3resok  resok;
default:
   void;
};
```

DESCRIPTION

Procedure GETATTR retrieves the attributes for a specified file system object. The object is identified by the file handle that the server returned as part of a LOOKUP, CREATE, MKDIR, SYMLINK, MKNOD, or READDIRPLUS procedure (or from the MOUNT service, described elsewhere). On entry, the arguments in **GETATTR3args** are:

object The file handle of an object whose attributes are to be retrieved.

On successful return, **GETATTR3res.status** is NFS3_OK and **GETATTR3res.resok** contains:

obj_attributes The attributes for the object.

Otherwise, **GETATTR3res.status** contains the error on failure and no other results are returned.

IMPLEMENTATION

The attributes of file system objects is a point of major disagreement between different operating systems. Servers should make a best attempt to support all of the attributes in the **fattr3** structure so that clients can count on this as a common ground. Some mapping may be required to map local attributes to those in the **fattr3** structure.

Today, most client NFS version 3 protocol implementations implement a time-bounded attribute caching scheme to reduce over-the-wire attribute checks.

ERRORS

```
NFS3ERR_PERM
NFS3ERR_IO
NFS3ERR_NXIO
NFS3ERR_STALE
NFS3ERR_BADHANDLE
NFS3ERR_SERVERFAULT
```

SEE ALSO

CREATE, LOOKUP, and READDIRPLUS. The MOUNT service can also return file handles and is described elsewhere.

Procedure 2 SETATTR

SETATTR: Set file attributes

SYNOPSIS

```
SETATTR3res
NFSPROC3_SETATTR(SETATTR3args) = 2;

union sattrguard3 switch (bool check) {
case TRUE:
   nfstime3    obj_ctime;
case FALSE:
   void;
};

struct SETATTR3args {
   nfs_fh3     object;
   sattr3      new_attributes;
   sattrguard3 guard;
};

struct SETATTR3resok {
   wcc_data    obj_wcc;
};

struct SETATTR3resfail {
   wcc_data    obj_wcc;
};

union SETATTR3res switch (nfsstat3 status) {
case NFS3_OK:
   SETATTR3resok     resok;
default:
   SETATTR3resfail   resfail;
};
```

DESCRIPTION

Procedure SETATTR changes one or more of the attributes of a file system object on the server. The new attributes are specified by a **sattr3** structure. On entry, the arguments in **SETATTR3args** are:

object	The file handle for the object.
new_attributes	A **sattr3** structure containing booleans and enumerations describing the attributes to be set and the new values for those attributes.
guard	A **sattrguard3** union:
check	TRUE if the server is to verify that **guard.obj_ctime** matches the **ctime** for the object. FALSE otherwise.

A client may request that the server check that the object is in an expected state before performing the SETATTR operation. To do this, it sets the argument **guard.check** to TRUE and the client passes a time value in **guard.obj_ctime**. If **guard.check** is TRUE, the server must compare the value of **guard.obj_ctime** to the current **ctime** of the object. If the values are not equal, the server must not change the object attributes and must return a status of NFS3ERR_NOT_SYNC. If **guard.check** is FALSE, the server will not perform this check.

On successful return, **SETATTR3res.status** is NFS3_OK and **SETATTR3res.resok** contains:

obj_wcc A **wcc_data** structure containing the old and new attributes for the object.

Otherwise, **SETATTR3res.status** contains the error on failure and **SETATTR3res.resfail** contains the following:

obj_wcc A **wcc_data** structure containing the old and new attributes for the object.

IMPLEMENTATION

The **guard.check** mechanism allows the client to avoid changing the attributes of an object on the basis of stale attributes. It does **not** guarantee exactly-once semantics. In particular, if a reply is lost and the server does not detect the retransmission of the request, the procedure can fail with NFS3ERR_NOT_SYNC even though the attribute setting was previously performed successfully. The client can attempt to recover from this error by getting fresh attributes from the server and sending a new SETATTR request using the new **ctime**. The client can optionally check the attributes to avoid the second SETATTR request if the new attributes show that the attributes have already been set as desired (though it may not have been the issuing client which set the attributes).

The **new_attributes.size** field changes the size of a file. A value of 0 causes the file to be truncated, a value less than the current size of **file** causes data from new size to the end of the **file** to be discarded, and a size greater than the current size of **file** causes logically zeroed data bytes to be added to the end of file. Servers are free to implement this using holes or actual zero data bytes. Clients should not make any assumptions regarding a server's implementation of this feature, beyond that the bytes returned will be zeroed. Servers must support extending the file size via SETATTR.

SETATTR is not guaranteed atomic. A failed SETATTR may partially change a file's attributes.

Changing the size of a file with SETATTR indirectly changes the **mtime**. A client must account for this as size changes can result in data deletion.

If server and client times differ, programs that compare client time to file times can break. A time maintenance protocol should be used to limit client/server time skew.

ERRORS

NFS3ERR_PERM	
NFS3ERR_IO	
NFS3ERR_ACCES	
NFS3ERR_INVAL	An attempt was made to set a 32 bit **uid** or **gid** on a server which supports only 16 bit **uid**s and **gid**s. Or another mismatch of attribute and file type occurred.
NFS3ERR_ROFS	
NFS3ERR_DQUOT	
NFS3ERR_NOT_SYNC	**guard.check** was true, but **ctime**s failed comparison.
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_SERVERFAULT	

SEE ALSO

CREATE, LOOKUP, and READDIRPLUS which return file handles.

Procedure 3 LOOKUP

LOOKUP: Lookup file name

SYNOPSIS

```
LOOKUP3res
NFSPROC3_LOOKUP(LOOKUP3args) = 3;

struct LOOKUP3args {
   diropargs3  what;
};

struct LOOKUP3resok {
   nfs_fh3        object;
   post_op_attr   obj_attributes;
   post_op_attr   dir_attributes;
};

struct LOOKUP3resfail {
   post_op_attr   dir_attributes;
};

union LOOKUP3res switch (nfsstat3 status) {
case NFS3_OK:
   LOOKUP3resok   resok;
default:
   LOOKUP3resfail resfail;
};
```

DESCRIPTION

Procedure LOOKUP searches a directory for a specific name and returns the attributes and file handle for the corresponding file system object. On entry, the arguments in **LOOKUP3args** are:

what	Object to look up.
dir	The file handle for the directory to search.
name	The name to be searched for. Refer to *General comments on file names* on page 17.

On successful return, **LOOKUP3res.status** is NFS3_OK and **LOOKUP3res.resok** contains:

object	The file handle for the object corresponding to **what.name**.
obj_attributes	The attributes for the object corresponding to **what.name**.
dir_attributes	The attributes for the directory, **what.dir**, after the operation completed.

Otherwise, **LOOKUP3res.status** contains the error on failure and **LOOKUP3res.resfail** contains the following:

dir_attributes	The attributes for the directory, **what.dir**.

IMPLEMENTATION

At first glance, in the case where **what.name** refers to a mount point on the server two different replies seem possible. The server can return either the file handle for the underlying directory that is mounted on, or the file handle of the root of the mounted directory. This ambiguity is simply resolved. A server will only return the file handle for an exported local file system object. If a remote file system is mounted over a directory, the server will return the file handle for the underlying local directory. If a local file system is mounted over a directory, the server will return the file handle for the local file system covering the directory, if it is exported. Otherwise, it will return the file handle for the underlying directory. A given server implementation may refine these rules given capabilities or limitations particular to that

implementation. Refer to *[X/OpenNFS]* for a discussion on exporting file systems.

Two file names are distinguished, as in the NFS version 2 protocol. The name "`.`" is to be interpreted as referring to the directory itself, while "`..`" is to be interpreted as referring to the *parent* directory; *i.e.* the directory which includes the specified directory as a member. There is no facility for dealing with a multiparented directory and NFS assumes a hierarchical organization, organized as a single rooted tree.

ERRORS

NFS3ERR_PERM	
NFS3ERR_IO	
NFS3ERR_NOENT	Name was not found in directory.
NFS3ERR_ACCES	
NFS3ERR_NOTDIR	**what.dir** does not identify a directory.
NFS3ERR_NAMETOOLONG	The file name is longer than the maximum defined for the file system (see PATHCONF **name_max**) and the file system does not truncate names (see PATHCONF **no_trunc**).
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_SERVERFAULT	

SEE ALSO

Procedure 4 ACCESS

ACCESS: Check Access Permission

SYNOPSIS

```
ACCESS3res
NFSPROC3_ACCESS(ACCESS3args) = 4;

const ACCESS3_READ   = 0x0001;
const ACCESS3_LOOKUP = 0x0002;
const ACCESS3_MODIFY = 0x0004;
const ACCESS3_EXTEND = 0x0008;
const ACCESS3_DELETE = 0x0010;
const ACCESS3_EXECUTE= 0x0020;

struct ACCESS3args {
   nfs_fh3  object;
   uint32   access;
};

struct ACCESS3resok {
   post_op_attr   obj_attributes;
   uint32         access;
};

struct ACCESS3resfail {
   post_op_attr   obj_attributes;
};

union ACCESS3res switch (nfsstat3 status) {
case NFS3_OK:
   ACCESS3resok   resok;
default:
   ACCESS3resfail resfail;
};
```

DESCRIPTION

Procedure ACCESS determines the access rights which a user, as identified by the credentials in the request, has with respect to a file system object. The client encodes the set of permissions which are to be checked in a bit mask.The server checks the permissions encoded in the bit mask and returns a bit mask encoded with the permissions that the client is allowed, and a status of NFS3_OK.

The results of this procedure are necessarily advisory in nature. That is, NFS3_OK return does not imply that such access will be allowed to the file system object in the future, as access rights can be revoked by the server at any time.

On entry, the arguments in **ACCESS3args** are:

object	The file handle for the file system object to which access is to be checked.
access	A bit mask of access permissions to check.

The following access permissions may be requested:

ACCESS3_READ	Read data from file or read a directory.
ACCESS3_LOOKUP	Lookup a name in a directory.
ACCESS3_MODIFY	Rewrite existing file data or modify existing directory entries.
ACCESS3_EXTEND	Write new data or add directory entries.

ACCESS3_DELETE	Delete existing directory entry.
ACCESS3_EXECUTE	Execute file (no meaning for a directory).

On successful return, **ACCESS3res.status** is NFS3_OK. The server should return a status of NFS3_OK if no errors occurred or if the only error that occurred during processing was a *permission denied* error from doing one or more of the access checks. The results in **ACCESS3res.resok** are:

obj_attributes	The attributes of **object**.
access	A bit mask of access permissions indicating access rights for the authentication credentials provided with the request.

Otherwise, **ACCESS3res.status** contains the error on failure and **ACCESS3res.resfail** contains the following:

obj_attributes	The attributes of **object**—if access to attributes is permitted.

IMPLEMENTATION

In general, it is insufficient for the client to attempt to deduce this information by inspecting the **uid**, **gid**, and **mode** fields in the file attributes, since the server may perform uid or gid mapping or enforce additional access control restrictions. It is also possible that the NFS server may not be in the same ID space as the NFS client. In these cases (and perhaps others), the NFS client can not reliably perform an access check with only current file attributes.

In the NFS version 2 protocol, the only reliable way to determine whether an operation was allowed was to try it and see if it succeeded or failed. Using the ACCESS procedure, the client can ask the server to indicate whether or not one or more classes of operations are permitted. The ACCESS operation is provided to allow clients to do access checking before doing a series of operations. This is useful in operating systems (such as UNIX) where permission checking is done only when a file or directory is opened. The ACCESS procedure would also be called at *open(2)* of a file by the client to get similar behavior of access checking at open for a local file. This procedure is invoked by NFS client access procedure (called possibly through *access(2)*). The intent is to make the behavior of opening a remote file more consistent with the behavior of opening a local file.

The information returned by the server in response to an ACCESS call is not permanent. The server can revoke access permission at any time.

The client NFS machine should use the effective credentials of the user to build the authentication information in the ACCESS RPC request used to determine access rights. It is the effective user and group credentials which are used in subsequent read and write operations. See the comments in *Permission issues* on page 67 for more information on this topic.

Many implementations do not directly support the ACCESS3_DELETE permission. Operating systems like UNIX will ignore the ACCESS3_DELETE bit if set on an access request on a normal file. In these system, delete permission on a file is determined by the access permissions on the directory in which the file resides, instead of being determined by the mode of the file.

The ACCESS procedure is used to obtain both the results of the access check and current file attributes. For an implementation which frequently retrieves ACLs, ACCESS can be viewed as a GETATTR with additional information about a user's access rights, and which is used in place of GETATTR.

ERRORS

NFS3ERR_PERM
NFS3ERR_IO
NFS3ERR_NXIO
NFS3ERR_STALE
NFS3ERR_BADHANDLE
NFS3ERR_SERVERFAULT

SEE ALSO

GETATTR, SETATTR, READ, WRITE

Procedure 5 READLINK

READLINK: Read from symbolic link

SYNOPSIS

```
READLINK3res
NFSPROC3_READLINK(READLINK3args) = 5;

struct READLINK3args {
   nfs_fh3  symlink;
};

struct READLINK3resok {
   post_op_attr   symlink_attributes;
   nfspath3       data;
};

struct READLINK3resfail {
   post_op_attr   symlink_attributes;
};

union READLINK3res switch (nfsstat3 status) {
case NFS3_OK:
   READLINK3resok    resok;
default:
   READLINK3resfail  resfail;
};
```

DESCRIPTION

Procedure READLINK reads the data associated with a symbolic link. The data is an ASCII string which is opaque to the server. That is, whether created via NFS from a client or created locally on the server, the data in a symbolic link is not interpreted when created, but is simply stored. On entry, the arguments in **READLINK3args** are:

symlink The file handle for a symbolic link (file system object of type NF3LNK).

On successful return, **READLINK3res.status** is NFS3_OK and **READLINK3res.resok** contains:

data The data associated with the symbolic link.
symlink_attributes The attributes for the symbolic link.

Otherwise, **READLINK3res.status** contains the error on failure and **READLINK3res.resfail** contains the following:

symlink_attributes The attributes for the symbolic link.

IMPLEMENTATION

A symbolic link is nominally a pointer to another file. The **data** is not necessarily interpreted by the server, just stored in the file. It is possible for a client implementation to store a path name which is not meaningful to the server operating system in a symbolic link. A READLINK operation returns the **data** to the client for interpretation. If different implementations want to share access to symbolic links, then they must agree on the interpretation of the data in the symbolic link.

The READLINK operation is only allowed on objects of type NF3LNK.

ERRORS

NFS3ERR_PERM	
NFS3ERR_IO	
NFS3ERR_INVAL	**Symlink** is not a symbolic link (type NF3LNK). (Note: The X/Open XNFS Specification defined the error status in this case as NFSERR_NXIO. This appears to be inconsistent with existing server practice.)
NFS3ERR_ACCES	
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_NOTSUPP	
NFS3ERR_SERVERFAULT	

SEE ALSO

SYMLINK for information on how to create symbolic links, and LOOKUP and GETATTR for information on attributes.

Procedure 6 READ

READ: Read From file

SYNOPSIS

```
READ3res
NFSPROC3_READ(READ3args) = 6;

struct READ3args {
   nfs_fh3     file;
   offset3     offset;
   count3      count;
};

struct READ3resok {
   post_op_attr   file_attributes;
   count3         count;
   bool           eof;
   opaque         data<>;
};

struct READ3resfail {
   post_op_attr   file_attributes;
};

union READ3res switch (nfsstat3 status) {
case NFS3_OK:
   READ3resok     resok;
default:
   READ3resfail   resfail;
};
```

DESCRIPTION

Procedure READ reads data from a file.

On entry, the arguments in **READ3args** are:

file	The file handle for the file from which data is to be read. This must identify a file system object of type NF3REG.
offset	The position within the file at which the read is to begin. An **offset** of 0 means read data starting at the beginning of the file. If **offset** is greater than or equal to the size of the file, the status NFS3_OK is returned with **count** set to 0 and **eof** set to TRUE.
count	The number of bytes of data which are to be read. The server may elect to return fewer bytes than requested. If **count** is 0, the READ will succeed and return 0 bytes of data. The size of **data** must be less than or equal to the value of the **rtmax** field in the FSINFO reply structure for the file system which contains **file**. If greater, the server may return **rtmax** bytes, resulting in a short read.

On successful return, **READ3res.status** is NFS3_OK and **READ3res.resok** contains:

file_attributes	The attributes of the file on completion of the read.
count	The number of bytes of data returned by the read.
eof	If the read ended at the end-of-file (formally, in a correctly formed READ request, if **READ3args.offset** plus **READ3resok.count** is equal to the size of the

file), **eof** is returned as TRUE; otherwise it is FALSE. A successful READ of an empty file will always return **eof** as TRUE.

data The counted data read from the file.

Otherwise, **READ3res.status** contains the error on failure and **READ3res.resfail** contains the following:

file_attributes The attributes of the file.

IMPLEMENTATION

The **nfsdata** type used for the READ and WRITE operations in the NFS version 2 protocol defining the data portion of a request or reply has been changed to a variable length opaque byte array. The maximum size allowed by the protocol is now limited by what XDR and underlying transports will allow. Consult the procedure FSINFO description for details.

It is poossible for the server to return fewer than **count** bytes of data. If the server returns less than the **count** requested, the client should issue another READ to get the remaining data. A server may return less data than requested under several circumstances. The file may have been truncated by another client or perhaps on the server itself, changing the file size from what the requesting client believes to be the case. This would reduce the actual amount of data available to the client. It is possible that the server may back off the transfer size and reduce the read request return. Server resource exhaustion may also occur necessitating a smaller read return.

Some NFS version 2 protocol server implementations returned fewer than the bytes requested which clients chose to interpret as an EOF. The addition of the **eof** flag in the NFS version 3 protocol provides a correct way of handling EOF.

Some NFS version 2 protocol server implementations incorrectly returned NFSERR_ISDIR if the file system object type was not a regular file. The correct return value is NFS3ERR_INVAL.

ERRORS

NFS3ERR_PERM	
NFS3ERR_IO	
NFS3ERR_NXIO	
NFS3ERR_ACCES	
NFS3ERR_INVAL	**File** is not file type NF3REG.
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_SERVERFAULT	

SEE ALSO

Procedure 7 WRITE

WRITE: Write to file

SYNOPSIS

```
WRITE3res
NFSPROC3_WRITE(WRITE3args) = 7;

struct WRITE3args {
   nfs_fh3  file;
   offset3  offset;
   count3   count;
   bool     stable;
   opaque   data<>;
};

struct WRITE3resok {
   wcc_data    file_wcc;
   count3      count;
   bool        committed;
   writeverf3  verf;
};

struct WRITE3resfail {
   wcc_data    file_wcc;
};

union WRITE3res switch (nfsstat3 status) {
case NFS3_OK:
   WRITE3resok    resok;
default:
   WRITE3resfail  resfail;
};
```

DESCRIPTION

Procedure WRITE writes data to a file. On entry, the arguments in **WRITE3args** are:

file	The file handle for the file to which data is to be written. This must identify a file system object of type NF3REG.
offset	The position within the file at which the write is to begin. An **offset** of 0 means write data starting at the beginning of the file.
count	The number of bytes of data that are to be written. If **count** is 0, the WRITE will succeed and return a **count** of 0, barring errors due to permissions checking. The server may elect to write fewer bytes than requested. The size of **data** must be less than or equal to the value of the **wtmax** field in the FSINFO reply structure for the file system that contains **file**. If greater, the server may write **wtmax** bytes, resulting in a short write.
stable	If **stable** is TRUE, the server **must** commit the data written (plus all file system metadata such as inode and indirect blocks in the UNIX operating system) to stable storage before returning results. This corresponds to the NFS version 2 protocol semantics. Any other behavior constitutes a protocol violation. If **stable** is FALSE, the server is free to commit any part of the data to stable storage, including all or none, before returning a reply to the client. There is no guarantee whether or when any uncommitted data will subsequently be committed to stable storage.

The only guarantee made by the server is that it will not destroy any data without changing the value of **verf**. See the discussion on COMMIT for more information on if and when data is committed to stable storage.

data The counted data to be written to the file.

On successful return, **WRITE3res.status** is NFS3_OK and **WRITE3res.resok** contains:

file_wcc Weak cache consistency data for the file. For a client that requires only the post-write file attributes, these can be found in **file_wcc.after**.

count The number of bytes of data written to the file. The server may elect to write fewer bytes than requested. If so, the actual count of bytes written starting at location **offset** is returned in this field.

committed If the server committed all data and metadata to stable storage, **committed** is returned as TRUE. If any part of the data and metadata was not so committed, **committed** must be returned as FALSE. If the **WRITE3args.stable** was TRUE, then **WRITE3res.committed** must be TRUE: anything else constitutes a protocol violation. If the **WRITE3args.stable** argument was FALSE, then **WRITE3res.committed** may be TRUE or FALSE.

verf This is a cookie that the client can use to determine whether the server has rebooted between a call to WRITE and a subsequent call to COMMIT. This cookie must be consistent during a single boot session and must be unique between instances of the NFS server (where uncommitted data may be lost).

Otherwise, **WRITE3res.status** contains the error on failure and **WRITE3res.resfail** contains the following:

file_wcc Weak cache consistency data for the file. For a client that requires only the post-write file attributes, these can be found in **file_wcc.after**. Note that even though the write failed, full **wcc_data** is returned to allow the client to determine whether the failed write resulted in any change to the file.

If a client writes data to the server with the **stable** bit FALSE, and the reply yields a **committed** bit of FALSE, the client will follow up some time in the future with a COMMIT operation to synchronize outstanding asynchronous data with the server's stable storage, barring client error. It is possible that due to client crash or other error that a subsequent COMMIT will not be received by the server.

IMPLEMENTATION

The **nfsdata** type used for the READ and WRITE operations in the NFS version 2 protocol defining the data portion of a request or reply has been changed to a variable length opaque byte array. The maximum size allowed by the protocol is now limited by what XDR and underlying transports will allow. Consult the procedure FSINFO description for details.

It is possible for the server to write fewer than **count** bytes of data. If the server writes less than the **count** requested, the client should issue another WRITE to write the remaining data.

It is assumed that the act of writing data to a file will cause the **mtime** of the file to be updated. However, the **mtime** of the file should not be changed unless the contents of the file are changed. Thus, a WRITE request with **count** set to 0 should not cause the **mtime** of the file to be updated.

The NFS version 3 protocol introduces *safe asynchronous writes*. The combination of WRITE with the stable flag clear followed by a COMMIT addresses the performance bottleneck found in the NFS version 2 protocol, the need to synchronously commit all writes to stable storage.

The definition of stable storage has been historically a point of contention. The following expected properties of stable storage may help in resolving design issues in the implementation. Stable storage is persistent storage that survives:

1. Repeated power failures.
2. Hardware failures (of any board, power supply, *etc.*).
3. Repeated software crashes, including reboot cycle.

This definition does not cover failure of the stable storage module itself.

A cookie, **verf**, is defined to allow a client to detect different instances of an NFS server over which cached, uncommitted data may be lost. In the most likely case, the cookie result allows the client to detect server reboots. This information is required so that the client can safely determine whether the server may have lost cached data. If the server fails unexpectedly and the client has uncommitted data from previous WRITE requests (done with the **stable** bit not set and in which the return flag **committed** was returned as FALSE) it may not have flushed cached data to stable storage. The burden of recovery is on the client and the client will need to retransmit the data to the server.

A suggested **verf** cookie would be to use the time that the server was booted or the time the server was last started (if restarting the server without a reboot results in lost buffers).

Note that the semantics of the WRITE procedure with the **stable** argument set to TRUE corresponds to NFS version 2 protocol semantics. If the server receives a request with **stable** set to TRUE, it must commit the data and metadata to stable storage before returning. It should set the **committed** field in the results to TRUE. Any other action is a protocol violation. If the server receives a request with **stable** set to FALSE, it is free to either commit the data and metadata to stable storage or not. It should return an indication of its action through the **committed** field in the result. If any of the data or metadata has not been flushed to stable storage, the **committed** field should be set to FALSE. The one restriction on the server is that it must not invalidate the data before flushing it to stable storage without changing the value of **verf**. It is assumed that most clients will use WRITE with **stable** set to FALSE and follow with a COMMIT. However, on a POSIX-conforming system, files opened with O_SYNC will probably need to be written using WRITE with **stable** set to TRUE.

The **committed** field in the results allows the client to do more effective caching. If the server is committing all WRITE requests to stable storage, then it should return with **committed** set to TRUE, regardless of the value of the **stable** field in the arguments. A server which uses an NVRAM accelerator may choose to implement this policy. The client can use this to increase the effectiveness of the cache by not having to retain cached data which has already been committed on the server.

Some implementations may return NFS3ERR_NOSPC instead of NFS3ERR_DQUOT when a user's quota is exceeded.

See additional comments under the COMMIT procedure description.

ERRORS

NFS3ERR_IO	
NFS3ERR_ACCES	
NFS3ERR_FBIG	The WRITE operation would cause **file** to become too large.
NFS3ERR_DQUOT	The operation would exceed a user's space quota.
NFS3ERR_NOSPC	The file system that contains **file** is full.
NFS3ERR_ROFS	The file system that contains **file** is read-only.
NFS3ERR_INVAL	**File** is not a regular file.
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_SERVERFAULT	

SEE ALSO

COMMIT for additional information on asynchronous writes.

Procedure 8 CREATE

CREATE: Create a file

SYNOPSIS

```
CREATE3res
NFSPROC3_CREATE(CREATE3args) = 8;

enum createmode3 {
   UNCHECKED = 0,
   GUARDED = 1,
   EXCLUSIVE = 2
};

union createhow3 switch (createmode3 mode) {
case UNCHECKED:
case GUARDED:
   sattr3         obj_attributes;
case EXCLUSIVE:
   createverf3    verf;
};

struct CREATE3args {
   diropargs3  where;
   createhow3  how;
};

struct CREATE3resok {
   post_op_fh3    obj;
   post_op_attr   obj_attributes;
   wcc_data       dir_wcc;
};

struct CREATE3resfail {
   wcc_data    dir_wcc;
};

union CREATE3res switch (nfsstat3 status) {
case NFS3_OK:
   CREATE3resok   resok;
default:
   CREATE3resfail resfail;
};
```

DESCRIPTION

Procedure CREATE creates a new regular file. On entry, the arguments in **CREATE3args** are:

where	Where the object is to be created:
dir	The file handle for the directory in which the object is to be created.
name	The name that is to be associated with the created object. Refer to *General comments on file names* on page 17.

When creating a regular file, there are three ways to create the file as defined by:

how	A union defining how the server is to handle the file creation, together with any

appropriate attributes:

mode One of UNCHECKED, GUARDED, and EXCLUSIVE. UNCHECKED means that the file should be created without checking for the existence of a duplicate file in the same directory. In this case, **how.obj_attributes** is a **sattr3** describing the initial attributes for the file. GUARDED specifies that the server should check for the presence of a duplicate file before performing the create, and should fail the request with NFS3ERR_EXIST if a duplicate file exists. If the file does not exist, the request is performed as described for UNCHECKED. EXCLUSIVE specifies that the server is to follow the exclusive creation semantics, using the verifier to ensure exclusive creation of the target. No attributes may be provided in this case, since the server may use the target file metadata to store the **createverf3** verifier. See additional comments below.

On successful return, **CREATE3res.status** is NFS3_OK and the results in **CREATE3res.resok** are:

obj The file handle for the newly created regular file.

obj_attributes The attributes for the regular file just created.

dir_wcc Weak cache consistency data for the directory, **where.dir**. For a client that requires on the post-CREATE directory attributes, these can be found in **dir_wcc.after**.

Otherwise, **CREATE3res.status** contains the error on failure and **CREATE3res.resfail** contains the following:

dir_wcc Weak cache consistency data for the directory, **where.dir**. For a client that requires only the post-CREATE directory attributes, these can be found in **dir_wcc.after**. Even though the CREATE failed, full **wcc_data** is returned to allow the client to determine whether the failing CREATE resulted in any change to the directory.

IMPLEMENTATION

Unlike NFS version 2 protocol, in which certain fields in the initial attributes structure were overloaded to indicate creation of devices and FIFOs in addition to regular files, this procedure only supports the creation of regular files. The MKNOD procedure was introduced in the NFS version 3 protocol to handle creation of devices and FIFOs. Implementations have no reason in the NFS version 3 protocol to overload CREATE semantics.

One aspect of the NFS version 3 protocol CREATE procedure warrants particularly careful consideration: the mechanism introduced to support the reliable exclusive creation of regular files. The mechanism comes into play when **how.mode** is EXCLUSIVE. In this case, **how.verf** contains a verifier which can reasonably be expected to be unique. A combination of a client identifier, perhaps the client IP address, and a unique number generated by the client, perhaps the NFS RPC transaction identifier, may be appropriate.

If the file does not exist, the server creates the file and stores the verifier on stable storage. For file systems which do not provide a mechanism for the storage of arbitrary file attributes, the server may use one or more elements of the file metadata to store the verifier. The verifier must be stored on stable storage to prevent erroneous failure on retransmission of the request. It is assumed that an exclusive create is being performed because the exclusive semantics are critical to the application. For example, a lock file for synchronization is being created. Because of the expected usage, it was deemed insufficient to rely solely on the normally volatile reply cache for storage of the verifier. The reply cache in volatile storage does not survive a crash and may actually flush on a long network partition, opening failure windows. In the UNIX local file system environment, the expected storage location for the verifier on creation is the metadata (time stamps) of the file. For this reason, an exclusive file create may not include initial attributes because the server would have nowhere to store the verifier.

If the server can not support these exclusive create semantics because of the requirement to commit the verifier to stable storage, it should fail the CREATE request with the error, NFS3ERR_NOTSUPP.

If the file already exists, the server reconstructs the file's verifier and compares it with the verifier in the request. If they match, the server treats the request as a success. The request is presumed to be a duplicate of an earlier, successful

request for which the reply was lost and which the server duplicate request cache mechanism did not detect. If the verifiers do not match, the request is rejected with the status NFS3ERR_EXIST.

Once the client has performed a successful exclusive create, it must issue a SETATTR to set the correct file attributes. Until it does so, it should not rely upon any of the file attributes, since the server implementation may need to overload file metadata to store the verifier.

Use of the GUARDED attribute does **not** provide exactly-once semantics. In particular, if a reply is lost and the server does not detect the retransmission of the request, the procedure can fail with NFS3ERR_EXIST even though the create was performed successfully.

Refer to *General comments on file names* on page 17.

ERRORS

NFS3ERR_PERM	
NFS3ERR_IO	
NFS3ERR_ACCES	File name is illegal (contains illegal characters) for the target file system.
NFS3ERR_EXIST	The (possibly truncated) **where.name** already exists in **where.dir**. This error can occur only if **how.mode** is GUARDED or EXCLUSIVE. Or the exclusive create verifier does not match in operation.
NFS3ERR_NOTDIR	**Where.dir** is not a directory.
NFS3ERR_NOSPC	The file system that contains **where.dir** is full.
NFS3ERR_ROFS	The file system that contains **where.dir** is read-only.
NFS3ERR_NAMETOOLONG	**Where.name** is longer than the maximum for the file system and **no_trunc** is TRUE.
NFS3ERR_DQUOT	
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_SERVERFAULT	

SEE ALSO

LOOKUP, MKNOD, SYMLINK, MKDIR

Procedure 9 MKDIR

MKDIR: Create a directory

SYNOPSIS

```
MKDIR3res
NFSPROC3_MKDIR(MKDIR3args) = 9;

struct MKDIR3args {
   diropargs3  where;
   sattr3      attributes;
};

struct MKDIR3resok {
   post_op_fh3    obj;
   post_op_attr   obj_attributes;
   wcc_data       dir_wcc;
};

struct MKDIR3resfail {
   wcc_data    dir_wcc;
};

union MKDIR3res switch (nfsstat3 status) {
case NFS3_OK:
   MKDIR3resok    resok;
default:
   MKDIR3resfail  resfail;
};
```

DESCRIPTION

Procedure MKDIR creates a new subdirectory in a directory. On entry, the arguments in **MKDIR3args** are:

where	Where the subdirectory is to be created:
dir	The file handle for the directory in which the subdirectory is to be created.
name	The name that is to be associated with the created object. Refer to *General comments on file names* on page 17.
attributes	The initial attributes for the subdirectory.

On successful return, **MKDIR3res.status** is NFS3_OK and the results in **MKDIR3res.resok** are:

obj	The file handle for the newly created directory.
obj_attributes	The attributes for the newly created subdirectory.
dir_wcc	Weak cache consistency data for the directory, **where.dir**. For a client that requires only the post-MKDIR directory attributes, these can be found in **dir_wcc.after**

Otherwise, **MKDIR3res.status** contains the error on failure and **MKDIR3res.resfail** contains the following:

dir_wcc	Weak cache consistency data for the directory, **where.dir**. For a client that requires only the post-MKDIR directory attributes, these can be found in **dir_wcc.after**. Even though the MKDIR failed, full **wcc_data** is returned to allow the client to determine whether the failing MKDIR resulted in any change to the directory.

IMPLEMENTATION

Refer to *General comments on file names* on page 17.

ERRORS

NFS3ERR_PERM	
NFS3ERR_IO	
NFS3ERR_ACCES	File name is illegal (contains illegal characters) for the target file system.
NFS3ERR_EXIST	"**.**" or "**..**" was specified as the subdirectory to create or another name collision occurred.
NFS3ERR_NOTDIR	**Where.dir** is not a directory.
NFS3ERR_NOSPC	The file system that contains **where.dir** is full.
NFS3ERR_ROFS	The file system that contains **where.dir** is read-only.
NFS3ERR_NAMETOOLONG	**Where.name** is longer than the maximum for the file system and **no_trunc** is TRUE.
NFS3ERR_DQUOT	
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_SERVERFAULT	
NFS3ERR_BADTYPE	A server may not support creation of directories.

SEE ALSO

LOOKUP, CREATE, MKNOD, SYMLINK

Procedure 10 SYMLINK

SYMLINK: Create a symbolic link

SYNOPSIS

```
SYMLINK3res
NFSPROC3_SYMLINK(SYMLINK3args) = 10;

struct symlinkdata3 {
   sattr3   symlink_attributes;
   nfspath3 symlink_data;
};

struct SYMLINK3args {
   diropargs3     where;
   symlinkdata3   symlink;
};

struct SYMLINK3resok {
   post_op_fh3    obj;
   post_op_attr   obj_attributes;
   wcc_data       dir_wcc;
};

struct SYMLINK3resfail {
   wcc_data    dir_wcc;
};

union SYMLINK3res switch (nfsstat3 status) {
case NFS3_OK:
   SYMLINK3resok     resok;
default:
   SYMLINK3resfail   resfail;
};
```

DESCRIPTION

Procedure SYMLINK creates a new file system object of type symbolic link in a directory. On entry, the arguments in **SYMLINK3args** are:

where	Where the symbolic link is to be created:
dir	The file handle for the directory in which the symbolic link is to be created.
name	The name that is to be associated with the created object. Refer to *General comments on file names* on page 17.
symlink	The symbolic link to create:
symlink_attributes	The initial attributes for the symbolic link.
symlink_data	The string containing the symbolic link data.

On successful return, **SYMLINK3res.status** is NFS3_OK and **SYMLINK3res.resok** contains:

obj	The file handle for the newly created symbolic link.
obj_attributes	The attributes for the newly created symbolic link.
dir_wcc	Weak cache consistency data for the directory, **where.dir**. For a client that requires only the post-SYMLINK directory attributes, these can be found in **dir_wcc.after**.

Otherwise, **SYMLINK3res.status** contains the error on failure and **SYMLINK3res.resfail** contains the following:

dir_wcc Weak cache consistency data for the directory, **where.dir**. For a client that requires only the post-SYMLINK directory attributes, these can be found in **dir_wcc.after**. Even though the SYMLINK failed, full **wcc_data** is returned to allow the client to determine whether the failing SYMLINK resulted in any change to the directory.

IMPLEMENTATION

Refer to *General comments on file names* on page 17.

For symbolic links, the actual file system node and its contents are expected to be created in one single atomic operation. That is, once the symbolic link is visible, there must not be a window where a READLINK would fail or return incorrect data.

ERRORS

NFS3ERR_PERM	
NFS3ERR_IO	
NFS3ERR_ACCES	File name is illegal (contains illegal characters) for the target file system.
NFS3ERR_EXIST	There is already an entry in the directory corresponding to the name of the symbolic link to be created.
NFS3ERR_NOTDIR	**Where.dir** is not a directory.
NFS3ERR_NOSPC	The file system that contains **where.dir** is full.
NFS3ERR_ROFS	The file system that contains **where.dir** is read-only.
NFS3ERR_NAMETOOLONG	**Where.name** is longer than the maximum for the file system and **no_trunc** is TRUE.
NFS3ERR_DQUOT	
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_NOTSUPP	The server does not support symbolic links.
NFS3ERR_SERVERFAULT	

SEE ALSO

READLINK, CREATE, MKNOD, MKDIR, LOOKUP

Procedure 11 MKNOD

MKNOD: Create a special device

SYNOPSIS

```
MKNOD3res
NFSPROC3_MKNOD(MKNOD3args) = 11;

struct devicedata3 {
   sattr3      dev_attributes;
   specdata3   spec;
};

union mknoddata3 switch (ftype3 type) {
case NF3CHR:
case NF3BLK:
   devicedata3 device;
case NF3SOCK:
case NF3FIFO:
   sattr3      pipe_attributes;
default:
   void;
};

struct MKNOD3args {
   diropargs3  where;
   mknoddata3  what;
};

struct MKNOD3resok {
   post_op_fh3    obj;
   post_op_attr   obj_attributes;
   wcc_data       dir_wcc;
};

struct MKNOD3resfail {
   wcc_data    dir_wcc;
};

union MKNOD3res switch (nfsstat3 status) {
case NFS3_OK:
   MKNOD3resok    resok;
default:
   MKNOD3resfail  resfail;
};
```

DESCRIPTION

Procedure MKNOD creates a new file system object of type *special* in a directory. Special files can be, for example, device files or named pipes. On entry, the arguments in **MKNOD3args** are:

where	Where the special file is to be created:
dir	The file handle for the directory in which the subdirectory is to be created.
name	The name that is to be associated with the created object. Refer to *General comments on file names* on page 17.

what	A union identifying the type of object to be created, together with the data and attributes appropriate to the type of object:
type	The type of the object to be created.

When creating a character special file (**what.type** is NF3CHR) or a block special file (**what.type** is NF3BLK), **what** includes:

device	A structure **devicedata3** with the following components:
dev_attributes	The initial attributes for the special file.
spec	The major/minor pair in **device.spec.specdata1** and **device.spec.specdata2** respectively.

When creating a UNIX-mode socket (**what.type** is NF3SOCK) or a FIFO (**what.type** is NF3FIFO), **what** includes:

pipe_attributes	The initial attributes for the file.

On successful return, **MKNOD3res.status** is NFS3_OK and **MKNOD3res.resok** contains:

obj	The file handle for the newly created special file.
obj_attributes	The attributes for the newly created special file.
dir_wcc	Weak cache consistency data for the directory, **where.dir**. For a client that requires only the post-MKNOD directory attributes, these can be found in **dir_wcc.after**.

Otherwise, **MKNOD3res.status** contains the error on failure and **MKNOD3res.resfail** contains the following:

dir_wcc	Weak cache consistency data for the directory, **where.dir**. For a client that requires only the post-MKNOD directory attributes, these can be found in **dir_wcc.after**. Even though the MKNOD failed, full **wcc_data** is returned to allow the client to determine whether the failing MKNOD resulted in any change to the directory.

IMPLEMENTATION

Refer to *General comments on file names* on page 17.

Without explicit support for special file type creation in the NFS version 2 protocol, fields in the CREATE argument fields were overloaded to indicate creation of certain types of objects. This overloading is no longer necessary.

ERRORS

NFS3ERR_PERM	
NFS3ERR_IO	
NFS3ERR_ACCES	File name is illegal (contains illegal characters) for the target file system.
NFS3ERR_EXIST	There is already an entry in the directory corresponding to the name of the object to create.
NFS3ERR_NOTDIR	**Where.dir** is not a directory.
NFS3ERR_NOSPC	The file system that contains **where.dir** is full.
NFS3ERR_ROFS	The file system that contains **where.dir** is read-only.
NFS3ERR_NAMETOOLONG	**Where.name** is longer than the maximum for the file system and **no_trunc** is TRUE.
NFS3ERR_DQUOT	
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_NOTSUPP	The server does not support any of the defined types.
NFS3ERR_SERVERFAULT	
NFS3ERR_BADTYPE	**What.type** is not supported on this server or is not a legal type. NF3REG is an illegal type for MKNOD.

SEE ALSO

Procedure 12 REMOVE

REMOVE: Remove a File

SYNOPSIS

```
REMOVE3res
NFSPROC3_REMOVE(REMOVE3args) = 12;

struct REMOVE3args {
   diropargs3  object;
};

struct REMOVE3resok {
   wcc_data    dir_wcc;
};

struct REMOVE3resfail {
   wcc_data    dir_wcc;
};

union REMOVE3res switch (nfsstat3 status) {
case NFS3_OK:
   REMOVE3resok   resok;
default:
   REMOVE3resfail resfail;
};
```

DESCRIPTION

Procedure REMOVE removes (deletes) an entry from a directory. If the entry in the directory was the last reference to the corresponding file system object, the object may be destroyed. On entry, the arguments in **REMOVE3args** are:

object A **diropargs3** structure identifying the directory entry to be removed:

dir The file handle for the directory from which the entry is to be removed. The file system object must be of type NF3DIR.

name The name of the entry to be removed. Refer to *General comments on file names* on page 17.

On successful return, **REMOVE3res.status** is NFS3_OK and **REMOVE3res.resok** contains:

dir_wcc Weak cache consistency data for the directory, **object.dir**. For a client that requires only the post-REMOVE directory attributes, these can be found in **dir_wcc.after**.

Otherwise, **REMOVE3res.status** contains the error on failure and **REMOVE3res.resfail** contains the following:

dir_wcc Weak cache consistency data for the directory, **object.dir**. For a client that requires only the post-REMOVE directory attributes, these can be found in **dir_wcc.after**. Even though the REMOVE failed, full **wcc_data** is returned to allow the client to determine whether the failing REMOVE resulted in any change to the directory.

IMPLEMENTATION

In general, REMOVE is intended to remove non-directory file objects and RMDIR is to be used to remove directories. However, REMOVE can be used to remove directories, subject to restrictions imposed by either the client or server architecture. This had been a source of confusion in the NFS version 2 protocol.

The concept of *last reference* is server specific. However, if the **nlink** field in the previous attributes of the object had the value 1, the client should not rely on being able to refer to the object via a file handle. Likewise, the client should not rely on the resources (disk space, directory entry, *etc.*) formerly associated with the object becoming immediately available. Thus, if a client needs to be able to continue to access a file after using REMOVE to remove it, the client should take steps to make sure that the file will still be accessible. The usual mechanism used is to use RENAME to rename the file from its old name to a new *hidden* name.

Refer to *General comments on file names* on page 17.

ERRORS

NFS3ERR_PERM	
NFS3ERR_NOENT	The directory does not contain an entry with the (possibly truncated) name **object.name**.
NFS3ERR_IO	
NFS3ERR_ACCES	
NFS3ERR_NOTDIR	**Object.dir** is not a directory.
NFS3ERR_NAMETOOLONG	**Object.name** is longer than the maximum for the file system and **no_trunc** is TRUE.
NFS3ERR_ROFS	The file system that contains **object.dir** is read-only.
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_SERVERFAULT	

SEE ALSO

CREATE

Procedure 13 RMDIR

RMDIR: Remove a Directory

SYNOPSIS

```
RMDIR3res
NFSPROC3_RMDIR(RMDIR3args) = 13;

struct RMDIR3args {
   diropargs3  object;
};

struct RMDIR3resok {
   wcc_data    dir_wcc;
};

struct RMDIR3resfail {
   wcc_data    dir_wcc;
};

union RMDIR3res switch (nfsstat3 status) {
case NFS3_OK:
   RMDIR3resok    resok;
default:
   RMDIR3resfail  resfail;
};
```

DESCRIPTION

Procedure RMDIR removes (deletes) a subdirectory from a directory. If the directory entry is the last reference to the corresponding directory object, the object may be destroyed. On entry, the arguments in **RMDIR3args** are:

object	A **diropargs3** structure identifying the directory entry to be removed:
dir	The file handle for the directory from which the entry is to be removed. The file system object must be of type NF3DIR.
name	The name of the entry to be removed. Refer to *General comments on file names* on page 17.

On successful return, **RMDIR3res.status** is NFS3_OK and **RMDIR3res.resok** contains:

dir_wcc	Weak cache consistency data for the directory, **object.dir**. For a client that requires only the post-RMDIR directory attributes, these can be found in **dir_wcc.after**.

Otherwise, **RMDIR3res.status** contains the error on failure and **RMDIR3res.resfail** contains the following:

dir_wcc	Weak cache consistency data for the directory, **object.dir**. For a client that requires only the post-RMDIR directory attributes, these can be found in **dir_wcc.after**. Note that even though the RMDIR failed, full **wcc_data** is returned to allow the client to determine whether the failing RMDIR resulted in any change to the directory.

IMPLEMENTATION

Note that on UNIX servers, removal of a non-empty directory is disallowed.

See *IMPLEMENTATION* on page 42 for comments on handling *last reference*.

ERRORS

NFS3ERR_PERM	
NFS3ERR_NOENT	The directory does not contain an entry with the (possibly truncated) name **object.name**.
NFS3ERR_IO	
NFS3ERR_ACCES	
NFS3ERR_INVAL	**Object.name** is "**.**".
NFS3ERR_EXIST	**Object.name** is "**..**".
NFS3ERR_NOTDIR	**Object.dir** is not a directory or **object.name** does not refer to a directory.
NFS3ERR_NAMETOOLONG	**Object.name** is longer than the maximum for the file system and **no_trunc** is TRUE.
NFS3ERR_ROFS	The file system that contains **object.dir** is read-only.
NFS3ERR_NOTEMPTY	The server will only remove empty directories and **object.name** is a directory that is not empty.
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_SERVERFAULT	

SEE ALSO

The REMOVE procedure.

Procedure 14 RENAME

RENAME: Rename a File or Directory

SYNOPSIS

```
RENAME3res
NFSPROC3_RENAME(RENAME3args) = 14;

struct RENAME3args {
   diropargs3  from;
   diropargs3  to;
};

struct RENAME3resok {
   wcc_data    fromdir_wcc;
   wcc_data    todir_wcc;
};

struct RENAME3resfail {
   wcc_data    fromdir_wcc;
   wcc_data    todir_wcc;
};

union RENAME3res switch (nfsstat3 status) {
case NFS3_OK:
   RENAME3resok   resok;
default:
   RENAME3resfail resfail;
};
```

DESCRIPTION

Procedure RENAME renames the file identified by **from.name** in the directory, **from.dir**, to **to.name** in the directory, **to.dir**. The operation is required to be atomic on the server. **To.dir** and **from.dir** must reside on the same file system on the server. On entry, the arguments in **RENAME3args** are:

from	A **diropargs3** structure identifying the source (the file system object to be renamed):
from.dir	The file handle for the directory from which the entry is to be removed.
from.name	The name of the entry that identifies the object to be renamed. Refer to *General comments on file names* on page 17.
to	A **diropargs3** structure identifying the target (the new name for the object):
to.dir	The file handle for the directory where the new entry is to be created.
to.name	The new name for the object. Refer to *General comments on file names* on page 17.

If the directory, **to.dir**, already contains an entry with the (possibly truncated) **to.name**, the source object must be compatible with the target: either both are non-directories or both are directories and the target must be empty. If compatible, the existing target is removed before the rename occurs.

On successful return, **RENAME3res.status** is NFS3_OK and **RENAME3res.resok** contains:

fromdir_wcc	Weak cache consistency data for the directory, **from.dir**.
todir_wcc	Weak cache consistency data for the directory, **to.dir**.

Otherwise, **RENAME3res.status** contains the error on failure and **RENAME3res.resfail** contains the following:

fromdir_wcc	Weak cache consistency data for the directory, **from.dir**.
todir_wcc	Weak cache consistency data for the directory, **to.dir**.

IMPLEMENTATION

The RENAME operation must be atomic on the server. That "**to.dir** and **from.dir** must reside on the same file system on the server, [or the operation will fail]" means that the **fsid** fields in the attributes for the directories are the same. If they reside on different file systems, the error NFS3ERR_XDEV is returned. Even though the operation is atomic, the status NFS3ERR_MLINK may be returned if the server used a "link/unlink" sequence internally.

A file handle may or may not become stale on a rename. However, server implementors are **strongly** encouraged to attempt to keep file handles from becoming stale in this fashion.

Refer to *General comments on file names* on page 17.

ERRORS

NFS3ERR_NOENT	The directory, **from.dir**, does not contain an entry with the (possibly truncated) name, **from.name**, or **to.dir** does not exist.
NFS3ERR_IO	
NFS3ERR_ACCES	
NFS3ERR_EXIST	**To.name** already exists in **to.dir**. See comments in *DESCRIPTION* above.
NFS3ERR_XDEV	**To.dir** and **from.dir** reside on different file systems on the server.
NFS3ERR_NOTDIR	**From.dir** or **to.dir** is not a directory (type NF3DIR).
NFS3ERR_ISDIR	
NFS3ERR_INVAL	**From.name** or **to.name** is "**.**" or "**..**", or the entry is an alias for **from.dir**.
NFS3ERR_NOSPC	The file system that contains **to.dir** is full.
NFS3ERR_ROFS	The file system that contains **from.dir** or **to.dir** is read-only.
NFS3ERR_MLINK	Even though the operation is atomic, this error may occur if the server used a link/unlink sequence internally.
NFS3ERR_NAMETOOLONG	**From.name** or **to.name** is longer than the maximum for the file system and **no_trunc** is TRUE.
NFS3ERR_NOTEMPTY	
NFS3ERR_DQUOT	
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_NOTSUPP	
NFS3ERR_SERVERFAULT	

SEE ALSO

LINK

Procedure 15 LINK

LINK: Create Link to an object

SYNOPSIS

```
LINK3res
NFSPROC3_LINK(LINK3args) = 15;

struct LINK3args {
   nfs_fh3     file;
   diropargs3  link;
};

struct LINK3resok {
   post_op_attr   file_attributes;
   wcc_data       linkdir_wcc;
};

struct LINK3resfail {
   post_op_attr   file_attributes;
   wcc_data       linkdir_wcc;
};

union LINK3res switch (nfsstat3 status) {
case NFS3_OK:
   LINKr3esok  resok;
default:
   LINK3resfailresfail;
};
```

DESCRIPTION

Procedure LINK creates a hard link from **file** to **link.name**, in the directory, **link.dir**. **file** and **link.dir** must reside on the same file system on the server. On entry, the arguments in **LINK3args** are:

file	The file handle for the existing file system object.
link	Where the link is to be created:
link.dir	The file handle for the directory in which the link is to be created.
link.name	The name that is to be associated with the created link. Refer to *General comments on file names* on page 17.

On successful return, **LINK3res.status** is NFS3_OK and **LINK3res.resok** contains:

file_attributes	The attributes of the file system object identified by file.
linkdir_wcc	Weak cache consistency data for the directory, **link.dir**.

Otherwise, **LINK3res.status** contains the error on failure and **LINK3res.resfail** contains the following:

file_attributes	The attributes of the file system object identified by **file**.
linkdir_wcc	Weak cache consistency data for the directory, **link.dir**.

IMPLEMENTATION

A hard link should have the property that changes to any of the linked files are reflected in all of the linked files. When a hard link is made to a file, the attributes for the file should have a value for **nlink** which is one greater than the value before the LINK.

Comments under RENAME regarding object and target residing on the same file system apply here as well.

Refer to *General comments on file names* on page 17.

ERRORS

NFS3ERR_IO	
NFS3ERR_ACCES	**Link.name** contains a "/".
NFS3ERR_EXIST	The (possibly truncated) name, **link.name**, already exists in **link.dir**.
NFS3ERR_XDEV	**File** and **link.dir** reside on different file systems.
NFS3ERR_NOTDIR	**Link.dir** is not a directory.
NFS3ERR_INVAL	**Link.name** is "." or "..".
NFS3ERR_NOSPC	The file system that contains **link.dir** is full.
NFS3ERR_ROFS	The file system that contains **link.dir** is read-only.
NFS3ERR_MLINK	
NFS3ERR_NAMETOOLONG	**Link.name** is longer than the maximum for the file system and **no_trunc** is TRUE.
NFS3ERR_DQUOT	
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_NOTSUPP	The server does not support hard links.
NFS3ERR_SERVERFAULT	

SEE ALSO

SYMLINK, RENAME

Procedure 16 READDIR

READDIR: Read From Directory

SYNOPSIS

```
READDIR3res
NFSPROC3_READDIR(READDIR3args) = 16;

struct READDIR3args {
   nfs_fh3     dir;
   cookie3     cookie;
   cookieverf3 cookieverf;
   count3      count;
};

struct entry3 {
   fileid3     fileid;
   filename3   name;
   cookie3     cookie;
   entry3      *nextentry;
};

struct dirlist3 {
   entry3   *entries;
   bool     eof;
};

struct READDIR3resok {
   post_op_attr   dir_attributes;
   cookieverf3    cookieverf;
   dirlist3       reply;
};

struct READDIR3resfail {
   post_op_attr   dir_attributes;
};

union READDIR3res switch (nfsstat3 status) {
case NFS3_OK:
   READDIR3resok     resok;
default:
   READDIR3resfail   resfail;
};
```

DESCRIPTION

Procedure READDIR retrieves a variable number of entries, in sequence, from a file system directory and returns the name and file identifier for each, together with information to allow the client to request additional directory entries in a subsequent READDIR request. On entry, the arguments in **READDIR3args** are:

dir	The file handle for the directory to be searched.
cookie	This should be set to 0 in the first request to read the directory. On subsequent requests, it should be a **cookie** as returned by the server.
cookieverf	This should be set to 0 in the first request to read the directory. On subsequent requests, it should be a **cookieverf** as returned by the server. The **cookieverf**

must match that returned by the READDIR in which the **cookie** was acquired.

count The maximum size of the **READDIR3resok** structure, in bytes. The size must include all XDR overhead. The server is free to return less than **count** bytes of data.

On successful return, **READDIR3res.status** is NFS3_OK and **READDIR3res.resok** contains:

dir_attributes The attributes of the directory, **dir**.

cookieverf The cookie verifier.

reply The directory list:

- **entries** Zero or more directory (**entry3**) entries.
- **eof** TRUE if the last member of **reply.entries** is the last entry in the directory or the list **reply.entries** is empty and the cookie corresponded to the end of the directory. If FALSE, there may be more entries to read.

Otherwise, **READDIR3res.status** contains the error on failure and **READDIR3res.resfail** contains the following:

dir_attributes The attributes of the directory, **dir**.

IMPLEMENTATION

In the NFS version 2 protocol, each directory entry returned included a cookie identifying a point in the directory. By including this cookie in a subsequent READDIR, the client could resume the directory read at any point in the directory. One problem with this scheme was that there was no easy way for a server to verify that a cookie was valid. If two READDIRs were separated by one or more operations that changed the directory in some way (for example, reordering or compressing it), it was possible that the second READDIR could miss entries, or process entries more than once. If the cookie was no longer usable (*e.g.* pointing into the middle of a directory entry), the server would have to indicate that the search had reached the end of the directory, even though more entries remained. There was no way that the client could distinguish this from a valid end-of-directory; the server hadn't reached the end of the directory, but the client remained unaware of any problem.

In the NFS version 3 protocol, each READDIR request includes both a cookie and a cookie verifier. For the first call, both are set to 0. The response includes a new cookie verifier, together with a cookie per entry. For subsequent READDIRs, the client must present both the cookie and the corresponding cookie verifier. Directory entry cookies may become invalid if the directory is modified. If the server detects that the cookie is no longer valid, it will reject the request with the status, NFS3ERR_BAD_COOKIE. The client should be careful to avoid holding directory entry cookies across operations that modify the directory contents, such as REMOVE and CREATE.

One implementation of the cookie verifier mechanism might be for the server to use the modification time of the directory. This might be overly restrictive, however. A better approach would be to record the time of the last directory modification that changed the directory organization in a way which would make it impossible to reliably interpret a cookie.

The server may return fewer than **count** bytes of XDR encoded entries. The **count** specified by the client in the request should be greater than or equal to FSINFO **dt_pref**.

Since UNIX clients impart a special meaning to the **fileid** value zero, UNIX clients should be careful to map zero **fileid** values to some other value, and servers of UNIX clients should try to avoid sending a zero **fileid**.

ERRORS

NFS3ERR_IO	
NFS3ERR_ACCES	
NFS3ERR_NOTDIR	**Dir** is not a directory.
NFS3ERR_BAD_COOKIE	**Cookie** is no longer valid.
NFS3ERR_TOOSMALL	**Count** of bytes is too small to return a single directory entry.
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_NOTSUPP	
NFS3ERR_SERVERFAULT	

SEE ALSO

See **dt_pref** description in FSINFO procedure.

Procedure 17 READDIRPLUS

READDIRPLUS: Read from directory extended

SYNOPSIS

```
READDIRPLUS3res
NFSPROC3_READDIRPLUS(READDIRPLUS3args) = 17;

struct READDIRPLUS3args {
   nfs_fh3     dir;
   cookie3     cookie;
   cookieverf3 cookieverf;
   count3      dircount;
   count3      maxcount;
};

struct entryplus3 {
   fileid3        fileid;
   filename3      name;
   cookie3        cookie;
   post_op_attr   name_attributes;
   post_op_fh3    name_handle;
   entryplus3     *nextentry;
};

struct dirlistplus3 {
   entryplus3  *entries;
   bool        eof;
};

struct READDIRPLUS3resok {
   post_op_attr   dir_attributes;
   cookieverf3    cookieverf;
   dirlistplus3   reply;
};

struct READDIRPLUS3resfail {
   post_op_attr   dir_attributes;
};

union READDIRPLUS3res switch (nfsstat3 status) {
case NFS3_OK:
   READDIRPLUS3resok    resok;
default:
   READDIRPLUS3resfail  resfail;
};
```

DESCRIPTION

Procedure READDIRPLUS retrieves a variable number of entries from a file system directory and returns complete information about each, together with information to allow the client to request additional directory entries in a subsequent READDIRPLUS. READDIRPLUS differs from READDIR only in the amount of information returned for each entry. In READDIR, each entry returns the file name and the **fileid**. In READDIRPLUS, each entry returns the name, attributes (including **fileid3**), and file handle. On entry, the arguments in **READDIRPLUS3args** are:

dir	The file handle for the directory to be searched.
cookie	This should be set to 0 on the first request to read a directory. On subsequent requests, it should be a **cookie** as returned by the server.
cookieverf	This should be set to 0 on the first request to read a directory. On subsequent requests, it should be a **cookieverf** as returned by the server. The **cookieverf** must match that returned by the READDIRPLUS call in which the **cookie** was acquired.
dircount	The maximum number of bytes of directory information returned. This number should not include the size of the attributes and file handle portions of the result.
maxcount	The maximum size of the **READDIRPLUS3resok** structure, in bytes. The size must include all NFS XDR overhead. The server is free to return fewer than **maxcount** bytes of data.

On successful return, **READDIRPLUS3res.status** is NFS3_OK and **READDIRPLUS3res.resok** contains:

dir_attributes	The attributes of the directory, **dir**.
cookieverf	The cookie verifier.
reply	The directory list:
entries	Zero or more directory (**entryplus3**) entries.
eof	TRUE if the last member of **reply.entries** is the last entry in the directory or the list **reply.entries** is empty and the cookie corresponded to the end of the directory. If FALSE, there may be more entries to read.

Otherwise, **READDIRPLUS3res.status** contains the error on failure and **READDIRPLUS3res.resfail** contains the following:

dir_attributes	The attributes of the directory, **dir**.

IMPLEMENTATION

Issues which need to be understood for this procedure include increased cache flushing activity on the client (as new file handles are returned with names) and over-the-wire overhead versus expected subsequent LOOKUP elimination. It is thought that this procedure may improve performance for directory browsing where attributes are always required as on the Apple Macintosh operating system and for MS-DOS.

The **dircount** and **maxcount** fields are included as an optimization. Consider a READDIRPLUS call on a UNIX operating system implementation for 1048 bytes; the reply does not contain many entries because of the overhead due to attributes and file handles. An alternative was to issue a READDIRPLUS call for 8192 bytes and then only use the first 1048 bytes of directory information. However, the server doesn't know that all that is needed is 1048 bytes of directory information (as would be returned by READDIR). It sees the 8192 byte request and issues a **VOP_READDIR** for 8192 bytes. It then steps through all of those directory entries, obtaining attributes and file handles for each entry. When it XDR encodes the result, the server only encodes until it gets 8192 bytes of results which include the attributes and file handles. Thus, it has done a larger **VOP_READDIR** and many more attribute fetches than it needed to. The ratio of directory entry size to size of attributes plus size of file handle is usually at least 8 to 1. The server has done much more work than it needed to.

The solution to this problem is for the client to provide two counts to the server. The first is the number of bytes of directory information that the client really wants, **dircount**. The second is the maximum number of bytes in the result, including the attributes and file handles, **maxcount**. Thus, the server will issue a **VOP_READDIR** for only the number of bytes that the client really wants to get, not an inflated number. This should help to reduce the size of **VOP_READDIR** requests on the server, thus reducing the amount of work done there, and to reduce the number of **VOP_LOOKUP**, **VOP_GETATTR**, and other calls done by the server to construct attributes and file handles.

See additional comments under READDIR.

ERRORS

NFS3ERR_IO	
NFS3ERR_ACCES	
NFS3ERR_NOTDIR	**Dir** is not a directory.
NFS3ERR_BAD_COOKIE	**Cookie** is no longer valid.
NFS3ERR_TOOSMALL	**Count** is too small to return a single directory entry (including file handle and attributes).
NFS3ERR_STALE	
NFS3ERR_BADHANDLE	
NFS3ERR_NOTSUPP	
NFS3ERR_SERVERFAULT	

SEE ALSO

See **dt_pref** description in FSINFO procedure.

Procedure 18 FSSTAT

FSSTAT: Get dynamic file system information

SYNOPSIS

```
FSSTAT3res
NFSPROC3_FSSTAT(FSSTAT3args) = 18;

struct FSSTAT3args {
   nfs_fh3  fsroot;
};

struct FSSTAT3resok {
   post_op_attr   obj_attributes;
   size3          tbytes;
   size3          fbytes;
   size3          abytes;
   size3          tfiles;
   size3          ffiles;
   size3          afiles;
   uint32         invarsec;
};

struct FSSTAT3resfail {
   post_op_attr   obj_attributes;
};

union FSSTAT3res switch (nfsstat3 status) {
case NFS3_OK:
   FSSTAT3resok      resok;
default:
   FSSTAT3resfail    resfail;
};
```

DESCRIPTION

Procedure FSSTAT retrieves volatile file system state information. On entry, the arguments in **FSSTAT3args** are:

fsroot	A file handle identifying a object in the file system. Normal usage is to provide a file handle for a mount point for a file system, as originally obtained from the mount service on the server.

On successful return, **FSSTAT3res.status** is NFS3_OK and **FSSTAT3res.resok** contains:

obj_attributes	The attributes of the file system object specified in **fsroot**.
tbytes	The total size, in bytes, of the file system.
fbytes	The amount of free space, in bytes, in the file system.
abytes	The amount of free space, in bytes, which is available to the user identified by the authentication information in the RPC. (This reflects space which is reserved by the file system; it does not reflect any quota system implemented by the server.)
tfiles	The total number of file slots in the file system. (On a UNIX server, this often corresponds to the number of inodes configured.)
ffiles	The number of free file slots in the file system.
afiles	The number of free file slots which are available to the user corresponding to the authentication information in the RPC. (This reflects slots that are reserved by the file system; it does not reflect any quota system implemented by the server.)

invarsec A measure of file system volatility: the number of seconds for which the file system is not expected to change. For a volatile, frequently updated file system this will be `0`. For an immutable file system, such as a CD-ROM, this would be the largest unsigned integer. For file systems which are infrequently modified (*e.g.* one containing local executables and on-line documentation) a value corresponding to a few hours or days might be used. The client may use this as a hint in tuning its cache management.

Otherwise, **FSSTAT3res.status** contains the error on failure and **FSSTAT3res.resfail** contains the following:

obj_attributes The attributes of the file system object specified in **fsroot**.

IMPLEMENTATION

Not all implementations can support the entire list of attributes. It is expected that servers will make a best effort at supporting all the attributes.

ERRORS

```
NFS3ERR_STALE
NFS3ERR_BADHANDLE
NFS3ERR_NOTSUPP
NFS3ERR_SERVERFAULT
```

SEE ALSO

`FSINFO`

Procedure 19 FSINFO

FSINFO: Get static file system Information

SYNOPSIS

```
FSINFO3res
NFSPROC3_FSINFO(FSINFO3args) = 19;

const FSF3_LINK         = 0x0001;
const FSF3_SYMLINK      = 0x0002;
const FSF3_HOMOGENEOUS  = 0x0008;
const FSF3_CANSETTIME   = 0x0010;

struct FSINFOargs {
   nfs_fh3  fsroot;
};

struct FSINFO3resok {
   post_op_attr   obj_attributes;
   uint32         rtmax;
   uint32         rtpref;
   uint32         rtmult;
   uint32         wtmax;
   uint32         wtpref;
   uint32         wtmult;
   uint32         dtpref;
   size3          maxfilesize;
   nfstime3       time_delta;
   uint32         properties;
};

struct FSINFO3resfail {
   post_op_attr   obj_attributes;
};

union FSINFO3res switch (nfsstat3 status) {
case NFS3_OK:
   FSINFO3resok      resok;
default:
   FSINFO3resfail    resfail;
};
```

DESCRIPTION

Procedure FSINFO retrieves nonvolatile file system state information and general information about the NFS server implementation. On entry, the arguments in **FSINFO3args** are:

fsroot A file handle identifying a file object. Normal usage is to provide a file handle for a mount point for a file system, as originally obtained from the mount service on the server.

On successful return, **FSINFO3res.status** is NFS3_OK and **FSINFO3res.resok** contains:

obj_attributes The attributes of the file system object specified in **fsroot**.

rtmax The maximum size of a READ request supported by the server. Any READ with a count greater than **rtmax** will result in a short read of **rtmax** bytes or less.

rtpref	The preferred size of a READ request. This should be the same as **rtmax** unless there is a clear benefit in performance or efficiency.
rtmult	The suggested multiple for the size of a READ request.
wtmax	The maximum size of a WRITE request supported by the server. In general, the client must respect **wtmax** since there is no guarantee that a server can cope with a larger write. Any WRITE with a count greater than **wtmax** will result in a short write of at most **wtmax** bytes.
wtpref	The preferred size of a WRITE request. This should be the same as **wtmax** unless there is a clear benefit in performance or efficiency.
wtmult	The suggested multiple for the size of a WRITE request.
dtpref	The preferred size of a READDIR request.
maxfilesize	The maximum size of a file on the file system.
time_delta	The server time granularity. When setting a file time using SETATTR, the server guarantees only to preserve times to this accuracy. If this is {0, 1}, the server can support nanosecond times. {0, 1000000} denotes millisecond precision, while {1, 0} indicates that times are accurate only to the nearest second.
properties	A bit mask of file system properties. The following values are presently defined:
FSF_LINK	If this bit is 1 (TRUE), the file system supports hard links.
FSF_SYMLINK	If this bit is 1 (TRUE), the file system supports symbolic links.
FSF_HOMOGENEOUS	If this bit is 1 (TRUE), the information returned by PATHCONF is identical for every file and directory in the file system. If it is 0 (FALSE), the client should retrieve PATHCONF information for each file and directory as required.
FSF_CANSETTIME	If this bit is 1 (TRUE), the server will set the times for a file via SETATTR if requested (to the accuracy indicated by **time_delta**). If it is 0 (FALSE), the server cannot set times as requested.

Otherwise, **FSINFO3res.status** contains the error on failure and **FSINFO3res.resfail** contains the following:

attributes	The attributes of the object **fsroot**.

IMPLEMENTATION

Not all implementations can support the entire list of attributes. It is expected that a server will make a best effort at supporting all the attributes.

The file handle provided is expected to be the file handle of the file system "root", as returned to the mount operation. Since mounts may occur anywhere within an exported tree, the server should expect FSINFO requests specifying file handles within the exported file system. It is conceivable that a server may export different types of file systems with different attributes returned to the FSINFO call. The client should retrieve FSINFO information for each mount completed. Though a server may return different FSINFO information for different files within a file system, there is no requirement that a client obtain FSINFO information for other than the file handle returned at mount.

The **maxfilesize** field determines whether a server's particular file system uses 32 bit sizes and offsets or 64 bit file sizes and offsets. This may have bearing on a client's processing.

The preferred sizes for requests are nominally tied to an exported file system mounted by a client. NFS deals with file systems. A surmountable issue arises in that the transfer size for an NFS request is not only dependent on characteristics of the file system but also on characteristics of the network interface, particularly the maximum transfer unit (or MTU). A server implementation is free to advertise different transfer sizes (for the fields **rtmax**, **rtpref**, **wtmax**, **wtpref**, **dtpref**) depending on the interface on which the FSINFO request is received. This is simply an implementation issue.

ERRORS

NFS3ERR_STALE
NFS3ERR_BADHANDLE
NFS3ERR_NOTSUPP
NFS3ERR_SERVERFAULT

SEE ALSO

FSSTAT

Procedure 20 PATHCONF

PATHCONF: Retrieve POSIX information

SYNOPSIS

```
PATHCONF3res
NFSPROC3_PATHCONF(PATHCONF3args) = 20;

struct PATHCONF3args {
   nfs_fh3  object;
};

struct PATHCONF3resok {
   post_op_attr   obj_attributes;
   uint32         linkmax;
   uint32         name_max;
   bool           no_trunc;
   bool           chown_restricted;
   bool           case_insensitive;
   bool           case_preserving;
};

struct PATHCONF3resfail {
   post_op_attr   obj_attributes;
};

union PATHCONF3res switch (nfsstat3 status) {
case NFS3_OK:
   PATHCONF3resok    resok;
default:
   PATHCONF3resfail  resfail;
};
```

DESCRIPTION

Procedure PATHCONF retrieves the "pathconf" information for a file or directory. If the FSF_HOMOGENEOUS bit is set in **FSFINFO3resok.properties**, the pathconf information will be the same for all files and directories in the exported file system in which this file or directory resides. On entry, the arguments in **PATHCONF3args** are:

object	The file handle for the object in question.

On successful return, **PATHCONF3res.status** is NFS3_OK and **PATHCONF3res.resok** contains:

obj_attributes	The attributes of the object specified by **object**.
linkmax	The maximum number of hard links to an object.
name_max	The maximum length of a component of a file name.
no_trunc	If TRUE, the server will reject any NFS request which includes a name longer than **name_max** with the error, NFS3ERR_NAMETOOLONG. If FALSE, any length name over **name_max** bytes will be silently truncated to **name_max** bytes.
chown_restricted	If TRUE, the server will reject any NFS request to change either the owner or the group associated with a file if the caller is not the super user. (Uid 0.)
case_insensitive	If TRUE, the server file system does not distinguish case when interpreting file names.
case_preserving	If TRUE, the server file system will preserve the case of a name during a CREATE, MKDIR, MKNOD, SYMLINK, RENAME, or LINK operation.

Otherwise, **PATHCONF3res.status** contains the error on failure and **PATHCONF3res.resfail** contains the following:

obj_attributes The attributes of the object specified by **object**.

IMPLEMENTATION

In implementations of the NFS version 2 protocol, *pathconf()* information was obtained at mount time through the mount protocol. The proper place to obtain it is as here, in the NFS protocol itself.

ERRORS

NFS3ERR_STALE
NFS3ERR_BADHANDLE
NFS3ERR_NOTSUPP
NFS3ERR_SERVERFAULT

SEE ALSO

Procedure 21 COMMIT

COMMIT: Commit cached data on a server to stable storage

SYNOPSIS

```
COMMIT3res
NFSPROC3_COMMIT(COMMIT3args) = 21;

struct COMMIT3args {
   nfs_fh3     file;
   offset3     offset;
   count3      count;
};

struct COMMIT3resok {
   wcc_data    file_wcc;
   writeverf3  verf;
};

struct COMMIT3resfail {
   wcc_data    file_wcc;
};

union COMMIT3res switch (nfsstat3 status) {
case NFS3_OK:
   COMMIT3resok   resok;
default:
   COMMIT3resfail resfail;
};
```

DESCRIPTION

Procedure COMMIT forces or flushes data to stable storage which was previously written with a WRITE procedure call with the **stable** field set to FALSE. On entry, the arguments in **COMMIT3args** are:

file	The file handle for the file to which data is to be flushed (committed). This must identify a file system object of type NF3REG.
offset	The position within the file at which the flush is to begin. An **offset** of 0 means to flush data starting at the beginning of the file.
count	The number of bytes of data which are to be flushed. If **count** is 0, a flush from **offset** to the end of file is done.

On successful return, **COMMIT3res.status** is NFS3_OK and **COMMIT3res.resok** contains:

file_wcc	Weak cache consistency data for the file. For a client that requires only the post-operation file attributes, these can be found in **file_wcc.after**.
verf	This is a cookie that the client can use to determine whether the server has rebooted between a call to WRITE and a subsequent call to COMMIT. This cookie must be consistent during a single boot session and must be unique between instances of the NFS server (where uncommitted data may be lost).

Otherwise, **COMMIT3res.status** contains the error on failure and **COMMIT3res.resfail** contains the following:

file_wcc	Weak cache consistency data for the file. For a client that requires only the post-write file attributes, these can be found in **file_wcc.after**. Note that even

though the COMMIT failed, full **wcc_data** is returned to allow the client to determine whether the file changed on the server between calls to WRITE and COMMIT.

IMPLEMENTATION

Procedure COMMIT is similar in operation and semantics to the POSIX *fsync(2)* system call which synchronizes a file's state with the disk, that is it flushes the file's data to disk. COMMIT performs the same operation for a client, flushing any unsynchronized data on the server to the server's disk for the specified file. Like *fsync(2)*, it may be that there is some modified data, or no modified data to synchronize. This is okay, as the data may have been synchronized by the server's normal periodic buffer synchronization activity. COMMIT will always return NFS3_OK, unless there has been an unexpected error.

COMMIT differs from *fsync(2)* in that it is possible for the client to flush a range of the file (most likely triggered by a buffer reclamation scheme on the client before file has been completely written).

The server implementation of COMMIT is reasonably simple. If the server receives a full file flush, that is starting at **offset** 0 and **count** 0, it should do the equivalent of *fsync*()'ing the file. Otherwise, it should arrange to have the cached data in the range specified by **offset** and **count** to be flushed to stable storage. In both cases, any metadata associated with the file must be flushed to stable storage before returning. It is not an error for there to be nothing to flush on the server. This simply means that the data and metadata which needed to be flushed have already been flushed or lost during the last server failure.

The client implementation of COMMIT is a little more complex. There are two reasons for wanting to commit a client buffer to stable storage. The first is that the client wants to reuse a buffer. In this case, the **offset** and **count** of the buffer are sent to the server in the COMMIT request. The server then flushes any cached data based on the **offset** and **count**, and flushes any metadata associated with the file. It then returns the status of the flush and the **verf** verifier. The other reason for the client to generate a COMMIT is for a full file flush, such as may be done at close. In this case, the client would gather together all of the buffers for this file which are marked with B_NEEDCOMMIT, do the COMMIT operation with an **offset** of 0 and **count** of 0, and then clear the B_NEEDCOMMIT bits on all of those buffers. Any other dirty buffers which were not marked with B_NEEDCOMMIT would get sent to the server in the normal fashion.

This implementation will require some modifications to the buffer cache on the client. After a buffer is written with **stable** FALSE, it must be considered as dirty by the client system until it either gets flushed via a COMMIT operation or written via a WRITE operation with **stable** TRUE. This is done to prevent the buffer from being freed and reused before the data can be flushed to stable storage on the server.

When a response comes back from either a WRITE or a COMMIT operation that contains an unexpected **verf**, the client will need to retransmit all of the buffers containing cached data to the server. How this is to be done is up to the implementor. If there is only one buffer of interest, than it should probably be sent back over in a WRITE request with the appropriate **stable** bit. If there more than one, it might be worthwhile retransmitting all of the buffers in WRITE requests with the **stable** bit off and then retransmitting the COMMIT operation to flush all of the data on the server to stable storage. The timing of these retransmissions is left to the implementor.

Note that the above description applies to page cache based systems as well as buffer cache based systems. In those systems, the virtual memory system will need to be modified instead of the buffer cache.

See additional comments under the WRITE procedure description.

ERRORS

NFS3ERR_IO
NFS3ERR_STALE
NFS3ERR_BADHANDLE
NFS3ERR_SERVERFAULT

SEE ALSO

WRITE

Implementation issues

The NFS protocol was designed to allow different operating systems to share files. However, since it was designed in a UNIX environment, many operations have semantics similar to the operations of the UNIX file system. This section discusses some of the general implementation-specific details and semantic issues. Procedure descriptions have implementation comments specific to that procedure.

A number of papers have been written describing implementation issues in NFS. The best overview paper is still *[Sandberg]*. *[Israel]*, *[Macklem]* and *[Pawlowski]* describe other implementations. *[X/OpenNFS]* provides a complete description of the NFS version 2 protocol and supporting protocols, as well as a discussion on implementation issues and procedure and error semantics.

Multiple version support

The RPC protocol provides explicit support for versioning of a service. Client and server implementations of NFS should support both versions, for full backwards compatibility, when possible. Default behavior of the RPC binding protocol is the client and server bind using the highest version number they both support. Client or server implementations which cannot easily support both versions (for example, because of memory restrictions) will have to choose what version to support. The NFS version 2 protocol would be a safe choice since fully capable clients and servers should support both versions.

Server/client relationship

The NFS protocol is designed to allow servers to be as simple and general as possible. Sometimes the simplicity of the server can be a problem, if the client wants to implement complicated file system semantics.

For example, some operating systems allow removal of open files. A process can open a file and, while it is open, remove it from the directory. The file can be read and written as long as the process keeps it open, even though the file has no name in the file system. It is impossible for a stateless server to implement these semantics. The client can do some tricks such as renaming the file on remove (to a *hidden* name), and only physical deleting it on close. The NFS version 3 protocol provides sufficient functionality to implement most file system semantics on a client.

Every NFS client can also potentially be a server, and remote and local mounted file systems can be freely intermixed. This leads to some interesting problems when a client travels down the directory tree of a remote file system and reaches the mount point on the server for another remote file system. Allowing the server to follow the second remote mount would require loop detection, server lookup, and user revalidation. Instead, both NFS version 2 protocol and NFS version 3 protocol implementations do not typically let clients cross a server's mount point. When a client does a `LOOKUP` on a directory on which the server has mounted a file system, the client sees the underlying directory instead of the mounted directory.

For example, if a server has a file system called `/usr` and mounts another file system on `/usr/src`, if a client mounts `/usr`, it does **not** see the mounted version of `/usr/src`. A client could do remote mounts that match the server's mount points to maintain the server's view. In this example, the client would also have to mount `/usr/src` in addition to `/usr`, even if they are from the same server.

Pathname interpretation

There are a few complications to the rule that pathnames are always parsed on the client. For example, symbolic links could have different interpretations on different clients. There is no answer to this problem in this specification. Another common problem for non-UNIX implementations is the special interpretation of the pathname "`..`" to mean the parent of a given directory. A future revision of the protocol may use an explicit flag to indicate the parent instead—however it is seemingly not a problem as many working non-UNIX implementations exist.

Permission issues

The NFS protocol, strictly speaking, does not define the permission checking used by servers. However, it is expected that a server will do normal operating system permission checking using `AUTH_UNIX` style authentication as the basis of its protection mechanism, or another stronger form of authentication such as `AUTH_DES` or `AUTH_KERB`. With `AUTH_UNIX` authentication, the server gets the client's effective *uid*, effective *gid*, and groups on each call and uses

them to check permission. These are the so-called *UNIX credentials*. AUTH_DES and AUTH_KERB use a *network name*, or netname, as the basis for identification (from which a UNIX server derives the necessary standard UNIX credentials). There are various problems with this method that have been resolved in interesting ways.

Using *uid* and *gid* implies that the client and server share the same *uid* list. Every server and client pair must have the same mapping from user to *uid* and from group to *gid*. Since every client can also be a server, this tends to imply that the whole network shares the same *uid/gid* space. If this is not the case, then it usually falls upon the server to perform some custom mapping of credentials from one authentication domain into another. A discussion on techniques on managing a shared user space, or providing mechanisms for user id mapping is beyond the scope of this specification.

Another problem arises due to the usually stateful open operation. Most operating systems check permission at open time, and then check that the file is open on each read and write request. With stateless servers, the server has no idea that the file is open and must do permission checking on each read and write call. UNIX client semantics of access permission checking on open can be provided with the ACCESS procedure call in this revision, which allows a client to explicitly check access permissions without resorting to trying the operation. On a local file system, a user can open a file and then change the permissions so that no one is allowed to touch it, but will still be able to write to the file because it is open. On a remote file system, by contrast, the write would fail. To get around this problem, the server's permission checking algorithm should allow the owner of a file to access it regardless of the permission setting. This is needed in a practical NFS server implementation, but it does depart from correct local file system semantics. This should not affect the return result of access permissions as returned by the ACCESS procedure, however.

A similar problem has to do with paging in an executable over the network. The operating system usually checks for execute permission before opening a file for demand paging, and then reads blocks from the open file. In a local UNIX file system, an executable file does not need read permission to execute (pagein). An NFS server can not tell the difference between a normal file read (where the read permission bit is meaningful) and a demand pagein read (where the server should allow access to the executable file if the execute bit is set for that user or group or public). To make this work, the server simply allows reading of files if the *uid* given in the call has either execute or read permission on the file, through ownership, group membership or public access. Again, this departs from correct local file system semantics.

In most operating systems, a particular user (on UNIX, the *uid* zero) has access to all files no matter what permission and ownership they have. This "super-user" permission may not be allowed on the server, since anyone who can become super-user on their workstation could gain access to all remote files. A UNIX server by default maps *uid* 0 to a distinguished value (UID_NOBODY) before doing its access checking. A server implementation may provide a mechanism to change this mapping. This works except for NFS root file systems (required for diskless NFS client support), where super-user access cannot be avoided. Export options are used, on the server, to restrict the set of clients allowed super-user access.

Duplicate request cache

The NFS failure recovery model uses client time-out and retry to handle server crashes, network partitions, and lost server replies. A retried request is called a *duplicate* of the original.

When used in a file server context, the term idempotent can be used to distinguish between operation types. An idempotent request is one that a server can perform more than once with equivalent results (though it may in fact change, as a side effect, the access time on a file, say for READ). Some NFS operations are obviously non-idempotent. They cannot be reprocessed without special attention simply because they may fail if tried a second time. The CREATE request, for example, can be used to create a file for which the owner does not have write permission. A duplicate of this request cannot succeed if the original succeeded. Likewise, a file can be removed only once.

The side effects caused by performing a duplicate non-idempotent request can be destructive (e.g. a truncate operation causing lost writes). The combination of a stateless design with the common choice of an unreliable network transport (UDP) implies the possibility of destructive replays of non-idempotent requests. Though to be more accurate, it is the inherent stateless design of NFS itself on top of an unreliable RPC mechanism which yields the possibility of destructive replays of non-idempotent requests, since even in an implementation of NFS over a reliable connection-oriented transport, a connection break with automatic reestablishment requires duplicate request processing (the client will retransmit the request, and the server needs to deal with a potential duplicate non-idempotent request).

Most NFS server implementations use a cache of recent requests (called the duplicate request cache) for the processing of duplicate non-idempotent requests. The duplicate request cache provides a *short term memory* mechanism in which the original completion status of a request is *remembered*, and the operation attempted only once. If a duplicate copy of this request is received, then the original completion status is returned.

The duplicate request cache mechanism has been useful in reducing destructive side effects caused by duplicate NFS requests. This mechanism, however, does not guarantee against these destructive side effects in all failure modes. Most servers store the duplicate request cache in RAM, so the contents are lost if the server crashes. The exception to this may possibly occur in a redundant server approach to high availability, where the file system itself may be used to share the duplicate request cache state. Even if the cache survives server reboots (or failovers in the high availability case), its effectiveness is a function of its size. A network partition can cause a cache entry to be reused before a client receives a reply for the corresponding request. If this happens, the duplicate request will be processed as a new one, possibly with destructive side effects.

A good description of the implementation and use of a duplicate request cache can be found in *[Juszczak]*.

File name component handling

Server implementations of NFS version 3 protocol will frequently impose restrictions on the names which can be created. Many servers will also forbid the use of names which contain certain characters, such as the path component separator used by the server operating system. For example, the UFS file system will reject a name which contains "/", while "`.`" and "`..`" are distinguished in UFS, and may not be specified as the name when creating a file system object. The exact error status values return for these errors is specified in the description of each procedure argument; the reader is cautioned that the values (which conform to NFS version 2 protocol server practice) are not necessarily obvious, nor are they consistent from one procedure to the next.

Synchronous modifying operations

Data modifying operations in the NFS protocol are synchronous. When a procedure returns to the client, the client can assume at the operation has completed and any data associated with the request is now on stable storage.

Some views on stable storage may be appropriate here. NFS servers must be able to recover without data loss from multiple power failures (including cascading power failures, *i.e.*, several power failures in quick succession), operating system failures, and hardware failure of components (*e.g.*, CPU) other than the storage medium itself (*e.g.*, disk, nonvolatile RAM)."

Some examples of stable storage which are allowable for an NFS server include:

1. Media commit of data, i.e., the modified data has been successfully written to the disk media, for example, the disk platter.
2. An immediate reply disk drive with battery-backed on-drive intermediate storage or uninterruptible power system. (UPS).
3. Server commit of data with battery-backed intermediate storage and recovery software.
4. Cache commit with uninterruptible power system (UPS) and recovery software.

Conversely, the following are not examples of stable storage:

1. An immediate reply disk drive without battery-backed on-drive intermediate storage or uninterruptible power system. (UPS).
2. Cache commit without both uninterruptible power system (UPS) and recovery software.

The **only** exception to this (introduced in this protocol revision) is as described under the `WRITE` procedure on the handling of the **`stable`** bit, and the use of the `COMMIT` procedure. It is the use of the synchronous `COMMIT` procedure which provides the necessary semantic support in the NFS version 3 protocol.

Lookups and name resolution

A common objection to the NFS protocol is the philosophy of component by component `LOOKUP` by the client in resolving a name. The objection is that this is inefficient, as latencies for component-by-component `LOOKUP` would be

unbearable.

Implementation practice ameliorates this. A name cache, providing component to file handle mapping, is kept on the client to short circuit actual LOOKUP invocations over the wire. The cache is subject to cache time-out parameters which bound attributes.

Adaptive retransmission

Most client implementations use either an exponential back-off strategy to some maximum retransmission value, or a more adaptive strategy which attempts congestion avoidance. Congestion avoidance schemes in NFS request retransmission are modelled on the work presented in *[Jacobson]*. *[Nowicki]* and *[Macklem]* describe congestion avoidance schemes for NFS over UDP.

Caching policies

The NFS version 3 protocol does not define a policy for caching on the client or server. In particular, there is no support for strict cache consistency between a client and server, nor between different clients. See *[Kazar]* for a discussion of the issues of cache synchronization and mechanisms in several distributed file systems.

Stable versus unstable writes

The setting of the **stable** field in the WRITE arguments, that is whether or not to do asynchronous WRITE requests, is straightforward on a UNIX client. If the client NFS code receives a write request that is not marked as B_ASYNC, it should generate the RPC with **stable** set to TRUE. If the request is marked as B_ASYNC, the RPC should be generated with **stable** set to FALSE. If the response comes back with the **committed** field set to TRUE, the client should just mark the write request as done and no further action is required. If **committed** is set to FALSE, indicating that the buffer was not synchronized with the server's disk, the client will need to mark the buffer in some way which indicates that a copy of the buffer lives on the server and that a new copy does not need to be sent to the server, but that a flush is required. For this discussion, let's call this bit, B_NEEDCOMMIT.

Note that this algorithm introduces a new state for buffers, thus there are now three states for buffers. The three states are dirty, done but needs to be committed, and done. This extra state on the UNIX client will most likely require modifications to the system outside of NFS.

One proposal that was rejected was the addition of a boolean **commit** argument to the WRITE operation. It would be used to indicate whether the server should do a full file commit after doing the write. This seems as if it could be useful if the client knew that it was doing the "last" write on the file. It is difficult to see how this could be used, given existing client architectures though.

The asynchronous write opens up the window of problems associated with write sharing. For example: client A writes some data asynchronously. Client A is still holding the buffers cached, waiting to commit them later. Client B reads the modified data and writes it back to the server. The server then crashes. When it comes back up, client A issues a COMMIT operation which returns with a different cookie as well as changed attributes. In this case, the correct action may or may not be to retransmit the cached buffers. Unfortunately, client A can't tell for sure, so it will need to retransmit the buffers, thus overwriting the changes from client B. Fortunately, write sharing is rare and the solution matches the current write sharing situation. Without using locking for synchornization, Last one there wins.

In a high availability (redundant system) server implementation, two cases exist which relate to the **verf** changing. If the high availability server implementation does not use a shared-memory scheme, then the **verf** should change on failover, since the unsynchronized data is not available to the second processor and there is no guarantee that the system which had the data cached was able to flush it to stable storage before going down. The client will need to retransmit the data to be safe. In a shared-memory high availability server implementation, the **verf** would not need to change because the server would still have the cached data available to it to be flushed. The exact policy regarding the **verf** in a shared memory high availability implementation, however, is up to the server implementor.

32 bit clients/servers and 64 bit clients/servers

The 64 bit nature of the NFS version 3 protocol introduces several compatibility problems. The most notable two are mismatched clients and servers. That is, a 32 bit client and a 64 bit server or a 64 bit client and a 32 bit server.

The problems of a 64 bit client and a 32 bit server are reasonably easy to handle. The client will never encounter a file which it can not handle. If it sends a request to the server which the server can not handle, the server should just reject the request with an appropriate error.

The problems of a 32 bit client and a 64 bit server are much harder to handle. In this situation, the server does not have a problem because it will be able to handle anything that the client can generate. However, the client may encounter a file that it can not handle. The client will not be able to handle a file whose size can not expressed in 32 bits. Thus, the client will not be able to properly decode the size of the file into its local attributes structure. It is also possible for a file to grow beyond the limit of the client while the client is accessing the file.

The solutions to these problems are left up to the individual implementor. However, there are two common approaches used to resolve this situation. The implementor is free to pick and choose between them or even to invent a new solution altogether.

The first most common solution is for the client to simply deny access to any file whose size can not expressed in 32 bits. This is probably the safest, but does introduce some strange semantics when the file grows beyond the limit of the client while it is being access by that client. The file becomes inaccessible even while it is being accessed.

The second solution is for the client to map any size greater than it can handle to the maximum size that it can handle. Effectively, it is lying to the application program. This allows the application access as much of the file as possible given the 32 bit offset restriction. This eliminates the strange semantic of the file effectively disappearing after it has been accessed, but does introduce other problems. The client will not be able to access the entire file.

Currently, the first solution is the recommended solution. However, client implementors are encouraged to do the best that they can to reduce the affects of this situation.

Appendix I: Mount protocol

The changes from the NFS version 2 protocol to the NFS version 3 protocol have required some changes in the MOUNT protocol. To meet the needs of the NFS version 3 protocol, a new version of the MOUNT protocol has been defined. This new protocol satisfies the requirements of the NFS version 3 protocol and addresses several other current market requirements.

RPC Information

Authentication

The MOUNT service uses AUTH_NONE in the NULL procedure. AUTH_UNIX, AUTH_SHORT, AUTH_DES, or AUTH_KERB are used for all other procedures. Other authentication types may be supported in the future.

Constants

These are the RPC constants needed to call the MOUNT service. They are given in decimal.

```
PROGRAM 100005
VERSION 3
```

Transport address

The MOUNT service is normally supported over the TCP and UDP protocols. The rpcbind daemon should be queried for the correct transport address.

Sizes

```
const MNTPATHLEN  = 1024;        /* Maximum bytes in a pathname */
const MNTNAMLEN   = 255;         /* Maximum bytes in a name */
const FHSIZE3     = 64;          /* Maximum bytes in a V3 filehandle */
```

Basic Data Types

```
typedef opaque fhandle3<FHSIZE3>;
typedef string dirpath<MNTPATHLEN>;
typedef string name<MNTNAMLEN>;

enum mountstat3 {
   MNT_OK               = 0,     /* no error */
   MNT3ERR_PERM         = 1,     /* Not owner */
   MNT3ERR_NOENT        = 2,     /* No such file or directory */
   MNT3ERR_IO           = 5,     /* I/O error */
   MNT3ERR_ACCES        = 13,    /* Permission denied */
   MNT3ERR_NOTDIR       = 20,    /* Not a directory */
   MNT3ERR_INVAL        = 22,    /* Invalid argument */
   MNT3ERR_NAMETOOLONG  = 63,    /* File name too long */
   MNT3ERR_NOTSUPP      = 10004, /* Operation not supported */
   MNT3ERR_SERVERFAULT  = 10006  /* A failure on the server */
};
```

Server Procedures

The following sections define the RPC procedures that are supplied by a MOUNT version 3 protocol server. The RPC procedure number is given at the top of the page along with the name and version. The SYNOPSIS provides the name of the procedure, the list of the names of the arguments, the list of the names of the results, followed by the XDR argument declarations and results declarations. The information in the SYNOPSIS is specified in RPC Data Description Language as defined in *[RFC1014]*. The DESCRIPTION section tells what the procedure is expected to do and how its arguments and results are used. The ERRORS section lists the errors returned for specific types of failures. The IMPLEMENTATION field gives information about how the procedure is expected to work and how it should be used by clients.

```
program MOUNT_PROGRAM {
   version MOUNT_V3 {
      void
       MOUNTPROC3_NULL(void)      = 0;
      mountres3
       MOUNTPROC3_MNT(dirpath)    = 1;
      mountlist
       MOUNTPROC3_DUMP(void)      = 2;
      void
       MOUNTPROC3_UMNT(dirpath)   = 3;
      void
       MOUNTPROC3_UMNTALL(void)   = 4;
      exports
       MOUNTPROC3_EXPORT(void)    = 5;
   } = 3;
} = 100005;
```

Procedure 0 MOUNTPROC3_NULL

Null: Do nothing

SYNOPSIS

```
void
MOUNTPROC3_NULL(void) = 0;
```

DESCRIPTION

Procedure MOUNTPROC3_NULL does not do any work. It is made available in all RPC services to allow server response testing and timing.

IMPLEMENTATION

It is important that this procedure do no work at all so that it can be used to measure the overhead of processing a service request. By convention, procedure 0 should never require any authentication. A server may choose to ignore this convention, in a more secure implementation, where responding to a procedure 0 call acknowledges the existence of a resource to an unauthenticated client.

ERRORS

Procedure 1 MOUNTPROC3_MNT

Mount: Add mount entry

SYNOPSIS

```
mountres3
MOUNTPROC3_MNT(dirpath) = 1;

struct mountres3_ok {
   fhandle3    fhandle;
   int         auth_flavors<>;
};

union mountres3 switch (mountstat3 fhs_status) {
case MNT_OK:
   mountres3_ok mountinfo;
default:
   void;
};
```

DESCRIPTION

Procedure `MOUNT3PROC_MNT` maps a path on the server to a filehandle. The path is an ASCII string that describes a directory on the server. If the call is successful (`MNT_OK`) the server returns an NFS filehandle and a vector of RPC authentication flavors that are supported with the client's use of the filehandle (or any filehandles derived from it) with the NFS protocol. The authentication flavors are defined in Section 7.2 and section 9 of Internet RFC 1057.

IMPLEMENTATION

If **`mountres3.fhs_status`** is `MNT_OK`, then **`mountres3.mountinfo`** contains the file handle for the directory and a list of acceptable authentication flavors. This file handle may only be used in version 3 of the NFS protocol. This procedure also results in the server adding a new entry to its mount list recording that this client has mounted the directory. Unix authentication or better is required.

ERRORS

Procedure 2 MOUNTPROC3_DUMP

Dump: Return mount entries

SYNOPSIS

```
mountlist
MOUNTPROC3_DUMP(void) = 2;

typedef struct mountbody *mountlist;

struct mountbody {
   name        ml_hostname;
   dirpath     ml_directory;
   mountlist   ml_next;
};
```

DESCRIPTION

Procedure MOUNTPROC3_DUMP returns the list of remotely mounted file systems. The mountlist contains one entry for each client hostname and directory pair.

IMPLEMENTATION

This list is derived from a list maintained on the server of clients that have requested filehandles with the MOUNTPROC3_MNT procedure. Entries are removed from this list only when a client calls the MOUNTPROC3_UMNT or MOUNTPROC3_MNTALL procedure. Entries may become stale if a client crashes.

ERRORS

Procedure 3 MOUNTPROC3_UMNT

Unmount: Remove mount entry

SYNOPSIS

```
void
MOUNTPROC3_UMNT(dirpath) = 3;
```

DESCRIPTION

Procedure `MOUNTPROC3_UMNT` removes the mount list entry for the directory which was previously the subject of a `MOUNTPROC3_MNT` call from this client. Unix authentication or better is required.

IMPLEMENTATION

ERRORS

Procedure 4 MOUNTPROC3_UMNTALL

Unmount all: Remove all mount entries

SYNOPSIS

```
void
MOUNTPROC3_UMNTALL(void) = 4;
```

DESCRIPTION

Procedure MOUNTPROC3_UMNTALL removes all of the mount entries for this client previously recorded by calls to MOUNTPROC3_MNT. Unix authentication or better is required.

IMPLEMENTATION

ERRORS

Procedure 5 MOUNTPROC3_EXPORT

Export: Return export list

SYNOPSIS

```
exports
MOUNTPROC3_EXPORT(void) = 5;

typedef struct groupnode *groups;

struct groupnode {
   name     gr_name;
   groups   gr_next;
};

typedef struct exportnode *exports;

struct exportnode {
   dirpath  ex_dir;
   groups   ex_groups;
   exports  ex_next;
};
```

DESCRIPTION

Procedure `MOUNTPROC3_EXPORT` returns a list of all the exported file systems, and which clients are allowed to mount each one. The names in the group list are implementation-specific and cannot be directly interpreted by clients. These names may represent hosts or groups of hosts.

IMPLEMENTATION

ERRORS

Appendix II: Lock manager protocol

Because the NFS protocol is stateless, an additional Network Lock Manager (NLM) protocol is required to support locking of NFS-mounted files. Version 3 of the NLM protocol, which is used with version 2 of NFS, is documented by X/Open *[X/OpenNFS]*.

Some of the changes in version 3 of the NFS protocol require a new version (version 4) of the NLM protocol. The following table summarizes the correspondence between NFS and NLM versions.

NFS and NLM protocol compatibility

NFS version	NLM version
2	1, 3
3	4

This appendix only discusses the differences between NLM versions 3 and 4. As in NFS version 3, almost all the names in NLM version 4 have been changed to include a version number. This appendix does not discuss changes that consist solely of a name change.

Basic Data Types for Locking

uint64

```
typedef unsigned hyper uint64;
```

int64

```
typedef hyper int64;
```

uint32

```
typedef unsigned long uint32;
```

int32

```
typedef long int32;
```

These types are new for NLM version 4. They are the same as in NFS version 3.

nlm4_stats

```
enum nlm4_stats {
   NLM4_GRANTED               = 0,
   NLM4_DENIED                = 1,
   NLM4_DENIED_NOLOCKS        = 2,
   NLM4_BLOCKED               = 3,
   NLM4_DENIED_GRACE_PERIOD   = 4,
   NLM4_DEADLCK               = 5,
   NLM4_ROFS                  = 6,
   NLM4_STALE_FH              = 7,
   NLM4_FBIG                  = 8,
   NLM4_FAILED                = 9
};
```

Nlm4_stats indicates the success or failure of a call. This version contains several new error codes, so that clients can provide more precise failure information to applications.

NLM4_GRANTED
: The call completed successfully.

NLM4_DENIED
: The call failed. For attempts to set a lock, this status means that if the client retries the call later, it may succeed.

NLM4_DENIED_NOLOCKS
: The call failed because the server could not allocate the necessary resources.

NLM4_BLOCKED
: Indicates that a blocking request cannot be granted immediately. The server will issue an NLM4_GRANTED callback to the client when the lock is granted.

NLM4_DENIED_GRACE_PERIOD
: The call failed because the server is reestablishing old locks after a reboot and is not yet ready to resume normal service.

NLM4_DEADLCK
: The request could not be granted, and blocking would cause a deadlock.

NLM4_ROFS
: The call failed because the remote file system is read-only. For example, some servers might not support exclusive locks on read-only file systems.

NLM4_STALE_FH
: The call failed because it uses an invalid file handle (e.g., the file has been deleted).

NLM4_FBIG
: The call failed because it specified a length or offset that exceeds the range supported by the server.

NLM4_FAILED
: The call failed for some reason not already listed. The client should take this status as a strong hint not to retry the request.

nlm4_holder

```
struct nlm4_holder {
   bool exclusive;
   int32 svid;
   netobj oh;
   uint64 l_offset;
   uint64 l_len;
};
```

This structure indicates the holder of a lock. The **exclusive** field tells whether the holder has an exclusive lock or a shared lock. The **svid** field identifies the process that is holding the lock. The **oh** field is an opaque object that identifies the host that is holding the lock. The **l_len** and **l_offset** fields identify the region that is locked. The only difference between NLM version 3 and NLM version 4 is that in version 3 the **l_len** and **l_offset** fields are 32 bits wide, while they are 64 bits wide in NLM version 4.

nlm4_lock

```
struct nlm4_lock {
   string caller_name<LM_MAXSTRLEN>;
   netobj fh;
   netobj oh;
   int32 svid;
   uint64 l_offset;
   uint64 l_len;
};
```

This structure describes a lock request. The **caller_name** field identifies the host that is making the request. The **fh** field identifies the file to lock. The **oh** field is an opaque object that identifies the host that is making the request, and the **svid** field identifies the process that is making the request. The **l_offset** and **l_len** fields identify the region of the file that the lock controls. A **l_len** of 0 means “to end of file”.

There are two differences between the NLM 3 and NLM 4 versions of this structure. First, in NLM 3 the length and offset are 32 bits wide, while they are 64 bits wide in NLM 4. Second, in NLM 3 the file handle is a fixed-length NFS version 2 file handle, which is encoded as a byte count followed by a byte array. In NLM 4 the file handle is already variable-length, so it is copied directly into the **fh** field. That is, the first 4 bytes of the **fh** field are the same as the byte count in an NFS **nfs_fh3**. The rest of the **fh** field contains the byte array from the NFS **nfs_fh3**.

nlm4_share

```
struct nlm4_share {
   string caller_name<LM_MAXSTRLEN>;
   netobj fh;
   netobj oh;
   fsh4_mode mode;
   fsh4_access access;
};
```

This structure is used to support DOS file sharing. The **caller_name** field identifies the host making the request. The **fh** field identifies the file to be operated on. The **oh** field is an opaque object that identifies the host that is making the request. The **mode** and **access** fields specify the file-sharing and access modes. The encoding of **fh** is a byte count, followed by the file handle byte array. See the description of *nlm4_lock* for more details.

NLM Procedures

The procedures in NLM version 4 are semantically the same as those in NLM version 3. The only semantic difference is the addition of a NULL procedure that can be used to test for server responsiveness. A syntactic change is that the procedures were renamed to avoid name conflicts with the values of **`nlm4_stats`**. Thus the procedure definition is as follows.

```
version NLM4_VERS {
   void
      NLMPROC4_NULL(void)                    = 0;
   nlm4_testres
      NLMPROC4_TEST(nlm4_testargs)           = 1;
   nlm4_res
      NLMPROC4_LOCK(nlm4_lockargs)           = 2;
   nlm4_res
      NLMPROC4_CANCEL(nlm4_cancargs)         = 3;
   nlm4_res
      NLMPROC4_UNLOCK(nlm4_unlockargs)       = 4;
   nlm4_res
      NLMPROC4_GRANTED(nlm4_testargs)        = 5;
   void
      NLMPROC4_TEST_MSG(nlm4_testargs)       = 6;
   void
      NLMPROC4_LOCK_MSG(nlm4_lockargs)       = 7;
   void
      NLMPROC4_CANCEL_MSG(nlm4_cancargs)     = 8;
   void
      NLMPROC4_UNLOCK_MSG(nlm4_unlockargs)   = 9;
   void
      NLMPROC4_GRANTED_MSG(nlm4_testargs)    = 10;
   void
      NLMPROC4_TEST_RES(nlm4_testres)        = 11;
   void
      NLMPROC4_LOCK_RES(nlm4_res)            = 12;
   void
      NLMPROC4_CANCEL_RES(nlm4_res)          = 13;
   void
      NLMPROC4_UNLOCK_RES(nlm4_res)          = 14;
   void
      NLMPROC4_GRANTED_RES(nlm4_res)         = 15;
   nlm4_shareres
      NLMPROC4_SHARE(nlm4_shareargs)         = 20;
   nlm4_shareres
      NLMPROC4_UNSHARE(nlm4_shareargs)       = 21;
   nlm4_res
      NLMPROC4_NM_LOCK(nlm4_lockargs)        = 22;
   void
      NLMPROC4_FREE_ALL(nlm4_notify)         = 23;
} = 4;
```

Procedure 0 NLMPROC4_NULL

NULL: Do nothing

SYNOPSIS

```
void
NLMPROC4_NULL(void) = 0;
```

DESCRIPTION

This procedure does no work. It is made available in all RPC services to allow server response testing and timing.

IMPLEMENTATION

It is important that this procedure do no work at all so that it can be used to measure the overhead of processing a service request. By convention, procedure 0 should never require any authentication.

ERRORS

Implementation issues

64-bit offsets and lengths

Some NFS servers can only support requests where the file offset or length fits in 32 or fewer bits. For these servers the lock manager will have the same restriction. If such a lock manager receives a request that it cannot handle (because the offset or length uses more than 32 bits), it should return `NLM4_FBIG`.

file handles

The change in the NFS file handle format complicates the lock manager. First, the lock manager needs some way to tell when an NFS version 2 file handle refers to the same file as an NFS version 3 file handle. (This is assuming that the lock manager supports both NLM version 3 clients and NLM version 4 clients.) Second, if the lock manager runs the file handle through a hashing function, the hashing function may need to be retuned to work with NFS version 3 file handles.

Appendix III: Bibliography

[Corbin] Corbin, John,
The Art of Distributed Programming—Programming Techniques for Remote Procedure Calls
Springer-Verlag, New York, New York. 1991.
Basic description of RPC and XDR and how to program distributed applications using them.

[Glover] Glover, Fred,
"TNFS Protocol Specification,"
Trusted System Interest Group, INTERNET-DRAFT, May 24, 1992.
Proposed draft standard for security extensions to NFS.

[Israel] Israel, Robert K., Sandra Jett, James Pownell, George M. Ericson,
"Eliminating Data Copies in UNIX-based NFS Servers,"
Uniforum Conference Proceedings, San Francisco, CA, February 27 - March 2, 1989.
Describes two methods for reducing data copies in NFS server code.

[Jacobson] Jacobson, V.,
"Congestion Control and Avoidance,"
Proc. ACM SIGCOMM '88, Stanford, CA, August 1988.
The paper describing improvements to TCP to allow use over Wide Area Networks and through gateways connecting networks of varying capacity. This work was a starting point for the NFS Dynamic Retransmission work.

[Juszczak] Juszczak, Chet,
"Improving the Performance and Correctness of an NFS Server,"
USENIX Conference Proceedings, USENIX Association, Berkeley, CA, June 1990, pages 53-63.
Describes reply cache implementation which avoids work in the server by handling duplicate requests. More important, though listed as a side-effect, the reply cache aids in the avoidance of destructive non-idempotent operation re-application—improving correctness.

[Kazar] Kazar, Michael Leon,
"Synchronization and Caching Issues in the Andrew File System,"
USENIX Conference Proceedings, USENIX Association, Berkeley, CA, Dallas Winter 1988, pages 27-36.
A description of the cache consistency scheme in AFS. Contrasted with other distributed file systems.

[Macklem] Macklem, Rick,
"Lessons Learned Tuning the 4.3BSD Reno Implementation of the NFS Protocol,"
Winter USENIX Conference Proceedings, USENIX Association, Berkeley, CA, January 1991.
Describes performance work in tuning the 4.3BSD Reno NFS implementation. Describes performance improvement (reduced CPU loading) through elimination of data copies.

[Mogul] Mogul, Jeffrey C.,
"A Recovery Protocol for Spritely NFS,"
USENIX File System Workshop Proceedings, Ann Arbor, MI, USENIX Association, Berkeley, CA, May 1992.
Second paper on Spritely NFS proposes a lease-based scheme for recovering state of consistency protocol.

[Nowicki] Nowicki, Bill,
"Transport Issues in the Network File System,"
ACM SIGCOMM newsletter *Computer Communication Review*, April 1989.
A brief description of the basis for the dynamic retransmission work.

[Pawlowski] Pawlowski, Brian, Ron Hixon, Mark Stein, Joseph Tumminaro,
"Network Computing in the UNIX and IBM Mainframe Environment,"

Uniforum '89 Conf. Proc., (1989)
Description of an NFS server implementation for IBM's MVS operating system.

[RFC1014] Sun Microsystems, Inc.,
"External Data Representation Specification,"
RFC-1014, DDN Network Information Center, SRI International, Menlo Park, CA.
Proposed standard for canonical format for data exchange, used with RPC.

[RFC1057] Sun Microsystems, Inc.,
"Remote Procedure Call Specification,"
RFC-1057, DDN Network Information Center, SRI International, Menlo Park, CA.
Remote procedure protocol specification.

[RFC1094] Sun Microsystems, Inc.,
"Network Filesystem Specification,"
RFC-1094, DDN Network Information Center, SRI International, Menlo Park, CA.
NFS version 2 protocol specification.

[Sandberg] Sandberg, R., D. Goldberg, S. Kleiman, D. Walsh, B. Lyon,
"Design and Implementation of the Sun Network Filesystem,"
USENIX Conference Proceedings, USENIX Association, Berkeley, CA, Summer 1985.
The basic paper describing the SunOS implementation of the NFS version 2 protocol, and discusses the goals, protocol specification and trade-offs.

[Srinivasan] Srinivasan, V., Jeffrey C. Mogul,
"Spritely NFS: Implementation and Performance of Cache Consistency Protocols",
WRL Research Report 89/5, Digital Equipment Corporation Western Research Laboratory, 100 Hamilton Ave., Palo Alto, CA, 94301, May 1989.
This paper analyzes the effect of applying a Sprite-like consistency protocol applied to standard NFS. The issues of recovery in a stateful environment are covered in [Mogul].

[X/OpenNFS] X/Open Company, Ltd.,
X/Open CAE Specification: Protocols for X/Open Internetworking: XNFS,
X/Open Company, Ltd., Apex Plaza, Forbury Road, Reading Berkshire, RG1 1AX, United Kingdom, 1991.
This is an indispensable reference for NFS version 2 protocol and accompanying protocols, including the Lock Manager and the Portmapper.

[X/OpenPCNFS] X/Open Company, Ltd.,
X/Open CAE Specification: Protocols for X/Open Internetworking: (PC)NFS, Developer's Specification,
X/Open Company, Ltd., Apex Plaza, Forbury Road, Reading Berkshire, RG1 1AX, United Kingdom, 1991.
This is an indispensable reference for NFS version 2 protocol and accompanying protocols, including the Lock Manager and the Portmapper.

Index

A

ACCESS procedure 24
attributes 11
  fattr3 11
  sattr3 14
  settable 14
authentication 3
  AUTH_DES 3, 68
  AUTH_KERB 3, 68
  AUTH_NONE 3
  AUTH_UNIX 3, 67
  netname 68
  RPC 3

C

caching 4, 70
  client 4, 5
  consistency 12, 13
  server 4
  wcc_data 13
client 1
COMMIT procedure 63
CREATE procedure 33
credentials
  for ACCESS checking 24
  UNIX 68

D

data consistency, see caching
duplicate request cache 68, 69

E

error
  NFS3ERR_NOTSUP 3
executable
  permissions issues 68
external data representation 2
  discriminated union 2
  hyper 2

F

file system
  export 22
FSINFO procedure 58
FSSTAT procedure 56

G

GETATTR procedure 19
gid 25

I

idempotent request
  definition 68

L

LINK procedure 48
lock manager 1
LOOKUP procedure 22

M

meta-data 4, 30
MKDIR procedure 36
MKNOD procedure 40
mode 25
mount 67
mount protocol 1
MOUNTPROC3_DUMP procedure 78
MOUNTPROC3_EXPORT procedure 81
MOUNTPROC3_MNT procedure 77
MOUNTPROC3_NULL procedure 76
MOUNTPROC3_UMNT procedure 79
MOUNTPROC3_UMNTALL procedure 80
MTU 59

N

non-idempotent request
  definition 68
  destructive replay 68
NULL procedure 18

P

PATHCONF procedure 61
pathname
  interpretation 67
  interpretation of .. 67

R

READ procedure 28
  nfsdata 29, 31
READDIR procedure 50
READDIRPLUS procedure 53
READLINK procedure 26
remote procedure call 2
  authentication, see authentication
remove
  of open files 67
REMOVE procedure 42
RENAME procedure 46
RMDIR procedure 44
RPC, see remote procedure call

S

server 1
SETATTR procedure 20
stable bit 30
stable storage 4, 30, 63
state
  file system 4
stateless 4, 67
SYMLINK procedure 38
synchronous operations 4

U

UID 68
uid 25

W

WRITE procedure 30

X

XDR, see external data representation