

NAME

akfquery – use form data via CGI in shell scripts

SYNOPSIS

akfquery *field_name* [*alternative*]

DESCRIPTION

With the program **akfquery** you can use forms with the **GET**-method in shell scripts.

A *field_name* must be provided. The program outputs the decoded field value to the standard output. If the field doesn't exist or if it is empty, then it outputs the *alternative*, if given. Otherwise the output is empty.

If the field has multiple values, the program outputs multiple lines. This can happen for example with checkboxes.

Special HTML-characters (<&"') are converted to HTML-entities.

Warning

Shell scripts are suitable for quick temporary solutions or drafts in local, private networks. But they shouldn't be used for productive work on the open Internet.

ENVIRONMENT

QUERY_STRING

contains the form data with the method GET

EXAMPLES

```
# save in variable for reuse
name=$(akfquery name "unknown")

echo "<p>Hello $name.</p>"

# for single use output you can directly include it
# the line breaks don't really matter for HTML
echo "<p>age:"
akfquery age
echo "</p>"

# hobby is done with checkboxes
echo "<ul>"
for i in $(akfquery hobby "no hobbies")
do
    echo "<li>$i</li>"
done
echo "</ul>"
```

AUTHORS

Copyright © 2018 Andreas K. Förster

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but **WITHOUT ANY WARRANTY**; without even the implied warranty of **MERCHANTABILITY** or **FITNESS FOR A PARTICULAR PURPOSE**. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>.

SEE ALSO

akfwebserver(1)

<https://akfoerster.de/p/akfnetz/>