Inter-Client Exchange Library

X Consortium Standard

Ralph Mor, X Consortium

Inter-Client Exchange Library: X Consortium Standard

© !"

" $ % % & & % % ' $ & $ $ &!
" % ( )* % ')+ $ * % ' ' ! & & !$ ' ! "
! & " $ % " ! $! ! & $, & % * % ' $ "
' " * % ' %! $ $! - & % ' & $.

/ 0 & & $ " & & !$ $ & ! %
* % '

/12 *34/56 2 7* # 3 7828)6* 7*) 57/139/ 56 6:/; 34 6:; <7:8 2 # 2** 3 7 #=728 7: =987:>
?9/ :3/ =7 7/28 /3 /12 56 6:/72* 34 2 16:/6?7=7/; 47/:2** 43 6 #6 /7 9=6 #9 #3*2 6:8
:3:7:4 7:>2 2:/ 7: :3 2 2:/ *16== /12 3:*3 /79 ?2 =76?=2 43 6:; =67 86 6>2* 3
3/12 =76?7=7/; 512/12 7: 6: 6 /73: 34 3:/ 6 / /3 / 3 3/12 57*2 6 7*7:> 4 3 39/ 34
3 7: 3::2 /73: 57/1 /12 *34/56 2 3 /12 9*2 3 3/12 826=7:>* 7: /12 *34/56 2

2@& & $ & " % !" ! $ $0 '
" ! $ * % ' ' ! ' ! A % " !"

Table of Contents

30 0 ' % 7 2
B / 7 2 = = ! 7 % & 7 2 B
7 $ $ 6!$ &
1 $ 4 $ = : "
C : # % @ C
&
&D % # &
6! & $
7 2 &
3 7 2 &
= % 7 2 & C
1 ? $ 6! & % 7 2 &
6&& 7 2 &
7 2 &
& 5 & # & $! B
E # & * ! $ * ! $ ' BB
& B
B
9 7 2 7 % " 4! & B
B 7 2 B
* $ 7 2 B
$ 7 2 B
2 1 $ C
! / $ *!
C & ! 4! & E
6&D ' $ "
6 6! & 9 4! &
? 7/ 6>7 33<72 6! &

Chapter 1. Overview of ICE

/ !" ! & & ' " " $ & "
" $! & 0 $ $
/ 7 2@& (7 2+ & $ $ 0 $ % " ' D %
! $!& & ' " " D ! % & "" " &
" $ "! @ $ 0 & &

Chapter 2. The ICE Library - C Language Interface to ICE

6 & ' ! A 7 2 "! % & !$ $
' 7 2 2 & & $ "& $ "- & $
% " BCC (' & & ! $ %% "- & $ % " & + /
@ % & & & ' & '
% & & "$ & 6! & " F! $ 6 & &
& & ' & $ ' % & & &
% ($ " @ " + 3 & 7 2 & &
$ ' ' & % & $ ProtocolSet-
up $) & 0) 0 & 3 & & && Proto-
colSetup (& ! & " F! $+ ' & $
" & % & & & ! &
" & 0 7 2 & & % %
7 2 ' & & 0 7 2 & & ! 7 2
$ $ % ' & ! & & ! $ '

/ 7 2 ! A & &D & & " " 9 & &D
' ProtocolSetup " $! & $ &
6 $$ % " 0 $!%% $!
' & &D ' % &! "

Chapter 3. Intended Audience

/ $&!" $$ " % " " % & $
% 7 2 / & & ' ! A 7 2 ' "D &
$ 0 $! & $ & "D & 7 2
1 ' 0 " & ' 0 "D " & 7 2
$ && 7 2 & & (% @ " " && &
& % "& + ?! & !$ $ $ $
$ % 7 2 % " &

Chapter 4. Header Files and Library Name

/ $ % G ,72,72 H$% % 72 $!&! $
%!& ICElib.h &!$ $ % G ,72,72 H ' & $
% % 72 & # & $ $ $' "
!$ &!$ $ % G ,72,72" H

6 & !$ D 72 ! 72

Chapter 5. Note on Prefixes

/ % ' " % @ ! $ $! ' &
ProtocolSetup $ & $ ' ProtocolReply

I IcePo 7& # & 3

I IcePa 7& # & 6&&

Chapter 6. Protocol Registration

7 $ % ' & @& " % 0 & & $ "!
& ' 7 2 / ! % % & $
"- & $ % & $ 0 $ & &D % &
" $ $! & / ' %! &
.

I 3 $ $ $ ProtocolSetup

I 3 $ $ $ ' ProtocolReply

7 & "" $ $ & &&! % ' &
7 2 & & 7% & &&! % 7 2 & & & $
& % 0 % " ' & ProtocolSetup & 0 $!
& $ 7% & %
& % 7 2 & & & ! ! $ D 0 $
0 & & $

/ IceRegisterForProtocolSetup %! & ! $ & $ % &
ProtocolSetup

```
int IceRegisterForProtocolSetup( *protocol_name, *vendor, *release,
version_count, *version_recs, auth_count, **auth_names, *auth_procs,
io_error_proc);
```

6 & % " % &

6 0 $ ' " & & % $ &

6 ' " & & % $ &

/ !" % $ %% 0 % & ! $

= % 0 $ & $ & &D

/ !" % ! & " $! $

/ % ! & " $! $

/ % ! & & &D % & ! &
" $

73 $:9==

IceRegisterForProtocolSetup ! "- & $ 0 $ %
&&! $ 7 $ & ! & 0 & IceProtocolSetup %! &
$ & $ ' "- & $ 3 & & & 0 $ "
% & ! $! "- & $

6 & " ! "! 0 % " & /
0 J & !" & % % ! $ 0 % & ' &
A $ $ & $ % % & 2 & 0 & $ & %
"- $ " 0 % & ' & &D ! $ %
& & " "

$ % !& K
" - J0 L
" J0 L
7& # # & # & & J" J &L
M 7& # &L

/ IcePoProcessMsgProc & &D % & % "
 & & 0 $ & $ ProtocolSetup 4 %!
% " &D % # &

6! & " F! $ % & & & " & 0 /
& "! ! & " $! ' 7 2
/ ! J " $! J & !" % ! & "
$ & &D A $ $ & $ % % & 4 % "
IcePoAuthProc & &D 6! & $

/ IceIOErrorProc & &D 0 D $ % 7 2 & & ! @ & $
D ;! ! $:9== % J J & % $ % $
4 %! % "

/ IceRegisterForProtocolReply %! & ! $ & $ % &
$ ProtocolSetup' ProtocolReply

Bool **IceRegisterForProtocolReply**(**protocol_name*, **vendor*, **release*, *version_count*, **version_recs*, *auth_count*, ***auth_names*, **auth_procs*, *host_based_auth_proc*, *protocol_setup_proc*, *protocol_activate_proc*, *io_error_proc*);

6 & % " % &

6 0 $ ' " & & % $
&

6 ' " & & % $
&

/ !" % $ %% 0 % & !
$

= % 0 $ & $ & &D

/ !" % ! & " $! $

/ % ! & " $! $

/ % ! & & &D % & !
& " $

1 $! & & &D

6 & &D 0 D $ ' ! & !&
& $ $ % ProtocolSetup ! % Protocol-
Reply

6 & &D 0 D $ % ProtocolReply

73 $:9==

IceRegisterForProtocolReply ! "- & $ 0 $ %
&&! $ / "- & $! $! $! F! " %
&

6 & " ! "! 0 % " & /
0 J & !" & % % ! $ 0 % & ' &
A $ $ & $ % % & 2 & 0 & $ & %
"- $ " 0 % & ' & &D ! $ %
& & " "

$ % !& K
"- J0 L
" J0 L
7& # # & # & & J" J &L
M 7& # &L

/ IcePaProcessMsgProc & &D % & % "
& & 0 $ & && $ ProtocolSetup 4 %!
% " &D % # &

6! & " F! $ % & & & " & 0 /
& "! ! & " $! ' 7 2
/ ! J " $! J & !" % ! & "
$ & &D A $ $ & $ % % & 4 % "
IcePaAuthProc * 6! & $

7% ! & % $ & " ProtocolSetup
F! $! & IceHostBasedAuthProc & &D 0 D $ '
" % & 7% & &D ! True Proto-
colSetup ' !&& $ 0 ! ! & % $:
! & & %% & 0 $ $ IceHostBasedAuthProc
' & ' ! True 7% $! & '$! ! $
:9== % J $J ! J &

```
Bool HostBasedAuthProc( *host_name);
```

/ " % & ProtocolSetup

/ J " !" % % " , '
% K & $ & & M

? & ! ProtocolSetup " $! & $ &
0 & &D & $ " ' % % $' Pro-
tocolSetup & " $ / &&! ' 7 % Ice-
ProtocolSetupProc & &D 0 D $ % ! & !&& %! & "
$! % 7 2 $ ProtocolReply 6 ! & F! $ %
& ! $ & $ " 7% IceProtocolSetupProc !
!&& %! ! 7 2 ' $ ProtocolReply $ 0 D
IceProtocolActivateProc & &D 3 ' '
& ProtocolSetup

/ IceProtocolActivateProc & &D $! $ $
% & $ " "" $ % '

ProtocolReply;! !$:9== % & J& 0 J & % $
  & &D

Status **ProtocolSetupProc**(*ice_conn*, *major_version*, *minor_version*, **vendor*, **release*, **client_data_ret*, ***failure_reason_ret*);

/ 72& & -&

/ "- 0 % &

/ " 0 % &

/ 0 $ $ &

/ $ &

$ & &D

4 ! ! $

/ $ & J$ J !" ' $ IcePa-
ProcessMsgProc & &D' 0 " 0$% &
72& &

/ 0 $ $!$ % $' free'
 $$

7% % ! &&! IceProtocolSetupProc !$! A ! '
  & $! % ! % ! J J / 72
' % % ""

/ IceProtocolActivateProc & &D $% $ % '.

void **ProtocolActivateProc**(*ice_conn*, *client_data*);

/ 72& & -&

/ & $ IceProtocolSetupProc & &D

/ IceIOErrorProc & &D 0D$ % 72 & & ! @ & $
 D ;! !$:9== % J J & % $ % $
4 %! % "

Callbacks for Processing Messages

5 & $ & '$ $ 72& &
(0 select & IceProcessMessages %!& 5
IceProcessMessages $ 72" $ ' "- &$
A (0$% 72 & + $ & %!& ' $
  % " ! &D $ & && $

7% " 0 & $ ProtocolSetup Ice-
PoProcessMsgProc & &D 0D$

void **PoProcessMsgProc**(*ice_conn*, *client_data*, *opcode*, *length*, *swap*, **reply_wait*, **reply_ready_ret*);

/ 72& & -&

$ & $' & 72& &

/ " &$ % "

/ (E ! + % " $ 72 $

6 % $& % ' &

7$& % 0D & ' %

7% True $

7% " 0 & && $ ProtocolSetup IcePa-ProcessMsgProc & &D 0D$

void **IcePaProcessMsgProc**(*ice_conn*, *client_data*, *opcode*, *length*, *swap*);

/ 72& & -&

$ & $' & 72& &

/ " &$ % "

/ (E ! + % " $ 72 $

6 % $& % ' &

7 $ $ " % & &D !$! "& $% $ % ! ($ 72 + : ' " & 6 & 0 & % $ 72 $ ' ' $ 72 % &

7 % & &D & J$!" & $ ' $ ProtocolSetup " 7 & % IcePoProcessMsgProc & $ ' & IceProtocolSetup 7 & % IcePaProcessMs-gProc & $ ' IceProtocolSetupProc & &D

/ IcePoProcessMsgProc & &D $ & &D J' !" 7% J' :9== 72 @ & %!& " & 0 & &D 4 @ " % * ")* 0 ;! %) " %!& !$ % & %)* 0 ;! %) 0 & &D / $ % '!& & &D'!$ $% $ " " $ $

1'0 % J' :9== & ' % % " 0 ! / J' % IceReplyWaitInfo

$% !& K
! $ F! & J %J F! L
"- J & $ J %J F! L
" J & $ J %J F! L
7& # L
M 7& 5 7 % L

IceReplyWaitInfo & "- ," & $ $ F! & !" %
" % ' & ' $ 7 &
" % $ (& ! $ & IcePointer
+ 7 " & ' 0 " % @ $ A $
& ' % ' 0 0 $ $!& ! $
% @ $ A $ 7% 0 $ '! $ @ & $
IcePoProcessMsgProc & &D ' 0 & $$ " " $
(+ " " % @ $ A !& ! 7% $ 0
(% @ " 0 + & ' %
'! $ -! % @ $ A & $ $
IcePoProcessMsgProc & &D '! $ & $ 7
% & & 0 % " " & $
%

7% J' :9== $ IcePoProcessMsgProc
! J' (& &D ' $+
J $ J !" ! $ True : ! $
! $ % & $ ' $ % 3 ' Ice-
PoProcessMsgProc ! $ $ 0 D
$ %

7% J' :9== & "! D 0 !
J $ J & ! " :9==

/ IcePaProcessMsgProc & &D $! $ ' "
& 0 & &D 4 @ " % * ")7
& F!) " %! & ! $ % & %)7 &
F!) 0 & &D

/ IcePaProcessMsgProc & &D $ 0 J' D Ice-
PoProcessMsgProc $ & ! & & 0 ! $ 0
&D % (% &D & &&! % & & & $ &
$ && & +

Authentication Methods

6 $ $ & "! ! & " $
! ' 7 2 4 & ! & " $ '
& &D " $.

I 3 $ $ ProtocolSetup

I 3 $ $ && - & F!

IcePoAuthProc & &D 0 D $ % & $ ProtocolSet-
up / & &D "! $)6! & F! $)
" ! F!)6! & : @ #) "
&

IcePoAuthStatus **IcePoAuthStatus** (*ice_conn*, *client_data*, *opcode*);

/ 7 2 & & - &

6 % ! ! & & &D
& $!

7%True ! & 0 $ %!& !$&
! ' " / !" !$
$

7%True ! J$ " 0 ' $($ $
& +

/ (+ % ! & $

/ $ % " ! &

/ (+ % $! $

/ $! $

7% ! & &$! &! $!
! & !$ & $!

6! & " F! 0 $ $! &
" $ 6 ! IcePoAuthProc " & $ " & ' !
& & $ " ' 0 " $ ' & 0
& 6 % & ProtocolSetup N ! J J :9== $ %!&
!$ A $ 7 ! F! 0 & %
& &D !$! $ 0 ! $
& &D

7% $ $ ' D 78 % & && ProtocolSetup & $
& IceConnectionString %!&

7 2 ' % % J$ J $ J J
' free

/ ! J$ " 0 &D %" " 7% $ "!
D $ 0 & % & &D ! " D & %

/ IcePoAuthProc !$! % % ! 0 ! .

I IcePoAuthHaveReply 0

I IcePoAuthRejected ! & - & $

I IcePoAuthFailed ! & % $

I IcePoAuthDoneCleanup $ & !

IcePaAuthProc & &D 0 D $ % & & 0 $ ProtocolSet-
up

IcePoAuthStatus **PoAuthStatus** (*ice_conn*, **auth_state_ptr*, *swap*, *auth_datalen*, *auth_data*, **reply_datalen_ret*, **reply_data_ret*, ***error_string_ret*);

/ 7 2 & & - &

6 % ! ! & & &D
& $!

7%True ! J$ " 0 ' $ ($ $
& +

/ (+ % & ! &
$

/ ! & $ % " &

/ % ! & $! $

/ ! & $! $

7% ! & - & $ %
! $

6! & " F! 0 $ $! &
" $ 6 ! IcePaAuthProc " & $ " & ' !
& & $ " ' 0 " $ ' & 0
& 6 % & ProtocolSetup ! J$ A N ! J J
:9== $ %! & ! $ A $ 7 ! F!
0 & % & &D ! $! $ 0 !
$ & &D

7% $ $ ' D 78 % & && ProtocolSetup & $
& IceConnectionString %! &

/ ! J$ " 0 &D %" " 7% $ "!
D $ 0 & % & &D ! " D & %

7 2 ' % " $ % J$ J $
J J ' free

/ IcePaAuthProc ! $! % % ! 0 ! .

I IcePaAuthContinue & ! (+ ! &

I IcePaAuthAccepted ! & && $

I IcePaAuthRejected ! & - & $

I IcePaAuthFailed ! & % $

Chapter 7. ICE Connections

7 $ % ' & 72 & & & '
% & & $ & & & & '
& & ' $ &! %

Opening an ICE Connection

/ 72 & & ' & (' % & & +
! IceOpenConnection

```
IceConn IceOpenConnection( *network_ids_list, context,
must_authenticate, major_opcode_check, error_length,
*error_string_ret);
```

* & % ' D 78(+ % &

! 6 F! - & :9== 9 $ $ "
% 72 & & & $ ('+

7%True & " ! &

9 $ % & '72 & & & $ (
'+

= % J J !" $

! ! " $ " % /
J J !" ! ! $ " "
: " J ! $

IceOpenConnection ! F! 72 & & - & % !&& $ L
' ! :9==

/ ' DJ $ J !" & % ' D 78 $ & ""
6 " ' "$! % ' D 78 7% % " '
"$! & $ ' D 78 $ 2 & ' D 78 % '
% " .

& ,
G "H.G !" H
$ &
,G "H..G - "H
S
& ,G "H.G H

& ' 0 " % %! & ! $
"D & IceOpenConnection 5 IceOpenConnection & $ "
! 0 ! $72 & & (% & "+
1 '0 & ' & $72 & & $ $

/ & @ !" ! $ $ " % 72 & & & $ 7%
& @ :9== & ' ' & & 7% & @

:9== & ' ! 0 ! $72& &
$%% :9==& @ & $'

7 $$ %"- J &$J& &D & A "- &$ 0 !
0 ! & $72& & ' !$ % "- &$ & 0
& & / & !$ % &"! 72& & ' '
& % " &

6 ! & F! " $$ 72 /
" $ '& ! & $ $ " " $ $

6% IceOpenConnection & $ & $ $ ProtocolSetup(
0$$ IceRegisterForProtocolSetup' & $+ & 0 ProtocolSetup
(0$$ IceRegisterForProtocolReply' & $+

Listening for ICE Connections

' && 72& & "! % & IceListenForConnections
IceListenForWellKnownConnections & % & & 6
% F!)) -& ! $ % & % " $
0 (% @" 9 @8" /#82 $ +

:" & ' 72 & 0 " & $
! -& *!& & ' ! IceComposeNetworkIdList @
& & " $"D " 0 & %
& & 7 & & " & % & % & &
$ -& " *!& & " ! IceListenForWell-
KnownConnections &% " % -&

Status **IceListenForConnections**(*count_ret, **listen_objs_ret,
error_length, *error_string_ret);

! !" % -& & $

! % F! -&

/ % J J !" $

! ! " $ " % /
J J ! ! $"" :"
J !$

/ ! 0 ! % IceListenForConnections A % % ! $ 0
0 ! % !&&

Status **IceListenForWellKnownConnections**(*port_id, *count_ret,
**listen_objs_ret, error_length, *error_string_ret);

* &% $ %& % $$ (+
$ / 0 ! "! & (),)H &""
())+ & & L 0$% %!! !

! !" % -& & $

/ !"O 72 " " ! 72! % (6 $@6+

! % F! - &

! % F! - &

/ % J J !" $

! ! " $ " % /
J J ! ! $"" : "
J ! $

IceListenForWellKnownConnections & !& % ' D 78 $
& D ' J $ $ " & - & %
! # J $!" - " % 7 2 ' D
78 7% - & % &! ' D 78 & & $ ' D 78
$ 7% - & & $ IceListenForWellKnownConnections
! % !

/ ! 0 ! % IceListenForWellKnownConnections A % % ! $
0 0 ! % !&&

/ & $ % - & ! IceFreeListenObjs

```
void IceFreeListenObjs( count,  *listen_objs);
```

/ !" % - &

/ - &

/ $ & '& & - & ! select $ & &
$' - &

/ $ & ! IceGetListenConnectionNumber

```
int IceGetListenConnectionNumber( *listen_objs);
```

/ - &

/ ' D 78 & $' - & ! IceGetListen-
ConnectionString

```
char IceGetListenConnectionString( listen_obj);
```

/ - &

6 ' D 78 % ' % " .

&,
G "H.G !" H
$ &
,G "H..G - "H
S
& ,G "H.G H

/ &" & % ' D 78 $ &"" (
% " & A $ IceOpenConnection ! IceComposeNetworkIdList

```
char IceComposeNetworkIdList( count,  *listen_objs);
```

/ !" % -&

/ -&

Host Based Authentication for ICE Connections

7% ! & % ' & " 72& & $
& F! $! & $! &
&$! " 0D$ 0$ & & % & & & 2&
-& !& & &D & $' $ & &D !
IceSetHostBasedAuthProc %!&

```
void IceSetHostBasedAuthProc( listen_obj,  host_based_auth_proc);
```

"# $ / -&

/ $! & &$!

?$%! & -& $! & &$! & $
' # :9==% J $J ! J &! %% $! &
% ' 0 !

```
Bool HostBasedAuthProc( *host_name);
```

/ " % & $ 72& &

/ J " !" % " , '
%K& $& & M

7%IceHostBasedAuthProc ! True && ' $ 0 !
! & % $: ! & & %%& 0 $ $
IceHostBasedAuthProc'& ' ! True

1 $! & '$ ProtocolSetup " / & &D
&% $ IceRegisterForProtocolReply %!& (%
+

Accepting ICE Connections

6% & & " $ & $ -& ! $ IceListenForConnections ! !$& IceAcceptConnection/ ! ' F!
72& & -&

```
IceConn IceAcceptConnection( listen_obj,  *status_ret);
```

/ -& '& '& & ' $ & $

! ! %"

/ !J !" % % ' 0 !.

I IceAcceptSuccess && !&& $$ $ %!& !
'& & -&

I IceAcceptFailure && % $ $ %!& ! :9==

I IceAcceptBadMalloc "" & % $ $ %!& ! :9==

7 $ & '& & ! !$& select % $ &
& $' -& 5 '& & $ & $ IceAcceptConnection%!& !$ & $ IceAcceptConnection" ! '
72& & $ / &! % & &
& &"0 $! & " & ?&! 72 &
&D $' % & & &"0 $(% &D & &&! %
& & & $ & + & "! ' % & &
! &"0 $

/ % ' !$ &$ $" '& & && $.

```
new_ice_conn = IceAcceptConnection (listen_obj, &accept_status);
if (accept_status != IceAcceptSuccess)
{
     close the file descriptor and return
}

status = IceConnectionStatus (new_ice_conn);
time_start = time_now;

while (status == IceConnectPending)
{
     select() on {new_ice_conn, all open connections}

     for (each ice_conn in the list of open connections)
          if (data ready on ice_conn)
          {
               status = IceProcessMessages (ice_conn, NULL, NULL);
               if (status == IceProcessMessagesIOError)
                    IceCloseConnection(ice_conn);
          }
     if data ready on new_ice_conn
     {
          /*
          * IceProcessMessages is called until the connection
          * is non-pending.  Doing so handles the connection
          * setup request and any authentication requirements.
          */

          IceProcessMessages ( new_ice_conn, NULL, NULL);
          status = IceConnectionStatus (new_ice_conn);
     }
     else
     {
          if (time_now - time_start > MAX_WAIT_TIME)
               status = IceConnectRejected;
     }
```

```
}

if (status == IceConnectAccepted)
{
     Add new_ice_conn to the list of open connections
}
else
{
     IceCloseConnection
     new_ice_conn
}
```

6% IceAcceptConnection & $ $ & & 0 $ $
& $ & 0 ProtocolSetup(0$$ IceRegisterForProto-
colReply' & $+ $ ProtocolSetup(0$$ IceRegisterForPro-
tocolSetup' & $+

Closing ICE Connections

/ & 72& & & $' IceOpenConnection IceAcceptConnec-
tion! IceCloseConnection

IceCloseStatus **IceCloseConnection**(*ice_conn*);

/ 72& & &

/ &! & 72& & % ' & $ "! " .

I / "! 0 & $A 72& & 5
IceOpenConnection & $! 0 ! $72& &
7% ! @ & & & " % & &!
& & * & 72& & & & IceOpen-
Connection"! " & $' & IceCloseConnection/ & &
& & & $ & IceCloseConnection

I / "! 0 & $A 2& " ProtocolSet-
up !&& $ & & & 0 & &! & " $
5 & @ & ! & & & Ice-
ProtocolShutdown%!& !$ & $'& $& " & 0
& &! (& & +

I 7% !$' $ & & & $
% 72& & "! 0 & & & $

IceCloseConnection ! % % ' 0 !.

I IceClosedNow 72& & ' & $ " / ' & &$!
' 0D$ $ & & ' % $

I IceClosedASAP 73 $ &&! $ & & ! IceCloseCon-
nection & $' $ IceProcessMessages/ ' & &
$! 0 0D$ " ! & & ' % $
(' 0 & A $ IceProcessMessages !
! % IceProcessMessagesConnectionClosed

I IceConnectionInUse & & ' & $ " &!
! $ & 0 &

I IceStartedShutdownNegotiation & & ' & $ "
$!$' $' & $ % 72&
& 5 & & &! & $ IceProcessMessages' !
! % IceProcessMessagesConnectionClosed

5 D ' & $ % 72& &
" $ & & ' ! !$' IceSetShut-
downNegotiation %!& !$ & $! %% !$' /
' 0 IceCloseConnection % "' D & &

void **IceSetShutdownNegotiation**(*ice_conn*, *negotiate*);

60 $72& & -&

7%False !$' ' ! $ %%

/ & &D !$' ! % 72& & ! IceCheckShut-
downNegotiation

Bool **IceCheckShutdownNegotiation**(*ice_conn*);

60 $72& & -&

IceCheckShutdownNegotiation ! True % !$' ' D
& & & L ' ! False: $%! %
& & 7 & & $' IceSetShutdownNegotiation %!&

Connection Watch Procedures

/ $$ ' & &$! ' & $ & " 72 '& &
0 IceOpenConnection IceAcceptConnection & & & 0
IceCloseConnection! IceAddConnectionWatch

Status **IceAddConnectionWatch**(*watch_proc*, *client_data*);

/ ' & &$! 0D ' 72 & &
&

/ ' $ ' & &$!

/ ! 0 ! % IceAddConnectionWatch A % % ! $ 0 0 !
% !&&

: 0 & IceOpenConnection" "72& &
7 !& & ' & &$! 0D$' & & %
& $(% ! & !&& $+ *" &! & & "
$ ' & &$! & $ % IceCloseConnection &! &
& & (% 7& % $+

/ ' & &$! 0 ! %! % & $ $$ % $
& & " D' '& & & $ $ "0 % $
& ' & & $ $?&! & & $D '

' $$ $ "0 % $ & % " & " D'!$ $%
%&! ' ! ' & &$!

! ' & &$! " $' 72 : !"
!$ "$! $ % 0&

7% " 72& & ' $ & $ 72 "
' & &$! $ ' & &$! ' 0D$
% & % 72& & (' !" True

/ ' & &$! % IceWatchProc

void **WatchProc**(*ice_conn*, *client_data*, *opening*, **watch_data*);

/ $ & $72& & IceConnectionNumber
% $ & & $' & &

$ & % $ & IceAddConnectionWatch

7%True & & $ 7% False & &
& $

!$ 0 & $

7% True & !$ N' & J$ $ "
$ 0 ! & & & $ $ ' & &$! 0D$
' False

/ "0 ' & &$! ! IceRemoveConnectionWatch

void **IceRemoveConnectionWatch**(*watch_proc*, *client_data*);

/ ' & &$! ' $ IceAddConnectionWatch

/ & J$ ' $ IceAddConnectionWatch

Chapter 8. Protocol Setup and Shutdown

/ & 0 & 0 72& & ! IceProtocolSetup

IceProtocolSetupStatus **IceProtocolSetup**(*ice_conn*, *my_opcode*, *client_data*, *must_authenticate*, **major_version_ret*, **minor_version_ret*, ***vendor_ret*, ***release_ret*, *error_length*, **error_string_ret*);

60 $72& & -&

/ "- &$ % & ! ! $
IceRegisterForProtocolSetup

/ & $ $ ' $
IcePoProcessMsgProc& &D

7%True & " ! &

/ "- 0 % & ! $! $

/ " 0 % & ! $! $

/ 0 $ & % $ & &&

/ & % $ & &&

* & % % J J !" $

! ! " $ " % /
J J !" ! ! $""
: " J ! $

/ 0 $ J $ J !$ % $' free'
$ $

IceProtocolSetup ! % % ' 0 ! .

I IceProtocolSetupSuccess "- J0 J " J0 J
0 $ J J

I IceProtocolSetupFailure IceProtocolSetupIOError & &D
J J % % ! / "- J0 J " J0 J
0 $ J J

I IceProtocolAlreadyActive & $ & 0 & &
/ "- J0 J " J0 J 0 $ J J

/ % 72 ' 0 & ' ! $ 72
& & ! IceProtocolShutdown

Status **IceProtocolShutdown**(*ice_conn*, *major_opcode*);

60 $72& & -&

/ "- &$ % & !$'

/ ! 0 ! % IceProtocolShutdown A % % ! $ 0 0 !
% !&&

4 ! ' &&! % "- &$ ' 0 $3 & %
"- &$ ' 0 & 0 $ & & ? & 0 $ ' "
ProtocolSetup !&& $$ & & : 72$ $% '
& ! & & !$'

Chapter 9. Processing Messages

/ & &" " 72& & ! IceProcessMessages

IceProcessMessagesStatus **IceProcessMessages**(*ice_conn*, **reply_wait*, **reply_ready_ret*);

60 $72& & -&

7$& % ' $%

7% True ! $

IceProcessMessages !$ '' .

I 7 % & " " $ &D & IceProcessMes-
sages $!

I 7 & $ & & IceProcessMessages' J' :9==
select ' $ $ 72& & /
72 " & A " &" " : "
&D$% ' & $ 0D & &D

IceReplyWaitInfo& "-," &$ $ F! & !" %
" % '& ' $7 &
" % $ (& !$& IcePointer
+ 7 " & ' 0 " %@$ A $
& ' % ' 0 0$$!&! $
%@$ A $ 7% 0 $ '!$ @ & $
IcePoProcessMsgProc& &D' 0 & $$ "" $
(+ "" %@$ A !&! 7% $ 0
(% @" 0 + & ' %
'!$ -! %@$ A & $ $
IcePoProcessMsgProc& &D'!$ & $
7 % & & 0 % ! ""
& $ %

```
typedef struct {
     unsigned long sequence_of_request;
     int major_opcode_of_request;
     int minor_opcode_of_request;
     IcePointer reply;
} IceReplyWaitInfo;
```

7% J' :9== $ IceProcessMessages
! J' (& &D' $+
J $J !" ' True

7% J' :9== & " :9==% J $J $
! $ 0 !' $

IceProcessMessages ! % % ' 0 !.

I IceProcessMessagesSuccess &&! $

I IceProcessMessagesIOError 73 &&! $ $ & "! @ &
& & & & IceCloseConnection

I IceProcessMessagesConnectionClosed 72 & & & $
(& % & & ' $% $ &! % !$'
&! IceProcessMessages 0 ' A + 8 " &
& 72& & & % $

Chapter 10. Ping

/ $)#)" & $ % 72& & !
IcePing

```
Status IcePing( ice_conn, ping_reply_proc, client_data);
```

60 $72& & -&

/ & &D 0D ' # 0

/ ' $ IcePingReplyProc & &D

IcePing ! A % % ! $ 0 0 ! % !&&

5 IceProcessMessages & # ' 0D IcePingReplyProc & &D

```
void PingReplyProc( ice_conn, client_data);
```

60 $72& & -&

/ & $ &% $ & IcePing

Chapter 11. Using ICElib Informational Functions

```
IceConnectStatus IceConnectionStatus( ice_conn);

IceConnectionStatus  !     ! %  72&  &   /      !
0 !  .

I IceConnectPending   &  &     0 $  (    !  &     D
     &+ /       0   &  &   &   $                    IceAcceptConnection

I IceConnectAccepted   &  &       && $ /       0
  &  &   &   $          IceAcceptConnection

I IceConnectRejected   &  &   $    -& $(     !  &
  %  $+ /       0   &  &   &   $                    IceAcceptConnection

I IceConnectIOError   73      &&! $    &  &

char  *IceVendor( ice_conn);

IceVendor  !    72     0 $  $  %&   %        $  %
&  &   /     !$  %  $'   &                     free'       $$

char  *IceRelease( ice_conn);

IceRelease  !        $  %&   %   72           $
%   &  &   /     !$  %  $'   &                        free'
 $$

int  IceProtocolVersion( ice_conn);

IceProtocolVersion  !    "- 0    %   72   &     &
 &

int  IceProtocolRevision( ice_conn);

IceProtocolRevision  !    "  0    %   72   &     &
 &

int  IceConnectionNumber( ice_conn);

IceConnectionNumber  !    %  $ &    %   72&  &

char  *IceConnectionString( ice_conn);

IceConnectionString  !     ' D 78 %   &      && $   &
 &   /     !$  %  $'   &                      free'       $$

unsigned long  IceLastSentSequenceNumber( ice_conn);

IceLastSentSequenceNumber  !     F! &  !"   %      "
     72&  &

unsigned long  IceLastReceivedSequenceNumber( ice_conn);
```

IceLastReceivedSequenceNumber ! F!& !" % "
&0$ 72& &

```
Bool IceSwapping( ice_conn);
```

IceSwapping ! True % ' & ' $ "
72& &

```
IcePointer IceGetContext( ice_conn);
```

IceGetContext ! & @ & $' & & & $
IceOpenConnection

Chapter 12. ICE Messages

6 72" 0 $$E $ / 72 "& $ $
' " % ' " & 0 % " $.

```
CARD8 major_opcode;
CARD8 minor_opcode;
CARD8 data[2];
CARD32 length B32;
```

/ $ $ % " $ & ! $ $$ /
% $ &% $! %E

Sending ICE Messages

/ 72 " ! ! !%% ! $ % " # &
$ % 72" & & " $ %!
! ! !%% "

7% 73 &&! $ 72 & & ' '
$ 4 %! % "

/ A % 72 ! ! !%% ! IceGetOutBufSize

int **IceGetOutBufSize**(*ice_conn*);

60 $72& & -&

/ %! 72 ! ! !%% ! IceFlush

int **IceFlush**(*ice_conn*);

60 $72& & -&

: ! ! !%% " " & %! $ % !%% & &
"

/ % ' "& & ! $ 72" .

IceGetHeader(*ice_conn*, *major_opcode*, *minor_opcode*, *header_size*, **pmsg*);

60 $72& & -&

/ "- &$ % "

/ " &$ % "

' / A % " $ (+

() * / &! $ % " $

/ " $ 6% "& & $
& $ " $

IceGetHeader ! $! " $ 72 & & 7
"- $" & $ % " $ A " O
% $ 7% $$ 0 $ % ' " O
% $!$!$ $

IceGetHeaderExtra(*ice_conn*, *major_opcode*, *minor_opcode*, *header_size*, *extra*, **pmsg*, **pdata*);

60 $72& & -&

/ "- &$ % "

/ " &$ % "

' / A % " $ (+

! / A % @ $ $ $ (E ! +

() * / &! $ % " $

/ " $ 6% "& & $
& $ " $

! 72 ! ! !%% ""$
% " $ / 0 $!$
$ 7% ' ! " 72 ! ! !%%
$:9==

IceGetHeaderExtra ! $ " ' % @ $ ($ 0
" + "! % 0 $ / &" " "! % 72
! ! !%%

IceSimpleMessage(*ice_conn*, *major_opcode*, *minor_opcode*);

60 $72& & -&

/ "- &$ % "

/ " &$ % "

IceSimpleMessage ! $ " $ & A
72 $ " $ $$ $

IceErrorHeader(*ice_conn*, *offending_major_opcode*, *offending_minor_opcode*, *offending_sequence_num*, *severity*, *error_class*, *data_length*);

60 $72& & -&

/ "- &$ % & '& '
$ & $

/ " &$ % & '& '
$ & $

+ / F! & !" % " &! $

IceCanContinue IceFatalToProtocol IceFatalTo-
Connection

/ &

= %$ (E ! + ' %
$

IceErrorHeader ! " $

: ' & & & $ 72" ! $%% "- &$
% 0 & / %% $ J"- J &$ $ "& "-
&$ % & % & $ "

> & ' & &"" & 0 &
@E @4444 * ") ! $$% " $

7&?$ @E

7&?$* @E

7&?$= @E B

7&?$! @E

& 0 & @ @%%%

/' $ 72& & ! IceWriteData"& 7% $ %
72!! !%% & $ 3 ' 72!! !%%
%! $ $ $ $ &

/ "& !$ & -!& ' IceGetHeader $ IceErrorHeader

IceWriteData(*ice_conn*, *bytes*, **data*);

60 $72& & -&

/ !" % '

/ $ '

/' $ F! ! IceWriteData16

IceWriteData16(*ice_conn*, *bytes*, **data*);

60 $72& & -&

/ !" % '

/ $ '

/' $ B F! ! IceWriteData32

IceWriteData32(*ice_conn*, *bytes*, **data*);

60 $72& & -&

/ !" % '

/ $ '

/' $ B F! ! IceWriteData32

/ & $ 72!! !%% ! IceSendData $ & $
$ 0 'D& & 7% & 72!! !%% % %! $

IceSendData(*ice_conn*, *bytes*, **data*);

60 $72& & -&

/ !" % $

/ $ $

/% & B " ! IceWritePad 6"@"!" % $
& &% $

IceWritePad(*ice_conn*, *bytes*, **data*);

60 $72& & -&

/ !" % '

/ !" % $ '

Reading ICE Messages

/ 72 " ! !%% !$% $ " 7% 72
& % " &D $(" " $ $ +
% 0 $ "D A " &" " "
$! !%% 6 ! % % "& $ & $
& $" &! $ ' &&! & &
% $ $! !%%

/ A % 72 ! !%% ! IceGetInBufSize

int **IceGetInBufSize**(*ice_conn*);

60 $72& & -&

5 $ " & "! D & &D % 73 7% 73
&&! $ % " " !$ ' ! 6%
! % "& $ & $ '% $ " IceValidIO
"& & !$ & &D % 73 &&! $ & & 6% 73
&&! $ 72& & $ ' $ 4
%! % "

Bool **IceValidIO**(*ice_conn*);

60 $72& & -&

/% ' "& & !$ $72"

IceReadSimpleMessage(*ice_conn*, **pmsg*);

60 $72& & -&

() * / &! $ % " $

/ " $

IceReadSimpleMessage ! $ % " $ & A E
72 $! ! B $ & $ $$ $:
72 ' $ % E & "-
& $ % " IceReadSimpleMessage " !
E L $ &! $ $! !%%

4 " ' 0 $ '' % $ "
3 " $ 0 0 $ &" " ! IceRead-
CompleteMessage / & $ " $ 0 0 $ " $ (
" E 72 $ + $ 0
$ &!D (IceReadMessageHeader $ IceReadData

IceReadCompleteMessage(*ice_conn*, *header_size*, **pmsg*, **pdata*);

60 $72& & -&

' / A % " $ (+

() * / &! $ % " $

/ " $

/ 0 $ % "

7% 72 ! !%% !%% & & IceReadCompleteMessage' $
& " " 72 ! !%% 3 ' !%% ' & $
$ 0 $ 6% & $!" ! $ & &D $
:9== "D ! ' !%% & "" & !%%

6% & IceReadCompleteMessage $ & " IceDis-
poseCompleteMessage ! $ & $

IceDisposeCompleteMessage(*ice_conn*, **pdata*);

60 $72& & -&

/ 0 $! $ IceReadCom-
pleteMessage

7% !%% $ & $ $ 0 $ (&! $ $
% 72 ! !%% + % $ 72

IceReadMessageHeader(*ice_conn*, *header_size*, **pmsg*);

60 $72& & -&

' / A % " $ (+

() * / &! $ % " $

/ " $

IceReadMessageHeader $ -! " $ / % $! $
$' IceReadData % " % " & / " $ % $ "
! $! $' 0 $ "! $ &!D

/ $$ $ & ! ! $!%% ! IceReadData

IceReadData(*ice_conn*, *bytes*, **pdata*);

60 $72& & -&

/ !" % $

/ $ $! ! $!%%

/ $$ F! ! IceReadData16

IceReadData16(*ice_conn*, *swap*, *bytes*, **pdata*);

60 $72& & -&

7%True, 0 ! ' ' $

/ !" % $

/ $ $! ! $!%%

/ $$ B F! ! IceReadData32

IceReadData32(*ice_conn*, *swap*, *bytes*, **pdata*);

60 $72& & -&

7%True, 0 ! ' ' $

/ !" % $

/ $ $! ! $!%%

/ % & B " ! IceReadPad 6 " @ "!" % $
& & % $

IceReadPad(*ice_conn*, *bytes*);

60 $72& & -&

/ !" % $

Chapter 13. Error Handling

/ ' $ % ! $ 7 2 .

I 3 $ & % & $ (% @ " & & $ &!
"& & $+

I 3 $ 7 2 & % & &

/ $ & & $! ! $! % ! % !
' $ $ & & $ % ! D

/ 7 2 $! IceSetErrorHandler

IceSetErrorHandler(*ice_conn*, *bytes*);

/ 7 2 $;! !$:9== $ % !
$

IceSetErrorHandler ! 0 ! $

/ 7 2 $ 0 D $ ' ! @ & $ 7 2 & ("-
& $ + & ! $ / & % $ % ! $ @
" stderr $ % 0 % & exit ' A 0 ! 7%
@ !$ & !$ ' $

: & $" !$ $ $ & 0
(!$ 0 ' $ +

6 7 2 $ % IceErrorHandler

void **IceErrorHandler**(*ice_conn*, *swap*, *offending_minor_opcode*, *offending_sequence_num*, *error_class*, *severity*, *values*);

/ 7 2 & & -&

6 % $ & % 0 ! $ '

/ 7 2 " & $ % %% $ "

+ / F! & !" % %% $ "

/ & % %% $ "

IceCanContinue IceFatalToProtocol IceFatalTo-Connection

6 $$ 0 ! & % & " & $
$ &

/ % ' & $ % $ 7 2 0 .

IceBadMinor
IceBadState
IceBadLength

```
IceBadValue
IceBadMajor
IceNoAuth
IceNoVersion
IceSetupFailed
IceAuthRejected
IceAuthFailed
IceProtocolDuplicate
IceMajorOpcodeDuplicate
IceUnknownProtocol
```

4 %! % " ") ! $ $

/ $ % 7,3 ! IceSetIOErrorHandler

```
IceIOErrorHandler IceSetIOErrorHandler( handler);
```

/ 7,3 $;! !$:9== $ % !
$

IceSetIOErrorHandler ! 0 ! 73 $

6 7 2 7,3 $ % IceIOErrorHandler

```
void IceIOErrorHandler( ice_conn);
```

/ 7 2 & & - &

/ ' ' % $ 73 7 2 .

I 7 % 73 $ $ ' 0 & $
73 $! ! $ & IceCloseConnection / 7 2 &
& 0) $ 73) ! $ %! ! $ $' & &
$ / @ " IceProcessMessages & $ ' !
! % IceProcessMessagesIOError 6 " & !$ & IceCloseConnection

I 7 & $ 73 $ $ & IceCloseConnection $!
longjmp & &D & O " 0 / setjmp $
longjmp & " ' D % " $ & & "!
D 0 $ " " D / % & $ " $ $

? % & 7,3 $ 0 D $ & '
$ % $ % 7,3 ' 0 IceIOErrorProc $
0 D $ / $! & %! & (IceRegisterForProtocolSetup $ IceRegisterForProtocolReply $ & ! $! $
& ! & % & &

```
void IceIOErrorProc( ice_conn);
```

/ 7 2 & & - &

: 0 IceIOErrorProc & &D "! ! / F! $ & !
& & 0 & "! % $ % D & & $ &
73 $ "! 0 D $ % ' $

Chapter 14. Multi-Threading Support

/ $ & "! $ & ' ! 7 2 !
IceInitThreads

* ! 7& 7 / $ (+

/ IceInitThreads %! & "! % 7 2 %! & "! $ $
 " & 7 "! & " % 7 2 & " $ IceInitThreads
 ! A ! % $ % ' A $ &D
!&& %! 7 % & IceInitThreads " & ! $
 &D ' A $ &

& $ % 7 2 ' 0 &D & & & % & $
 && 7 2 & & (% @ " ' " + / &
' & " " $ " & 0 $ $.

void **IceLockConn**(*ice_conn*);

void **IceUnlockConn**(*ice_conn*);

/ 7 2 & & - &

/ D 7 2 & & &D $ & 0 7 2 & & !
IceAppLockConn $ IceAppUnlockConn

void **IceAppLockConn**(*ice_conn*);

/ 7 2 & & - &

/ IceAppLockConn %! & & " &D ! $! &
 & ! IceAppUnlockConn & $ 3 $ " ! 7 2
& & & ' &D 7% " 0 ! & $ IceInit-
Threads IceAppLockConn %% &

void **IceAppUnlockConn**(*ice_conn*);

/ 7 2 & & - &

/ IceAppUnlockConn %! & ' $ & " 7 2 &
 & & ' &D $ 0 ! & IceAppLockConn % "
 $ 7% " 0 ! & $ IceInitThreads IceAppUnlock-
Conn %% &

Chapter 15. Miscellaneous Functions

/ & & & & (% @" ' " ' 0
$ + ! IceAllocScratch2& 72& & & & & & $
' / & & & %% " $ ' $$ / &
% & & & ! $ 0$ % 72 %!&
& $

```
char *IceAllocScratch( ice_conn,  size);
```

/ 72& & -&

' / !" % F! $

: "" ! $ IceAllocScratch !$ % $
& / 72 ' % "" ' 72& & & $

Chapter 16. Acknowledgements

/ D ? *& % % ! %! ! $ % 7 2
/ D P $? ' = 8 0 0 4 *
> $ P %% < < * ! D 1 " *' &D
P " > $ $ D 5 @

Appendix A. Authentication Utility Functions

6 $ &! $ $ &!" " ' & ! & $ $
7 2 (% ConnectionSetup" ProtocolSetup" +
" " $ $ Q

/ $ @ $ & " ! %! & " ! 7 2 ! %
/ ! % & ! $! & $ ' &

/ & 7 2 ! % .

I > % "

I = &D

I 9 &D

I $

I 5

I * & %

/ % ' 0 $ @ & $ " D
) & !) ' ! $ @ $$ " 0 $ $ %

7 $! ! %! & G ,7 2,7 2! H $ % "!
& !$ $

6 7 2 ! % $ % $ % ' $!& ! .

```
typedef struct {
     char *protocol_name;
     unsigned short protocol_data_length;
     char *protocol_data;
     char *network_id;
     char *auth_name;
     unsigned short auth_data_length;
     char *auth_data;
} IceAuthFileEntry;
```

/ & J " " ")7 2) % & & ! ! &
! & " !&) * #) 4 & & & % & $ &
& % $ & J$ " " / & ! $ & % $
$ " 0 $ % " %

/ ' DJ $ " " ' D 78 % & && ! &
(% @ " ' D 78 % " + 6 ' D 78 % '
% ".

/ !"O 7 2 " " !" & % 7 2 ! %

& ,
G "H.G !" H

$ &
,G "H..G - "H

S
& ,G "H.G H

/ ! J " " " " % ! & " $ / ! J$
" " & ! ! & $ $! J$ J " "
!" % $

/ $ % ! ! A % " ! IceAuthFileName

& N7& 6! 4 :"(+

7% 7 269/13 7/; 0 " 0 % 0 ! ! $ 3 '
$ % ! ! A % " R13 2, 7 2 ! / " &
& $ $! $ % $

/ & ! ! $! A % % "! &D $ ' &
IceLockAuthFile/ %! & D $0 % % & link "
& ' % % " % ' D $ @

int **IceLockAuthFile**(**file_name*, *retries*, *timeout*, *dead*);

/ ! A % &D

/ !" %

/ !" % & $ % &

7% &D $ @ & % $ $ $ & $ $
D 6 0 ! % A ! $! & $ D $ &D

3 % 0 ! ! $.

I IceAuthLockSuccess &D !&& $ $

I IceAuthLockError " &&! $ $ errno " 0 ! %!

I IceAuthLockTimeout & % $!" % % $

/ ! &D ! A % ! IceUnlockAuthFile

int **IceUnlockAuthFile**(**file_name*);

/ ! A % ! &D

/ $ @ ! A % ! IceReadAuthFileEntry

IceAuthFileEntry ***IceReadAuthFileEntry**(**auth_file*);

/ ! A %

: % & % % $ %
& %! & 7% & ! $ "
$:9== ! $

2 !$ % ' & IceFreeAuthFileEntry

/ ' ! A % ! IceWriteAuthFileEntry

```
Status IceWriteAuthFileEntry( *auth_file,  *entry);
```

/ ! A %

/ '

: % & % % ' %
& %! & / %! & ! A ! % '
!&& %!

/ & $ %! ! A % % " & 0
& J ", ' DJ $,! J " ! ! IceGetAuthFileEntry

```
IceAuthFileEntry *IceGetAuthFileEntry(protocol_name, network_id,
auth_name);
```

/ " % & &

/ ' D 78 &

/ ! & " $ &

7%IceGetAuthFileEntry % % $!& :9== ! $

/ % ! $ IceReadAuthFileEntry IceGetAuthFileEntry ! IceFreeAuthFileEntry

```
void IceFreeAuthFileEntry( *entry);
```

/ %

Appendix B. MIT-MAGIC-COOKIE-1 Authentication

/ !"O 7 2 " " ! " 7/ 6>7
33<72 ! & & " ! ! % ! $ & $ 6
$ @ 6

7 "$ & !& " " & & D
& IceGenerateMagicCookie $! O & 7 2 !
% & & & & & 7 $ ' " & & &
" " @ &! "& " !$! $ " & & D
! O 7 2 ! % " "&

7 $$ " & & D 7 2 ! % &
$ & IceSetPaAuthData %! & $ " & & D
"" 5 & " " % 7/ 6>7 33<72 ! & &
$! && - & & & ' & " " & & D $
F! " & & D ""

```
char *IceGenerateMagicCookie( length);
```

/ $ $ % " & & D

/ " & & D ! $' ! " $ 7% "" & & $
% " & & D %! & ' ! :9== 3 ' " & & D
!$ % $' & free

/ ! & $ "" ! IceSetPaAuthData !
%! & ! $ % 7/ 6>7 33<72 ! & ! " ! $
% $$! & " $ %! !

```
void IceSetPaAuthData( num_entries,  *entries);
```

/ !" % ! & $

/ % ! & $

2 & & $ ' & " (% @ ")7 2) % 7 2
& & ! ! &) * #) % " " ! & +
' D 78 %) &&) & ! & " (% @ "
7/ 6>7 33<72 + $! & $ / 7 2 ' "
' 0 ! $ (& J " ' DJ $
! J " + !

```
typedef struct {
 char *protocol_name;
 char *network_id;
 char *auth_name;
 unsigned short auth_data_length;
 char *auth_data;
} IceAuthDataEntry;
```