

# Numerical Method of Identification of an Unknown Source Term in a Heat Equation

AFET GOLAYOĞLU FATULLAYEV\*

University of Kocaeli, Department of Mathematics, 41100 Anitpark, Izmit, Kocaeli, Turkey

(Received 5 January 2000)

A numerical procedure for an inverse problem of identification of an unknown source in a heat equation is presented. Approach of proposed method is to approximate unknown function by polygons linear pieces which are determined consecutively from the solution of minimization problem based on the overspecified data. Numerical examples are presented.

**Key words:** Parabolic equation; Inverse problem; Unknown source; Finite difference method

**Classification:** 35K15, 35Q99, 39A10

## 1 INTRODUCTION

In this paper we solve the problem of structural identification of an unknown source term in a heat equation subject to the specification of the solution at the boundary. This problem is described by the following inverse problem:

Find  $u = u(x, t)$  and  $F = F(u)$  which satisfy

$$u_t(x, t) = u_{xx}(x, t) + F(u(x, t)), \quad (x, t) \in Q_T = (0, 1) \times (0, T), \quad (1)$$

$$u(x, 0) = 0, \quad x \in (0, 1), \quad (2)$$

$$u_x(0, t) = g(t), \quad t \in (0, T), \quad (3)$$

$$u_x(1, t) = 0, \quad t \in (0, T), \quad (4)$$

---

\* Corresponding author. E-mail: AFET@edu.tr

subject to the overspecification

$$u(0, t) = f(t), \quad t \in (0, T) \quad (5)$$

where  $f(t)$  and  $g(t)$  are known functions.

In the context of heat conduction and diffusion when  $u$  represents temperature and concentration, the unknown function  $F(u)$  is interpreted as a heat and material source, respectively, while in a chemical or biochemical application  $F$  may be interpreted as a reaction term. Although the results in this paper apply to each of these interpretations, the unknown function  $F(u)$  will be referred to here as a source term.

The problem above in such formulation have been studied by authors [1] recently.

One approach to solve this problem referred to in the literature as the method of output least squares is to assume that the unknown function is a specific functional form depending on some parameters and then seek to determine optimal parameter values so as to minimize an error functional based on the overspecified data. However, this approach has some drawbacks. For example, it is usually not evident that the solution to the optimization problem solves the original inverse problem and the error functional may be based on data which do not uniquely determine the unknown function. Another methods to solve this problem are residual update methods such as Newton, Homotopy and FPP (Fixed Point Projection) methods [4]. The main difficulty with these methods is the form of the non-linearity. The approach of method presented in this paper is not of these types.

The strategy used here is to approximate unknown function by polygons linear pieces which are determined consecutively from the solution of minimization problem associated with finding minimum of function based on the additional condition. This paper is organized as follows. In section 2 we give the formulation of the direct and inverse problems and the properties of solution of the direct problem. In section 3 we describe a numerical procedure for the solution of the formulated inverse problem. Numerical examples are presented in section 4.

## 2 DIRECT AND INVERSE PROBLEMS

Let  $F$  is continuous and piecewise differentiable on  $R$  and  $g \in C(0, \infty)$  with  $g(0) = 0$  functions. Then initial boundary value problem (1)–(4) has a unique classical solution in  $Q'_T$  for sufficiently small  $T'$  (local existence of a solution) [3]. It is known that if the local solution is known to satisfy an a priori estimate then the local solution may be extended to a global solution. In particular, if it is known a priori that the solution of (1)–(4) satisfies

$$|u(x, t)| \leq C_1 \quad \text{for } 0 \leq x \leq 1 \quad \text{and} \quad 0 \leq t \leq T \quad (6)$$

for some  $T > 0$ , then it can be concluded that  $T' = T$ . One refers to (1)–(4) as a direct problem.

Let  $u = u(x, t; F, g)$  denote the solution of (1)–(4) for boundary input  $g = g(t)$  and source term  $F = F(u)$ . Assume that this solution is known to satisfy (6) for a fixed  $T > 0$  so that  $u(x, t)$  is then a solution in  $Q_T$ . Then  $u(x, t)$  will be said to be a solution of the direct problem. The function  $f(t) = u(0, t; F, g)$  will be viewed as an output corresponding to the input  $g(t)$  in the presence of the source term  $F$ . In [1] the following properties were deduced for the direct problem solution:

Suppose that  $g(t) < 0$  for  $0 < t < T$ . Then

- a) for each  $t$ ,  $0 < t < T$ ,  $f(t) = u(0, t) > u(x, t) > u(1, t)$  for  $0 < x < 1$ . If, in addition,  $F(0) \geq 0$  with  $F(u) \geq 0$  for  $0 \leq u \leq U_1$  for some  $U_1 > 0$ , then exists  $T_1 > 0$  such that  $f'(t) > 0$  for  $0 < t < T_1$  and
- b)  $f(t) = u(0, t) > u(x, t) > u(1, t) \geq 0$  for  $0 < x < 1, 0 < t < T_1$ .

We shall use these properties to construct numerical procedure for the solution of considered problem.

Now the inverse problem can be defined as follows: suppose  $g \in C[0, T]$ ,  $g(0) = 0$ ,  $g(t) < 0$  and  $f \in C'[0, T]$ ,  $f(0) = 0$ ,  $f'(t) > 0$  for  $0 < t < T$ . Then the problem of determining  $F(u)$  on an interval  $[0, f(T)]$  from the data  $f(t)$  and  $g(t)$  whose values are known on

the interval  $[0, T]$  will be said the inverse problem. The uniqueness of formulated and similar inverse problem has been established in [1,5].

### 3 PROCEDURE OF NUMERICAL SOLUTION

Let  $\tau = \Delta t > 0$  and  $h = \Delta x > 0$  be step length on time and space coordinate,  $\{0 = t_0 < t_1 < \dots < t_M = T\}$  and  $\{0 = x_0 < x_1 < \dots < x_N = 1\}$  denote partitions of the  $[0, T]$  and  $[0, 1]$  respectively. It follows from the properties of direct problem solution that  $\{u_0 \leq u_1 \leq \dots \leq u_M\}$ , where  $u_i = f(t_i)$ , defines a corresponding partition of the interval  $[u_0, f(T)]$ , where  $u_0 = \inf_{(x,t) \in Q_T} u(x, t)$  and  $f(T) = \sup_{(x,t) \in Q_T} u(x, t)$ . We replace the region  $Q_T$  by a set of grid points  $(x_i, t_n)$  denoted by  $(i, n)$ .

We may write the problem (1)–(5) at the grid points  $(i, n)$  as

$$\frac{\partial u_{i,n}}{\partial t} = \frac{\partial^2 u_{i,n}}{\partial x^2} + F(u_{i,n}), \quad 1 \leq i \leq N-1, \quad 1 \leq n \leq M, \quad (7)$$

$$u_{i,0} = 0, \quad 0 \leq i \leq N \quad (8)$$

$$\frac{\partial u_{0,n}}{\partial x} = g(t_n), \quad 1 \leq n \leq M \quad (9)$$

$$\frac{\partial u_{N,n}}{\partial x} = 0, \quad 1 \leq n \leq M, \quad (10)$$

and

$$u_{0,n} = f(t_n), \quad 1 \leq n \leq M \quad (11)$$

The implicit finite difference approximation of this system may be written in the form

$$\frac{U_{i,n} - U_{i,n-1}}{\tau} = \frac{U_{i+1,n} - 2U_{i,n} + U_{i-1,n}}{h^2} + F(U_{i,n}),$$

$$1 \leq i \leq N-1, \quad 1 \leq n \leq M, \quad (12)$$

$$U_{i,0} = u_0, \quad 0 \leq i \leq N, \quad (13)$$

$$\frac{U_{1,n} - U_{0,n}}{h} = g(t_n), \quad 1 \leq n \leq M, \quad (14)$$

$$\frac{U_{N,n} - U_{N-1,n}}{h} = 0, \quad 1 \leq n \leq M, \quad (15)$$

$$U_{N,n} = f(t_n), \quad 1 \leq n \leq M, \quad (16)$$

where  $U_{i,n}$  is the approximate value of  $u_{i,n}$ . The difference scheme (12)–(16) has a second order approximation on  $x$  on the interior nodal points and first order approximation in  $t$ .

Define  $P_n(u)$  a polygonal (*i.e.*, continuous and piecewise linear) approximation of  $F(u)$   $[u_0, u_n]$  as follows. For each  $m = 1, 2, \dots, n$ , let  $P_n(u)$  given for  $u_{m-1} < u \leq u_m$  by

$$P_n(u) = F_{m-1} \frac{u_m - u}{u_m - u_{m-1}} + F_m \frac{u - u_{m-1}}{u_m - u_{m-1}} \quad (17)$$

where  $F_m = F(u_m)$ .  $P_0(u) = F_0 = \text{const}$ . Assume that  $F(u(x, 0)) = F_0$  is known. This value can be found from the solution of (7)–(11) by using finite difference approximation (12)–(16) with  $n = 1$  if we assume that  $F(u)$  is constant on the initial time segment  $(0, t_1)$ , *i.e.*,  $F(u) = F_0 = \text{const}$ . on  $[u_0, u_1]$ . We shall determine graph of unknown function  $F(u)$  on the consecutive segments  $[u_1, u_2], [u_2, u_3], \dots, [u_{M-1}, u_M]$  in the following manner.

First it will be shown how  $F_2 = F(u_2)$  is determined and then the procedure will be generalized to the case of subsequent  $l$ 's.

Let  $\beta \leq F'(u) \leq \gamma$  for any  $u$  and let  $u(x, t; \alpha)$ , where  $\alpha \in (\tan^{-1} \beta, \tan^{-1} \gamma)$ , denote the solution of (1)–(4) for

$$F(u) = \begin{cases} F(u; \alpha) = F_1 + tg\alpha(u - u_1), & \text{if } u \geq u_1, \\ F_0, & \text{if } u \in [u_0, u_1], \end{cases} \quad (18)$$

on the time segment  $[0, t_2]$ . Let  $\alpha_2 = \arg \min_{\alpha} I(\alpha)$ , where  $I(\alpha) = |u(0, t_2; \alpha) - f(t_2)|$ . Then we can define  $F_2 = F_1 + tg\alpha_2(u_2 - u_1)$  and on  $[u_1, u_2]$  unknown  $F(u)$  will be approximated by  $P_2(u)$ .

To find  $F_l$  one the first  $l$  constants  $F_0, F_1, \dots, F_{l-1}$  are known, let  $u(x, t; \alpha)$  denote the solution of (1)–(4) for

$$F(u) = \begin{cases} F(u; \alpha) = F_{l-1} + tg\alpha(u - u_{l-1}), & \text{if } u \geq u_{l-1}, \\ P_{l-1}(u), & \text{if } u \in [u_0, u_{l-1}], \end{cases} \quad (19)$$




FIGURE 1

on the interval  $[0, t_l]$ , and  $\alpha_l = \arg \min_{\alpha} I(\alpha)$ , where

$$I(\alpha) = |u(0, t_l; \alpha) - f(t_l)| \quad (20)$$

Then  $F_l = F_{l-1} + tg\alpha_1(u_l - u_{l-1})$  and  $P_l(u)$  approximate the unknown  $F(u)$  on  $[u_0, u_l]$ .

Executing this procedure for  $l = 1$  to  $l = M$  generates a polygonal approximation  $P_M(u)$  for  $F(u)$  on the partition  $[u_0, u_1, \dots, u_M]$ .

Numerical experiments to test the effectiveness of this algorithm which will be discussed in the following section.

#### 4 NUMERICAL EXAMPLES

In this section we report some results of our numerical calculations using the numerical algorithm proposed in the previous section.

The data function  $g(t)$ , the source  $F(u)$ ,  $u_0$  and  $T$  were given by

$$g(t) = -3t, \quad F(u) = 5 - 4(u + 1), \quad T = 1, \quad u_0 = 0.$$

By solving the direct problem with these data by using implicit finite-difference approximation (12)–(16), the solution values of  $f(t)$  were recorded. Then the inverse problem was solved with this overspecification to determine the unknown source  $F(u)$ . For minimization of (20) here the method of golden section search is used. Results of determination of  $F(u)$  by the presented numerical procedure, are illustrated in Figures 1–3, corresponds to results with grids  $N \times M = 50 \times 5, 50 \times 10, 50 \times 30$ , respectively, where the symbols correspond to approximate results and the ones without symbols correspond to exact  $F(u)$ . It is seen that




FIGURE 2

approximation of  $F(u)$  is improved by increasing the number of nodes and that for sufficiently large number of nodes the agreement between numerical and exact solution becomes uniformly good.




FIGURE 3




FIGURE 4

In the next example input data were used from the previous example. Artificial errors were introduced into the overspecified data by defining function

$$f^*(t_n) = f(t_n)(1 + d(t_n, q)), \quad n = 1, 2, \dots, M.$$

Here  $d(t_n, q)$  represents the level of relative error in the corresponding piece of data. Calculation results with grid  $N \times M = 50 \times 20$  are presented in Figure 4 according to cases with  $d(t, 0.02)$ , and  $d(t, 0.04)$ . As seen from the figure that in this case results are worsening and there are approximations in some integral norm. It is also seen that  $P_M(u)$  appears to be a relative good approximation for small values of artificial errors.

## 5 CONCLUSION AND FUTURE DIRECTIONS

Considered problem in this paper has such properties that presented method is readily available. Numerical experiments show effectiveness of the presented method in determining close estimates of unknown source term in a heat equation. In considered problem additional condition is given on boundary, but the proposed procedure may be used for the solution of problems where additional conditions are given on the interior points. The presented method can be applied for the solution of class of inverse problem associated with parabolic equation

$$u_t = F(x, t, u, u_{xx}, p(u))$$

with appropriate initial, boundary and additional conditions, where  $u(x, t)$  and  $p(u)$  are to be determined. This method can be extended also for the solution of multidimensional and multiple coefficient inverse problems.

## References

- [1] Cannon, J. R. and DuChateau, P. (1998). "Structural Identification of an Unknown Source Term in a Heat Equation", *Inverse Problems*, **14**, 535–551.
- [2] Cannon, J. R. and DuChateau, P. (1980). "An Inverse Problem for an Unknown Source in a Heat Equation", *J. of Mathematical Analysis and Applications*, **75**, 465–485.
- [3] Ladyzhenskaya, O. A., Solonnikov, V. A. and Uralceva, N. N. (1967). *Linear and Quasilinear Equations of Parabolic Type*, Nauka, Moscow, [in Russian].
- [4] Pilant, M. and Rundell, W. (1989). "Undetermined coefficient problems for quasilinear parabolic equations", Proceedings of the conference on Inverse Problems in Partial Differential Equation, Arcata, California, July 29–August 4.
- [5] DuChateau, P. and Rundell, W. (1985). "Unicity in an Inverse Problem for an Unknown Reaction Term in a Reaction-diffusion Equation", *J. Diff. Eq.*, **59**, 155–164.



## Special Issue on Intelligent Computational Methods for Financial Engineering

### Call for Papers

As a multidisciplinary field, financial engineering is becoming increasingly important in today's economic and financial world, especially in areas such as portfolio management, asset valuation and prediction, fraud detection, and credit risk management. For example, in a credit risk context, the recently approved Basel II guidelines advise financial institutions to build comprehensible credit risk models in order to optimize their capital allocation policy. Computational methods are being intensively studied and applied to improve the quality of the financial decisions that need to be made. Until now, computational methods and models are central to the analysis of economic and financial decisions.

However, more and more researchers have found that the financial environment is not ruled by mathematical distributions or statistical models. In such situations, some attempts have also been made to develop financial engineering models using intelligent computing approaches. For example, an artificial neural network (ANN) is a nonparametric estimation technique which does not make any distributional assumptions regarding the underlying asset. Instead, ANN approach develops a model using sets of unknown parameters and lets the optimization routine seek the best fitting parameters to obtain the desired results. The main aim of this special issue is not to merely illustrate the superior performance of a new intelligent computational method, but also to demonstrate how it can be used effectively in a financial engineering environment to improve and facilitate financial decision making. In this sense, the submissions should especially address how the results of estimated computational models (e.g., ANN, support vector machines, evolutionary algorithm, and fuzzy models) can be used to develop intelligent, easy-to-use, and/or comprehensible computational systems (e.g., decision support systems, agent-based system, and web-based systems)

This special issue will include (but not be limited to) the following topics:

- **Computational methods:** artificial intelligence, neural networks, evolutionary algorithms, fuzzy inference, hybrid learning, ensemble learning, cooperative learning, multiagent learning

- **Application fields:** asset valuation and prediction, asset allocation and portfolio selection, bankruptcy prediction, fraud detection, credit risk management
- **Implementation aspects:** decision support systems, expert systems, information systems, intelligent agents, web service, monitoring, deployment, implementation

Authors should follow the Journal of Applied Mathematics and Decision Sciences manuscript format described at the journal site <http://www.hindawi.com/journals/jamds/>. Prospective authors should submit an electronic copy of their complete manuscript through the journal Manuscript Tracking System at <http://mts.hindawi.com/>, according to the following timetable:

Manuscript Due	December 1, 2008
First Round of Reviews	March 1, 2009
Publication Date	June 1, 2009

### Guest Editors

**Lean Yu**, Academy of Mathematics and Systems Science, Chinese Academy of Sciences, Beijing 100190, China; Department of Management Sciences, City University of Hong Kong, Tat Chee Avenue, Kowloon, Hong Kong; [yulean@amss.ac.cn](mailto:yulean@amss.ac.cn)

**Shouyang Wang**, Academy of Mathematics and Systems Science, Chinese Academy of Sciences, Beijing 100190, China; [sywang@amss.ac.cn](mailto:sywang@amss.ac.cn)

**K. K. Lai**, Department of Management Sciences, City University of Hong Kong, Tat Chee Avenue, Kowloon, Hong Kong; [mskkklai@cityu.edu.hk](mailto:mskkklai@cityu.edu.hk)