Package 'fMRItools'

November 14, 2026

Type Package

Title Routines for Common fMRI Processing Tasks

Version 0.9.2

Maintainer Amanda Mejia <mandy.mejia@gmail.com>

Description Supports fMRI (functional magnetic resonance imaging) analysis tasks including reading in 'CIFTI', 'GIFTI' and 'NIFTI' data, temporal filtering, nuisance regression, and aCompCor (anatomical Components Correction) (Muschelli et al. (2014) <doi:10.1016/j.neuroimage.2014.03.028>).

Depends R (>= 3.5.0)

License GPL-3

Encoding UTF-8

Imports stats, matrixStats

Suggests ciftiTools, corpcor, expm, gifti, knitr, rmarkdown, pesel, RNifti, oro.nifti, gsignal, testthat (>= 3.0.0), covr, quantreg, graphics, grDevices, RColorBrewer, viridis, ggcorrplot, ggplot2, scales

URL https://github.com/mandymejia/fMRItools

BugReports https://github.com/mandymejia/fMRItools/issues

Config/roxygen2/version 8.1.1

NeedsCompilation no

Author Amanda Mejia [aut, cre] (ORCID: <https://orcid.org/0000-0002-4312-8974>), Damon Pham [aut] (ORCID: <https://orcid.org/0000-0001-7563-4727>), Mark Fiecas [ctb]

Repository CRAN

Date/Publication 2026-11-14 04:50:02 UTC

Contents

all_binary . . . 3
all_integers . . . 4
as.matrix_ifti . . . 4
bandstop_filter . . . 5
carpetplot . . . 6
carpetplot_stack . . . 7
colCenter . . . 8
color_palette . . . 8
CompCor . . . 9
CompCor_HCP_apply . . . 11
CompCor_HCP_calc . . . 12
coordlist_to_vol . . . 15
crop_vol . . . 15
dct_bases . . . 16
dct_convert . . . 16
despike_3D . . . 17
dice_coef . . . 18
dilate_mask_vol . . . 19
dual_reg . . . 19
dual_reg_parc . . . 21
erode_mask_vol . . . 23
expand_RPs . . . 24
flags2spikes . . . 24
fmat_mult . . . 25
fMRItools . . . 26
fsl_bptf . . . 26
gaussian_hpf_mat . . . 27
gaussian_lpf_mat . . . 28
hat_matrix . . . 28
infer_format_ifti . . . 29
infer_format_ifti_vec . . . 29
is_1 . . . 30
is_constant . . . 30
is_integer . . . 31
is_posNum . . . 31
mask_BOLD . . . 32
mat2UT . . . 32
match_exactly . . . 33
match_input . . . 33
match_nets . . . 34
mean_squares . . . 35
Mode . . . 36
norm_BOLD . . . 36
nuisance_regression . . . 38
pad_vol . . . 39
PCA . . . 39

pct_sig . . . 40
plot_FC . . . 41
plot_FC_gg . . . 42
read_nifti . . . 43
scale_design_mat . . . 44
scale_med . . . 44
scale_timeseries . . . 45
sign_flip . . . 46
skew_pos . . . 46
sum_neighbors_vol . . . 47
temporal_filter . . . 47
unmask_mat . . . 48
unvec_mat . . . 49
unvec_vol . . . 50
UT2mat . . . 50
validate_design_mat . . . 51
var_decomp . . . 52
vox_locations . . . 52

Index **53**

`all_binary` *All binary?*

Description

Check if a data vector or matrix is all zeroes and ones. Option to also accept logical values.

Usage

```
all_binary(x, logical_ok = TRUE)
```

Arguments

`x`	The data vector or matrix
`logical_ok`	Is a logical vector or matrix also acceptable? Default: `TRUE`.

Value

Logical. Is `x` binary data?

all_integers *All integers?*

Description

Check if a data vector or matrix is all integers.

Usage

```
all_integers(x)
```

Arguments

x	The data vector or matrix

Value

Logical. Is x all integers?

as.matrix_ifti *Convert CIFTI, NIFTI, or GIFTI input to $T \times V$ matrix*

Description

Convert CIFTI, NIFTI, or GIFTI input to a $T \times V$ matrix by reading it in with the corresponding package and then separating the data from the metadata. Also works with the intermediate R objects created from reading these files: "xifti" objects from ciftiTools, "gifti" objects from gifti, "nifti" or "niftiExtension" objects from oro.nifti, and "niftiImage" objects from RNifti.

For CIFTI files, only intents supported by ciftiTools are supported: dscalar, dtseries, and dlabel. For NIFTI file or NIFTI-intermediate R objects, the data will be vectorized/masked.

Usage

```
as.matrix_ifti(
  x,
  meta = FALSE,
  sortSub = FALSE,
  TbyV = TRUE,
  verbose = FALSE,
  ...
)
```

Arguments

x	The object to coerce to a matrix
meta	Return metadata too? Default: FALSE.
sortSub	For CIFTI format input only. Sort subcortex by labels? Default: FALSE (sort by array index).
TbyV	Return the data matrix in $T \times V$ form? Default: TRUE. If FALSE, return in $V \times T$ form instead. Using this argument may be faster than transposing after the function call.
verbose	Print updates? Default: FALSE.
...	If x is a file path, additional arguments to the function used to read in x can be specified here. For example, if x is a path to a CIFTI file, ... might specify which idx and brainstructures to read in.

Value

If !meta, x as a matrix. If meta, a list of length two: the first entry is x as a matrix, and the second entry is the metadata of x.

---

bandstop_filter *Bandstop filter*

Description

Filter out frequencies within a given range using a Chebyshev Type II stopband. Essentially a convenience wrapper for the cheby2 function.

Usage

```
bandstop_filter(X, TR, f1, f2, Rs = 20)
```

Arguments

X	A numeric matrix, with each column being a timeseries to apply the stopband filter. For fMRI data, X should be T timepoints by V brain locations.
TR	The time step between adjacent rows of x, in seconds
f1, f2	The frequency limits for the filter, in Hz. f1 < f2
Rs	The amount of attenuation of the stopband ripple, in dB

Value

The filtered data

Examples

```
if (requireNamespace("gsignal", quietly=TRUE)) {
 n_voxels = 1e4
 n_timepoints = 100
 X = cbind(arima.sim(n=100, list(ar=.6)), arima.sim(n=100, list(ar=.6)))
 Y = bandstop_filter(X, .72, .31, .43)
}
```

`carpetplot` *Carpetplot*

Description

Plot a matrix with `graphics::image`. For fMRI data, this is the "carpetplot" or grayplot coined by (Power, 2017). The `graphics` and `grDevices` packages are required.

Usage

```
carpetplot(
  x,
  qcut = 0.1,
  fname = NULL,
  center = TRUE,
  scale = FALSE,
  colors = "gray255",
  sortSub = TRUE,
  ...
)
```

Arguments

`x`	The $T \times V$ numeric data matrix, or a `"xifti"` object. In the plot, the T index will increase from left to right, and the V will increase from top to bottom.
`qcut`	Sets blackpoint at the `qcut` quantile, and the whitepoint at the `1-qcut` quantile. Default: `.1`. This is equivalent to setting the color range between the 10% and 90% quantiles. The quantiles are computed across the entire data matrix after any centering or scaling. Must be between 0 and .49. If `0` or `NULL` (default), do not clamp the data values.
`fname`	A `.pdf` (highly recommended) or `.png` file path to write the carpetplot to. If `NULL` (default), return the plot directly instead of writing a file.
`center, scale`	Center and scale the data? If `x` is fMRI data which has not otherwise been centered or scaled, it is recommended to center but not scale it (default).
`colors`	`"gray255"` (default) will use a grayscale color ramp from black to white. Otherwise, this should be a character vector of color names to use. Colors will be assigned from the lowest to the highest data value, after any clamping of the data values by `qcut`.

sortSub	If x is a "xifti" object with subcortical data, should the voxels be sorted by structure alphabetically? Default: TRUE.
...	Additional arguments to pdf or png, such as width and height.

Value

The image or NULL, invisibly if a file was written.

References

- Power, J. D. A simple but useful way to assess fMRI scan qualities. NeuroImage 154, 150-158 (2017).

---

carpetplot_stack *Stacked carpetplot*

Description

Stacks carpetplots on top of one another by rbinding the matrices.

Usage

```
carpetplot_stack(
  x_list,
  center = TRUE,
  scale = FALSE,
  qcut = 0.1,
  match_scale = TRUE,
  nsep = 0,
  ...
)
```

Arguments

x_list	List of data matrices
center, scale	Center and scale the data? If x is fMRI data which has not otherwise been centered or scaled, it is recommended to center but not scale it (default).
qcut	Sets blackpoint at the qcut quantile, and the whitepoint at the 1-qcut quantile. Default: .1. This is equivalent to setting the color range between the 10% and 90% quantiles. The quantiles are computed across the entire data matrix after any centering or scaling. Must be between 0 and .49. If 0 or NULL (default), do not clamp the data values.
match_scale	Match the scales of the carpetplots? Default: TRUE.
nsep	Equivalent number of data locations for size of gap between carpetplots. Default: zero (no gap).
...	Additional arguments to carpetplot

Value

NULL, invisibly

---

colCenter *Center matrix columns*

Description

Efficiently center columns of a matrix. (Faster than base::scale.)

Usage

```
colCenter(X)
```

Arguments

X	The data matrix. Its columns will be centered.

Value

The centered data

---

color_palette *Color palette*

Description

Color palettes for fMRI data analysis tasks

Usage

```
color_palette(pal = "Beach")
```

Arguments

pal	"Beach" (default; blue to white to red), "Sand" (white to red), or "Water" (white to blue).

Value

A data.frame with two columns: "col" has the hex code of color, and "val" has the placement of colors between zero and one.

CompCor *Anatomical CompCor*

Description

The aCompCor algorithm for denoising fMRI data using noise ROIs data

Usage

```
CompCor(
  X,
  ROI_data = "infer",
  ROI_noise = NULL,
  noise_nPC = 5,
  noise_erosion = NULL,
  center = TRUE,
  scale = TRUE,
  prelim_nuisance = NULL,
  nuisance = NULL
)
```

Arguments

X	Wide numeric data matrix ($Tobservations$ by $Vvariables$, $T << V$). For example, if X represents an fMRI run, T should be the number of timepoints and V should be the number of brainordinate vertices/voxels. Or, a 4D array or NIFTI or file path to a NIFTI (I by J by K by T observations), in which case ROI_data must be provided. (The vectorized data will be $Ttimepoints$ by $V_{in-mask}voxels$) Or, a ciftiTools "xifti" object or a file path to a CIFTI (The vectorized data will be $Ttimepoints$ by $V_{left+right+sub}grayordinates$).
ROI_data	Indicates the data ROI. Allowed arguments depend on X: If X is a matrix, this must be a length V logical vector, where the data ROI is indicated by TRUE values. If "infer" (default), all columns of X will be included in the data ROI (rep(TRUE, V)). If X is an array or NIFTI, this must be either a vector of values to expect for out-of-mask voxels in X, or a (file path to a) 3D NIFTI. In the latter case, each of the volume dimensions should match the first three dimensions of X. Voxels in the data ROI should be indicated by TRUE and all other voxels by FALSE. If "infer" (default), will be set to c(0, NA, NaN) (include all voxels which are not constant 0, NA, or NaN). If X is a "xifti" this must be the brainstructures argument to ciftiTools::read_cifti. If "infer" (default), brainstructures will be set to "all" (use both left and right cortex vertices, and subcortical voxels). If NULL, the data ROI will be empty. This is useful for obtaining just the noise ROI, if the data and noise are located in separate files.

`ROI_noise` Indicates the noise ROIs for aCompCor. Should be a list where each entry corresponds to a distinct noise ROI. The names of the list should be the ROI names, e.g. `"white_matter"` and `"csf"`. The expected formats of the list entries depends on `X`:

For all types of `X`, `ROI_noise` entries can be a matrix of noise ROI data. The matrix should have T rows, with each column being a data location's timeseries.

If `X` is a matrix, entries can also indicate a noise ROI within `X`. These entries must be a length V logical vector with `TRUE` values indicating locations in `X` within that noise ROI. Since the ROIs must not overlap, the masks must be mutually exclusive with each other, and with `ROI_data`.

If `X` is an array or NIFTI, entries can also indicate a noise ROI within `X`. These entries must be a logical array or (file path to) a 3D NIFTI with the same spatial dimensions as `X`, and with `TRUE` values indicating voxels inside the noise ROI. Since the ROIs must not overlap, the masks must be mutually exclusive with each other, and with `ROI_data`.

(If `X` is a `"xifti"`, entries must be data matrices, since no grayordinate locations in `X` are appropriate noise ROIs).

`noise_nPC` The number of principal components to compute for each noise ROI. Alternatively, values between 0 and 1, in which case they will represent the minimum proportion of variance explained by the PCs used for each noise ROI. The smallest number of PCs will be used to achieve this proportion of variance explained.

Should be a list or numeric vector with the same length as `ROI_noise`. It will be matched to each ROI based on the name of each entry, or if the names are missing, the order of entries. If it is an unnamed vector, its elements will be recycled. Default: `5` (compute the top 5 PCs for each noise ROI).

`noise_erosion` The number of voxel layers to erode the noise ROIs by. Should be a list or numeric vector with the same length as `ROI_noise`. It will be matched to each ROI based on the name of each entry, or if the names are missing, the order of entries. If it is an unnamed vector, its elements will be recycled. Default: `NULL`, which will use a value of 0 (do not erode the noise ROIs). Note that noise erosion can only be performed if the noise ROIs are volumetric.

`center`, `scale` Center the columns of the noise ROI data by their medians, and scale by their MADs? Default: `TRUE` for both. Note that this argument affects the noise ROI data and not the data that is being cleaned with aCompCor. Centering and scaling of the data being cleaned can be done after this function call.

`prelim_nuisance`

Nuisance signals to regress from the noise ROIs before computing the PCs. Should be a T by P numeric matrix where P represents the number of preliminary nuisance signals. Default: `NULL` (do not do any preliminary nuisance regression).

`nuisance` Nuisance signals to regress from each data column in addition to the noise ROI PCs. Should be a T by N numeric matrix where N represents the number of nuisance signals. To not perform any nuisance regression set this argument to `NULL`, `0`, or `FALSE`. Default: `NULL`.

Details

This function performs two steps, each of which is available as a separate function. First, the principal components (PCs) of each noise region of interest (ROI) are calculated. For each ROI, voxels are centered and scaled (can be disabled with the arguments `center` and `scale`), and then the PCs are calculated via the singular value decomposition.

Next, aCompCor is performed to remove the shared variation between the noise ROI PCs and each location in the data. This is accomplished by a nuisance regression using a design matrix with the noise ROI PCs, any additional regressors specified by `nuisance`, and an intercept term, which is done by `CompCor_clean`. (To detrend the data and perform aCompCor in the same regression, `nuisance` can be set to DCT bases obtained with the function `dct_bases`.)

If `prelim_nuisance` includes an intercept, note that the PCs may retain a small component along the constant, because the centering of each noise ROI voxel is by the median (see `noise_PCs`).

Value

A list with entries `"data"`, `"noise"`, and potentially `"ROI_data"`.

The entry `"data"` will be a matrix where each row or column corresponds to a data location (if it was originally an array, the locations will be voxels in spatial order). Each location's time series will have each noise PC regressed from it. This entry will be `NULL` if there was no data.

The entry `"noise"` is a `"CompCor_noise"` object: a list with the noise PC scores (`"PCs"`), their corresponding variance (`"var"`), and their ROI mask (`"ROI_noise"`), for each noise ROI.

If the data ROI is not all `TRUE`, the entry `"ROI_data"` will have the ROI mask for the data.

References

- Behzadi, Y., Restom, K., Liau, J. & Liu, T. T. A component based noise correction method (CompCor) for BOLD and perfusion based fMRI. NeuroImage 37, 90-101 (2007).
- Muschelli, J. et al. Reduction of motion-related artifacts in resting state fMRI using aCompCor. NeuroImage 96, 22-35 (2014).

See Also

CompCor_clean, CompCor_HCP_calc

`CompCor_HCP_apply` *Clean HCP CIFTI data with aCompCor*

Description

Regresses noise PCs from HCP CIFTI data. The PCs can be calculated from the NIFTI fMRI data and NIFTI labels with `CompCor_HCP_calc`. This is a wrapper to `CompCor_clean` which handles the CIFTI data.

Usage

```
CompCor_HCP_apply(
  cii,
  noise,
  idx = NULL,
  brainstructures = c("left", "right"),
  DCT = 0,
  nuisance_too = NULL,
  verbose = FALSE
)
```

Arguments

cii	"xifti" (or file path to the CIFTI) from which the noise ROI components will be regressed. In the HCP, the corresponding file is e.g. "../Results/rfMRI_REST1_LR/rfMRI_REST1_LR
noise	The noise components, as returned by CompCor_HCP_calc for a single idx (i.e. a list with an entry named "PCs").
idx	A numeric vector indicating the timepoints of cii to use, or NULL (default) to use all timepoints. This should match the timepoints used to compute noise.
brainstructures	Choose among "left", "right", and "subcortical". Only used if cii is a file path. Default: c("left", "right") (cortical data only)
DCT	Add DCT bases to the nuisance regression? Use an integer to indicate the number of cosine bases. Use 0 (default) to forgo detrending. An intercept is always included in the regression, so the data does not need to be centered.
nuisance_too	A matrix of nuisance signals to add to the nuisance regression. Should have T rows. NULL to not add additional nuisance regressors (default).
verbose	Should occasional updates be printed? Default: FALSE.

Value

The cleaned surface-based data as a "xifti" object.

See Also

CompCor_HCP_calc, CompCor_clean

CompCor_HCP_calc *Anatomical CompCor for HCP NIFTI data: noise PCs*

Description

Computes the noise principal components (PCs) for aCompCor from HCP-format data. Obtains the noise ROIs from the NIFTI fMRI data and the NIFTI labels, and then the PCs of each ROI (see `noise_PCs`). This function only computes the noise PCs: it does not clean any data. To clean the surface-based CIFTI data with aCompCor using these noise PCs, see `CompCor_HCP_apply`. (To clean other data, see `CompCor_clean`.) For general data, see `CompCor`.

Usage

```
CompCor_HCP_calc(
  nii,
  nii_labels,
  ROI_noise = c("wm_cort", "csf"),
  noise_nPC = 5,
  noise_erosion = NULL,
  idx = NULL,
  center = TRUE,
  scale = TRUE,
  prelim_nuisance = NULL,
  verbose = FALSE
)
```

Arguments

`nii`	I by J by K by T NIFTI object or array (or file path to the NIFTI) which contains whole-brain data, including the noise ROIs. In the HCP, the corresponding file is e.g. "../Results/rfMRI_REST1_LR/rfMRI_REST1_LR.nii.gz"
`nii_labels`	I by J by K NIFTI object or array (or file path to the NIFTI) which contains the corresponding labels to each voxel in `nii`. Values should be according to this table: https://surfer.nmr.mgh.harvard.edu/fswiki/FsTutorial/AnatomicalROI/FreeSurferColorLUT In the HCP, the corresponding file is "ROIs/Atlas_wmparc.2.nii.gz".

`ROI_noise`	A list of numeric vectors. Each entry should represent labels in `nii_labels` belonging to a single noise ROI, named by that entry's name. Or, this can be a character vector of at least one of the following: `"wm_cort"` (cortical white matter), `"wm_cblm"` (cerebellar white matter), `"csf"` (cerebrospinal fluid). In the latter case, these labels will be used:
	`"wm_cort" c(3000:4035, 5001, 5002)`
	`"wm_cblm" c(7, 46)`
	`"csf" c(4, 5, 14, 15, 24, 31, 43, 44, 63, 250, 251, 252, 253, 254, 255))`
	These default ROIs are based on this forum post: https://www.mail-archive.com/hcp-users@humanconnectome.org/msg00931.html
	Default: `c("wm_cort", "csf")`

`noise_nPC`	The number of principal components to compute for each noise ROI. Alternatively, values between 0 and 1, in which case they will represent the minimum proportion of variance explained by the PCs used for each noise ROI. The smallest number of PCs will be used to achieve this proportion of variance explained.

Should be a list or numeric vector with the same length as `ROI_noise`. It will be matched to each ROI based on the name of each entry, or if the names are missing, the order of entries. If it is an unnamed vector, its elements will be recycled. Default: `5` (compute the top 5 PCs for each noise ROI).

`noise_erosion` The number of voxel layers to erode the noise ROIs by. Should be a list or numeric vector with the same length as `ROI_noise`. It will be matched to each ROI based on the name of each entry, or if the names are missing, the order of entries. If it is an unnamed vector, its elements will be recycled. Default: `NULL`, which will use a value of 0 (do not erode the noise ROIs).

`idx` A numeric vector indicating the timepoints to use, or `NULL` (default) to use all timepoints. (Indexing begins with 1, so the first timepoint has index 1 and the last has the same index as the length of the scan.)

`center, scale` Center the columns of the noise ROI data by median, and scale the columns of the noise ROI data by MAD? Default: `TRUE` for both.

`prelim_nuisance`

Nuisance signals to regress from the noise ROIs before computing the PCs (see `CompCor`). A T by P numeric matrix, where T is the number of timepoints in `idx`. Default: `NULL` (do not do any preliminary nuisance regression).

`verbose` Should occasional updates be printed? Default: `FALSE`.

Details

The noise ROI data is extracted from the full NIFTI array (rather than from a copy of the array subsetted to `idx`), which avoids duplicating the whole 4D array in memory.

Value

A `"CompCor_noise"` object: a list with entries `"PCs"` (the noise PC scores for each noise ROI), `"var"` (the variance of each PC), and `"ROI_noise"` (the noise ROI masks, after erosion). This is the same form as the `"noise"` entry of the result of `CompCor`.

References

- Behzadi, Y., Restom, K., Liau, J. & Liu, T. T. A component based noise correction method (CompCor) for BOLD and perfusion based fMRI. NeuroImage 37, 90-101 (2007).
- Muschelli, J. et al. Reduction of motion-related artifacts in resting state fMRI using aCompCor. NeuroImage 96, 22-35 (2014).

See Also

CompCor, CompCor_clean, CompCor_HCP_apply

coordlist_to_vol *Convert coordinate list to 3D array*

Description

Converts a sparse coordinate list to its non-sparse volumetric representation.

Usage

```
coordlist_to_vol(coords, fill = FALSE)
```

Arguments

coords	The sparse coordinate list. Should be a "data.frame" or matrix with voxels along the rows and three or four columns. The first three columns should be integers indicating the spatial coordinates of the voxel. If the fourth column is present, it will be the value used for that voxel. If it is absent, the value will be TRUE or 1 if fill is not one of those values, and FALSE or 0 if fill is. The data type will be the same as that of fill. The fourth column must be logical or numeric.
fill	Logical or numeric fill value for the volume. Default: FALSE.

Value

The volumetric data

crop_vol *Crop a 3D array*

Description

Remove empty (zero-valued) edge slices from a 3D array.

Usage

```
crop_vol(x)
```

Arguments

x	The numeric 3D array to crop.

Value

A list of length two: "data", the cropped array, and "padding", the number of slices removed from each edge of each dimension.

dct_bases *Generate cosine bases for the DCT*

Description

https://en.wikipedia.org/wiki/Discrete_cosine_transform "DCT II"

Usage

```
dct_bases(T_, n, idx = NULL)
```

Arguments

T_	Length of timeseries
n	Number of cosine bases (indices 1:n). Ignored if idx is provided.
idx	Optional integer vector of specific basis indices to compute (each in 1:T_). Avoids building the full $T \times T$ matrix.

Value

Matrix with cosine bases along columns

dct_convert *DCT and frequency conversion*

Description

Convert between number of DCT bases and Hz of highpass filter

Usage

```
dct_convert(T_, TR, n = NULL, f = NULL)

dct2Hz(T_, TR, n)

Hz2dct(T_, TR, f)
```

Arguments

T_	Length of timeseries (number of timepoints)
TR	TR of the fMRI scan, in seconds (the time between timepoints)
n	Number of cosine bases
f	Hz of highpass filter

Details

Provide either `n` or `f` to calculate the other.

If only the total length of the scan is known, you can set that to `TR` and use `T_=1`.

$f = n/(2 * T_* TR)$

Value

If `n` was provided, the highpass filter cutoff (Hz) is returned. Otherwise, if `f` was provided, the number of cosine bases is returned. The result should be rounded before passing to `dct_bases`

---

despike_3D *3dDespike from AFNI*

Description

Identify and interpolate outliers. See the AFNI documentation for 3dDespike for additional information.

Usage

```
despike_3D(
  Yt,
  c1 = 2.5,
  c2 = 4,
  basis = NULL,
  method = c("auto", "OLD", "NEW"),
  localedit = FALSE,
  corder = NULL
)
```

Arguments

`Yt`	The data vector (at least 15 time points).
`c1`	spike threshold (AFNI's `-cut`). Default: `2.5`. Must be at least `1`.
`c2`	upper range of the acceptable deviation from the fit. Default: `4`. Must be at least `c1 + 0.5`.
`basis`	Optional precomputed `despike_3D.basis`, to avoid recomputing it for many data vectors of equal length.
`method`	How to fit the curve: `"OLD"` for the L1 fit (requires the `quantreg` package), `"NEW"` for the faster least-squares fit after a simple outlier removal (the results are similar, not identical), or `"auto"` (default) to use `"NEW"` if there are more than 500 time points and `"OLD"` otherwise, as AFNI does.
`localedit`	Use AFNI's `-localedit` method to replace spikes? Default: `FALSE`.
`corder`	The number of sine/cosine pairs in the curve (AFNI's `-corder`). Default: `NULL` to use `round(length(Yt)/30)` (at most 50 for the `"OLD"` method). Ignored if `basis` is provided.

Details

Follows `3dDespike`: a smooth curve is fit to the time series (`despike_3D.basis`), the residuals' scale is estimated, and values far from the curve are pulled in (`despike_3D.interpolate`). Not implemented: AFNI's `-NEW25` and `-ignore` options, and voxel masking.

Value

The despiked data vector.

References

Cox RW (1996). AFNI: software for analysis and visualization of functional magnetic resonance neuroimages. *Computers and Biomedical Research*, 29(3), 162-173. doi:10.1006/cbmr.1996.0014

Cox RW, Hyde JS (1997). Software tools for analysis and visualization of fMRI data. *NMR in Biomedicine*, 10(4-5), 171-178. doi:10.1002/(SICI)10991492(199706/08)10:4/5<171::AIDNBM453>3.0.CO;2-L

Examples

```
y <- rnorm(99) + cos(seq(99)/15)*3
y[20] <- 20
despike_3D(y, method="NEW")
if (requireNamespace("quantreg", quietly=TRUE)) {
 despike_3D(y)
}
```

---

dice_coef *Dice coefficient*

Description

Dice coefficient

Usage

```
dice_coef(X, Y = NULL)
```

Arguments

`X`, `Y`	Numeric vectors, or matrices with locations along the rows and networks along the columns. Dice coefficients will be calculated between each pair of networks between `X` and `Y`; if `Y` is not provided, `X` will be used for `Y`.

Value

The Dice coefficients in a $Q_x \times Q_y$ matrix, where Q_x is the number of columns in `X`, Q_y is the number of columns in `Y`, and element ij is the Dice coefficient between network i of `X` and network j of `Y`.

dilate_mask_vol *Dilate 3D mask*

Description

Dilate a volumetric mask by a certain number of voxel layers. For each layer, any out-of-mask voxel adjacent to at least one in-mask voxel is added to the mask.

Usage

```
dilate_mask_vol(vol, n_dilate = 1, out_of_mask_val = NA, new_val = 1)
```

Arguments

vol	The 3D array to dilate. The mask to dilate is defined by all values not in out_of_mask_val.
n_dilate	The number of layers to dilate the mask by. Default: 1.
out_of_mask_val	A voxel is not included in the mask if and only if its value is in this vector. Default: NA. If vol is simply a logical array with TRUE values for in-mask voxels, use out_of_mask_val=FALSE.
new_val	Value for voxels newly added to the mask. Default: 1. If vol is simply a logical array with TRUE values for in-mask voxels, use new_val=1.

Details

Diagonal voxels are not considered adjacent, i.e. the voxel at (0,0,0) is not adjacent to the voxels at (1,1,0) or (1,1,1), although it is adjacent to (1,0,0).

Value

The dilated vol. It is the same as vol, but dilated voxels are replaced with new_val.

dual_reg *Dual Regression*

Description

Perform dual regression.

Usage

```
dual_reg(
  BOLD,
  GICA,
  drop_first = 0,
  nuisance = NULL,
  scrub = NULL,
  TR = NULL,
  hpf = 0.01,
  lpf = NULL,
  scale_by = c("mean", "sd", "FUN", "none"),
  scale_sm_FWHM = 4,
  scale_sm_xifti = NULL,
  scale_FUN = NULL,
  GSR = FALSE
)
```

Arguments

BOLD	Subject-level fMRI data matrix ($V \times T$). Rows will be centered.
GICA	Group-level independent components ($V \times Q$)
drop_first	(Optional) Number of volumes to drop from the start of each BOLD session. Default: 0.
nuisance	(Optional) Nuisance matrix to regress from the BOLD data. Nuisance regression is performed in a simultaneous regression with any spike regressors from scrub and DCT bases from hpf. Note that the nuisance matrix should be provided with timepoints matching the original BOLD irregardless of drop_first. Nuisance matrices will be truncated automatically if drop_first>0.
scrub	(Optional) Numeric vector of integers giving the indices of volumes to scrub from the BOLD data. (List the volumes to remove, not the ones to keep.) Scrubbing is performed within a nuisance regression by adding a spike regressor to the nuisance design matrix for each volume to scrub. Note that indices are counted beginning with the first index in the BOLD session irregardless of drop_first. The indices will be adjusted automatically if drop_first>0.
TR	The temporal resolution of the data, i.e. the time between volumes, in seconds. TR is required for detrending with hpf.
hpf, lpf	The frequencies at which to apply temporal filtering to the data during preprocessing, in Hertz. Set either to NULL to disable. Default: 0.01 Hz highpass filter, and NULL for the lowpass filter (disabled). Highpass filtering is accomplished by nuisance regression of discrete cosine transform (DCT) bases. Lowpass filtering is accomplished by a non-linear filter: fsl_bptf. Note the TR argument is required for temporal filtering. If TR is not provided, an error is raised if hpf and lpf have been set.

scale_by	Scale the BOLD at each voxel based on either its "mean" (default), its "sd", or do not scale ("none"). Mean scaling cannot be used if the BOLD have already been de-meaned.
scale_sm_FWHM	Full width at half maximum (FWHM) for smoothing the estimates of scale across brain locations (see scale_by), to reduce the variance of the estimates. Set to 0 to disable smoothing, or Inf for "global" smoothing (estimate and use one measure of scale across the entire brain). Otherwise, for "local" smoothing, this should be a positive number. Default: 4.
scale_sm_xifti	Required only for "local" smoothing of the scale estimates with CIFTI data (see scale_sm_FWHM). To smooth the scale estimates, provide a "xifti" object aligned with BOLD. If no "xifti" object is provided (default) smoothing must be skipped.
scale_FUN	If scale_by is "FUN", this function is used to compute the scaling measure from BOLD, after it has been centered (and so after dropping any volumes, and applying nuisance regression, scrubbing, and temporal filtering). Otherwise, ignored.
GSR	Center BOLD across columns (each image)? This is equivalent to performing global signal regression. Default: FALSE.

Details

Row centering is required and column centering is not recommended. Scaling and detrending depend on user preference.

Value

A list containing the subject-level independent components **S** ($Q \times V$), and subject-level mixing matrix **A** (TxQ).

Examples

```
nT <- 30
nV <- 400
nQ <- 7
mU <- matrix(rnorm(nV*nQ), nrow=nV)
mS <- mU %*% diag(seq(nQ, 1)) %*% matrix(rnorm(nQ*nT), nrow=nQ)
BOLD <- mS + rnorm(nV*nT, sd=.05) + 10
GICA <- mU
dual_reg(BOLD=BOLD, GICA=mU, scale_sm_FWHM=Inf, TR=.72)
```

---

dual_reg_parc *Dual Regression for parcel data*

Description

Perform multiple regression for parcel data.

Usage

```
dual_reg_parc(
  BOLD,
  parc,
  parc_vals,
  drop_first = 0,
  nuisance = NULL,
  scrub = NULL,
  TR = NULL,
  hpf = 0.01,
  lpf = NULL,
  scale_by = c("mean", "sd", "FUN", "none"),
  scale_sm_FWHM = 4,
  scale_sm_xifti = NULL,
  scale_FUN = NULL,
  GSR = FALSE
)
```

Arguments

BOLD	fMRI numeric data matrix ($V \times T$)
parc	The parcellation as an integer vector.
parc_vals	The parcel values (keys) in desired order, e.g. `sort(unique(parc))`.
drop_first	(Optional) Number of volumes to drop from the start of each BOLD session. Default: `0`.
nuisance	(Optional) Nuisance matrix to regress from the BOLD data. Nuisance regression is performed in a simultaneous regression with any spike regressors from `scrub` and DCT bases from `hpf`. Note that the nuisance matrix should be provided with timepoints matching the original `BOLD` irregardless of `drop_first`. Nuisance matrices will be truncated automatically if `drop_first>0`.
scrub	(Optional) Numeric vector of integers giving the indices of volumes to scrub from the BOLD data. (List the volumes to remove, not the ones to keep.) Scrubbing is performed within a nuisance regression by adding a spike regressor to the nuisance design matrix for each volume to scrub. Note that indices are counted beginning with the first index in the `BOLD` session irregardless of `drop_first`. The indices will be adjusted automatically if `drop_first>0`.
TR	The temporal resolution of the data, i.e. the time between volumes, in seconds. `TR` is required for detrending with `hpf`.
hpf, lpf	The frequencies at which to apply temporal filtering to the data during preprocessing, in Hertz. Set either to `NULL` to disable. Default: `0.01` Hz highpass filter, and `NULL` for the lowpass filter (disabled). Highpass filtering is accomplished by nuisance regression of discrete cosine transform (DCT) bases. Lowpass filtering is accomplished by a non-linear filter: `fsl_bptf`.

Note the TR argument is required for temporal filtering. If TR is not provided, an error is raised if hpf and lpf have been set.

scale_by — Scale the BOLD at each voxel based on either its "mean" (default), its "sd", or do not scale ("none"). Mean scaling cannot be used if the BOLD have already been de-meaned.

scale_sm_FWHM — Full width at half maximum (FWHM) for smoothing the estimates of scale across brain locations (see scale_by), to reduce the variance of the estimates. Set to 0 to disable smoothing, or Inf for "global" smoothing (estimate and use one measure of scale across the entire brain). Otherwise, for "local" smoothing, this should be a positive number. Default: 4.

scale_sm_xifti — Required only for "local" smoothing of the scale estimates with CIFTI data (see scale_sm_FWHM). To smooth the scale estimates, provide a "xifti" object aligned with BOLD. If no "xifti" object is provided (default) smoothing must be skipped.

scale_FUN — If scale_by is "FUN", this function is used to compute the scaling measure from BOLD, after it has been centered (and so after dropping any volumes, and applying nuisance regression, scrubbing, and temporal filtering). Otherwise, ignored.

GSR — Center BOLD across columns (each image)? This is equivalent to performing global signal regression. Default: FALSE.

Value

A list containing the subject-level independent components **S** ($Q \times V$), and subject-level mixing matrix **A** (TxQ).

`erode_mask_vol` *Erode 3D mask*

Description

Erode a volumetric mask by a certain number of voxel layers. For each layer, any in-mask voxel adjacent to at least one out-of-mask voxel is removed from the mask.

Usage

```
erode_mask_vol(vol, n_erosion = 1, out_of_mask_val = NA)
```

Arguments

vol — The 3D array to erode. The mask to erode is defined by all values not in out_of_mask_val.

n_erosion — The number of layers to erode the mask by. Default: 1.

out_of_mask_val — A voxel is not included in the mask if and only if its value is in this vector. The first value of this vector will be used to replace eroded voxels. Default: NA. If vol is simply a logical array with TRUE values for in-mask voxels, use out_of_mask_val=FALSE.

Details

Diagonal voxels are not considered adjacent, i.e. the voxel at (0,0,0) is not adjacent to the voxels at (1,1,0) or (1,1,1), although it is adjacent to (1,0,0).

Value

The eroded `vol`. It is the same as `vol`, but eroded voxels are replaced with `out_of_mask_val[1]`.

`expand_RPs` *Expand realignment parameters (RPs)*

Description

Compute the squares, differences, and square differences of each RP timeseries.

Usage

```
expand_RPs(RPs)
```

Arguments

`RPs`	A $T \times N$ numeric matrix, where T is the number of timepoints and N is the number of RPs (typically six) to expand.

Value

A $T \times 4N$ numeric matrix, with the first N columns being the original `RPs`, the next N being the differences, the next N being the squares, and the last N being the squared differences.

`flags2spikes` *Flags to nuisance spikes*

Description

Convert flagged volumes to corresponding one-hot encoded vectors which can be used for nuisance regression.

Usage

```
flags2spikes(flags, n_time)
```

Arguments

`flags`	Numeric vector of integers indicating the indices of the flagged volumes. Or, a logical vector of length `n_time` where `TRUE` values indicate the flagged volumes.
`n_time`	The length of the vectors to obtain. For nuisance regression, this is the length of the BOLD data. The highest index in `flags` should not exceed `n_time`.

Value

A numeric matrix of ones and zeroes. The number of rows will be `n_time` and the number of columns will be the number of flags. Each column will have a `1` at the flag index, and `0` elsewhere.

`fmat_mult` *Filter matrix multiplication*

Description

Multiplies a data matrix by a filter matrix, efficiently handling orientations of the input and output data to avoid unnecessary transpositions.

Usage

```
fmat_mult(dat, fmat, dat_idx_by_var = NULL, out_idx_by_var = TRUE)
```

Arguments

`dat`	The data matrix to multiply.
`fmat`	The filter matrix to multiply with. The first and second dimensions match the number of indices in `dat`.
`dat_idx_by_var`	Is `dat` indices by variables?
`out_idx_by_var`	Should the result be indices by variables?

Value

The filtered/multiplied data matrix.

Examples

```
dat <- matrix(rnorm(7000), 100, 70)
fmat <- gaussian_hpf_mat(100, 2)
# Below all yield the same result.
dat_filt <- fmat_mult(dat, fmat)
dat_filt2 <- fmat_mult(dat, fmat, dat_idx_by_var=TRUE)
dat_filt3 <- fmat_mult(t(dat), fmat)
dat_filt4 <- t(fmat_mult(dat, fmat, out_idx_by_var=FALSE))
```

fMRItools *fMRItools: Routines for Common fMRI Processing Tasks*

Description

See `help(package="fMRItools")` for a list of functions.

Author(s)

Maintainer: Amanda Mejia <mandy.mejia@gmail.com> (ORCID)

Authors:

- Amanda Mejia <mandy.mejia@gmail.com> (ORCID)
- Damon Pham <damondpham@gmail.com> (ORCID)

Other contributors:

- Mark Fiecas <mfiecas@umn.edu> [contributor]

See Also

Useful links:

- https://github.com/mandymejia/fMRItools
- Report bugs at https://github.com/mandymejia/fMRItools/issues

fsl_bptf *Band-Pass temporal filter*

Description

Apply a band-pass temporal filter to data using Gaussian high-pass and low-pass filters. This function is designed to replicate the behavior of the high-pass filter in FSL's `-bptf` command from `fslmaths`, and to use a similar strategy for the low-pass filter.

Usage

```
fsl_bptf(
  dat,
  HP_sigma = NULL,
  LP_sigma = NULL,
  dat_idx_by_var = TRUE,
  out_idx_by_var = TRUE
)
```

Arguments

dat	A numeric matrix of time-series data.
HP_sigma	Numeric. The standard deviation of the Gaussian kernel for the high-pass filter, in time points. Default: NULL (no high-pass filtering). sigma = 0.5 * cutoff_sec / TR
LP_sigma	Numeric. The standard deviation of the Gaussian kernel for the low-pass filter, in time points. Default: NULL (no low-pass filtering).
dat_idx_by_var	Is dat indices (timepoints) by variables? Default: TRUE.
out_idx_by_var	Should the result be indices (timepoints) by variables?

Value

A filtered numeric object of the same dimensions as dat, transposed if out_idx_by_var and dat_idx_by_var differ.

References

FSL FEAT User Guide

Examples

```
cutoff_sec <- 2000 # filter cutoff in seconds
tr <- .72 # in seconds
hp_sigma <- 0.5 * cutoff_sec / tr
dat <- matrix(rnorm(1200 * 70), 1200, 70)
dat_filt <- fsl_bptf(dat, HP_sigma=hp_sigma)
```

---

gaussian_hpf_mat *Gaussian HPF matrix*

Description

Matrix for applying a Gaussian-weighted local linear detrending high-pass filter.

Usage

```
gaussian_hpf_mat(nT, sigma)
```

Arguments

nT	The number of time points in the data.
sigma	The standard deviation of the Gaussian kernel in time points.

Value

A matrix of size nT x nT that can be used to apply a Gaussian high-pass filter to data.

gaussian_lpf_mat *Gaussian LPF matrix*

Description

Matrix for applying a Gaussian low-pass filter.

Usage

```
gaussian_lpf_mat(nT, sigma)
```

Arguments

nT	The number of time points in the data.
sigma	The standard deviation of the Gaussian kernel in time points.

Value

A matrix of size nT x nT that can be used to apply a Gaussian low-pass filter to data.

hat_matrix *Hat matrix*

Description

Get the hat matrix from a design matrix.

Usage

```
hat_matrix(design)
```

Arguments

design	The T by Q design matrix

Details

Uses the QR decomposition.

Value

The T by T hat matrix

Examples

```
hat_matrix(cbind(seq(100), 1))
```

infer_format_ifti *Infer fMRI data format*

Description

Infer fMRI data format

Usage

```
infer_format_ifti(BOLD, verbose = FALSE)
```

Arguments

BOLD	The fMRI data
verbose	Print the format? Default: FALSE.

Value

A length-two vector. The first element indicates the format: "CIFTI" file path, "xifti" object, "GIFTI" file path, "gifti" object, "NIFTI" file path, "nifti" object, "RDS" file path, or "data". The second element indicates the sub-format if relevant; i.e. the type of CIFTI or GIFTI file/object.

infer_format_ifti_vec *Infer fMRI data format for several inputs*

Description

Vectorized version of infer_format_ifti. Expects all inputs to have the same format.

Usage

```
infer_format_ifti_vec(BOLD, verbose = FALSE)
```

Arguments

BOLD	The vector of fMRI data, expected to be of one format
verbose	Print the format? Default: FALSE.

Details

Raises an error if the elements of BOLD do not share the same format.

Value

A length-two vector. The first element indicates the format: "CIFTI" file path, "xifti" object, "GIFTI" file path, "gifti" object, "NIFTI" file path, "nifti" object, "RDS" file path, or "data". The second element indicates the sub-format if relevant; i.e. the type of CIFTI or GIFTI file/object.

is_1 *Is this object the expected data type, and length one?*

Description

Is this object the expected data type, and length one?

Usage

```
is_1(x, dtype = c("numeric", "logical", "character"))
```

Arguments

x	The value to check
dtype	The data type. Default: "numeric". Also can be "logical" or "character"

Value

TRUE if x is dtype and length one.

is_constant *Is this numeric vector constant?*

Description

Is this numeric vector constant?

Usage

```
is_constant(x, TOL = 1e-08)
```

Arguments

x	The numeric vector
TOL	minimum range of x to be considered non-constant. Default: 1e-8

Value

Is x constant?

is_integer *Is this an integer?*

Description

Is this an integer?

Usage

```
is_integer(x, nneg = FALSE)
```

Arguments

x	The putative integer
nneg	Require x>=0 (non-negative) too?

Value

Logical indicating whether x is an integer

is_posNum *Is this object a positive number? (Or non-negative)*

Description

Is this object a positive number? (Or non-negative)

Usage

```
is_posNum(x, zero_ok = FALSE)
```

Arguments

x	The value to check
zero_ok	Is a value of zero ok?

Value

Logical indicating if x is a single positive or non-negative number

mask_BOLD *Create a mask based on vertices that are invalid*

Description

Create a mask based on vertices that are invalid

Usage

```
mask_BOLD(BOLD, meanTol = -Inf, varTol = 1e-06, verbose = TRUE)
```

Arguments

BOLD	A $V \times T$ numeric matrix. Each row is a location.
meanTol, varTol	Tolerance for mean and variance of each data location. Locations which do not meet these thresholds are masked out of the analysis. Defaults: `-Inf` for `meanTol` (ignore), and `1e-6` for `varTol`.
verbose	Print messages counting how many locations are removed?

Value

A logical vector indicating valid vertices

mat2UT *Matrix to Upper Triangular Vector*

Description

Returns the vectorized upper triangle of a square matrix

Usage

```
mat2UT(x, diag = FALSE)
```

Arguments

x	A square matrix
diag	Get the diagonal values too? Default: `FALSE`

Value

The vectorized upper triangle of x.

match_exactly *Do these character vectors match exactly?*

Description

Checks if a user-defined character vector matches an expected character vector. That is, they share the same lengths and entries in the same order. For vectors of the same lengths, the result is `all(a == b)`.

Usage

```
match_exactly(
  user,
  expected,
  fail_action = c("message", "warning", "stop", "nothing")
)
```

Arguments

`user`	Character vector of user input.
`expected`	Character vector of expected/allowed values.
`fail_action`	If any value in `user` could not be matched, or repeated matches occurred, what should happen? Possible values are `"message"` (default), `"warning"`, `"stop"`, and `"nothing"`.

Details

Attributes are ignored.

Value

Logical. Do `user` and `expected` match?

match_input *Match user inputs to expected values*

Description

Match each user input to an expected/allowed value. Raise a warning if either several user inputs match the same expected value, or at least one could not be matched to any expected value. `ciftiTools` uses this function to match keyword arguments for a function call. Another use is to match brainstructure labels ("left", "right", or "subcortical").

Usage

```
match_input(
  user,
  expected,
  fail_action = c("stop", "warning", "message", "nothing"),
  user_value_label = NULL
)
```

Arguments

user	Character vector of user input. These will be matched to expected using match.arg.
expected	Character vector of expected/allowed values.
fail_action	If any value in user could not be matched, or repeated matches occurred, what should happen? Possible values are "stop" (default; raises an error), "warning", and "nothing".
user_value_label	How to refer to the user input in a stop or warning message. If NULL, no label is used.

Value

The matched user inputs.

---

match_nets *Find best matches for each network based on Dice overlap*

Description

For each network (map or parcel) in A, it finds the network in B with which it has the highest Dice coefficient. (Some networks in B will have zero matches, and some will have more than one.)

Usage

```
match_nets(A, B = "Yeo_7", B_zero_drop = TRUE, brainstructures = "existing")
```

Arguments

A	The networks to find matches for. Can be a CIFTI file path, a "xifti" object, a numeric matrix (locations by networks, and can be continuous or binary), or a locations-length vector giving the network index each location belongs to.
B	The networks to match to. Can be a CIFTI file path, a "xifti" object, a numeric matrix (locations by networks, and can be continuous or binary), a locations-length vector giving the network index each location belongs to, or the name of a parcellation included in ciftiTools. Default: "Yeo_7".

B_zero_drop If B is a parcellation (i.e. a vector of network indices), and the lowest parcel index is 0, drop that level? Sometimes the zero-valued parcel is used for the medial wall or other invalid locations. Default: TRUE. If FALSE, treat it as a candidate for matching just like all the other parcels.

brainstructures
The brainstructures to use, if A and/or B are CIFTI data. Default: "existing" to use the brainstructures present in A (or in B if A is a matrix).

Details

If the resolutions of A and B differ, it will try to resample B to match the resolution of A.

Value

A numeric vector giving the indices of B networks that are the best matches for each network in A. order(match_nets(A, B)) would give an indexing of A that rearranges its networks according to the order of networks in B.

---

mean_squares *Compute mean squares from variance decomposition*

Description

Compute mean squares from variance decomposition

Usage

```
mean_squares(vd)
```

Arguments

vd The variance decomposition

Value

The mean squares

Mode *Mode of data vector*

Description

Get mode of a data vector. But use the median instead of the mode if all data values are unique.

Usage

```
Mode(x)
```

Arguments

x	The data vector

Value

The mode

norm_BOLD *Normalize BOLD data*

Description

Clean the data (scrubbing, detrending, nuisance regression, and temporal filtering in a simultaneous framework), then center it, then scale it, in that order.

Usage

```
norm_BOLD(
  BOLD,
  drop_first = 0,
  nuisance = NULL,
  scrub = NULL,
  TR = NULL,
  hpf = 0.01,
  lpf = NULL,
  center_rows = TRUE,
  center_cols = FALSE,
  scale_by = c("mean", "sd", "FUN", "none"),
  scale_sm_FWHM = 4,
  scale_sm_xifti = NULL,
  scale_sm_xifti_mask = NULL,
  scale_FUN = NULL,
  give_stats = FALSE
)
```

Arguments

BOLD	fMRI numeric data matrix ($V \times T$)
drop_first	(Optional) Number of volumes to drop from the start of each BOLD session. Default: 0.
nuisance	(Optional) Nuisance matrix to regress from the BOLD data. Nuisance regression is performed in a simultaneous regression with any spike regressors from scrub and DCT bases from hpf. Note that the nuisance matrix should be provided with timepoints matching the original BOLD irregardless of drop_first. Nuisance matrices will be truncated automatically if drop_first>0.
scrub	(Optional) Numeric vector of integers giving the indices of volumes to scrub from the BOLD data. (List the volumes to remove, not the ones to keep.) Scrubbing is performed within a nuisance regression by adding a spike regressor to the nuisance design matrix for each volume to scrub. Note that indices are counted beginning with the first index in the BOLD session irregardless of drop_first. The indices will be adjusted automatically if drop_first>0.
TR	The temporal resolution of the data, i.e. the time between volumes, in seconds. TR is required for detrending with hpf.
hpf, lpf	The frequencies at which to apply temporal filtering to the data during preprocessing, in Hertz. Set either to NULL to disable. Default: 0.01 Hz highpass filter, and NULL for the lowpass filter (disabled). Highpass filtering is accomplished by nuisance regression of discrete cosine transform (DCT) bases. Lowpass filtering is accomplished by a non-linear filter: fsl_bptf. Note the TR argument is required for temporal filtering. If TR is not provided, an error is raised if hpf and lpf have been set.
center_rows, center_cols	Center BOLD data across rows (each data location's time series) or columns (each time point's image)? Default: TRUE for row centering, and FALSE for column centering.
scale_by	Scale the BOLD at each voxel based on either its "mean" (default), its "sd", or do not scale ("none"). Mean scaling cannot be used if the BOLD have already been de-meaned.
scale_sm_FWHM	Full width at half maximum (FWHM) for smoothing the estimates of scale across brain locations (see scale_by), to reduce the variance of the estimates. Set to 0 to disable smoothing, or Inf for "global" smoothing (estimate and use one measure of scale across the entire brain). Otherwise, for "local" smoothing, this should be a positive number. Default: 4.
scale_sm_xifti	Required only for "local" smoothing of the scale estimates with CIFTI data (see scale_sm_FWHM). To smooth the scale estimates, provide a "xifti" object aligned with BOLD. If no "xifti" object is provided (default) smoothing must be skipped.
scale_sm_xifti_mask	For local smoothing of scale estimates, the data must be unmasked to be mapped back to the surface. So if the data are masked, provide the mask here.

scale_FUN — If scale_by is "FUN", this function is used to compute the scaling measure from BOLD, after it has been centered (and so after dropping any volumes, and applying nuisance regression, scrubbing, and temporal filtering). Otherwise, ignored.

give_stats — Return the intercept, residual SD estimates, and full design matrix from the nuisance regression? Default: FALSE

Value

Normalized BOLD data matrix ($V \times T$), or if give_stats, a list with three elements: the normed BOLD, the intercept estimate, and the residual SD estimate.

---

nuisance_regression *Nuisance regression*

Description

Performs nuisance regression. Important note: the data and design matrix must both be centered, or an intercept must be included in the design matrix.

Usage

```
nuisance_regression(Y, design)
```

Arguments

Y — The $T \times V$ or $V \times T$ data.

design — The $T \times Q$ matrix of nuisance regressors.

Value

The data after nuisance regression.

Examples

```
Y <- matrix(rnorm(700), nrow=100)
design <- cbind(seq(100), 1)
nuisance_regression(Y, design)
```

pad_vol *Pad 3D Array*

Description

Pad a 3D array by a certain amount in each direction, along each dimension. This operation is like the opposite of cropping.

Usage

```
pad_vol(x, padding, fill = NA)

uncrop_vol(x, padding, fill = NA)
```

Arguments

x	A 3D array, e.g. `unvec_vol(xifti$data$subcort, xifti$meta$subcort$mask)`.
padding	A 3×2 matrix indicating the number of slices to add at the beginning (first column) and end (second column) of each of dimension, e.g. `xifti$meta$subcort$mask_padding`.
fill	Value to pad with. Default: `NA`.

Value

The padded array

Examples

```
x <- array(seq(24), dim=c(2,3,4))
y <- pad_vol(x, array(1, dim=c(3,2)), 0)
stopifnot(all(dim(y) == dim(x)+2))
stopifnot(sum(y) == sum(x))
z <- crop_vol(y)$data
stopifnot(identical(dim(x), dim(z)))
stopifnot(max(abs(z - x))==0)
```

PCA *PCA for tall matrix*

Description

Efficient PCA for a tall matrix (many more rows than columns). Uses the eigendecomposition of the covariance matrix. The dimensionality of the result can be preset with `Q` or estimated with PESEL.

Usage

```
PCA(X, center = TRUE, Q = NULL, Q_max = 100, Vdim = 0)
```

Arguments

X	The tall numeric matrix for which to compute the PCA. For fMRI data, X should be V brain locations by T timepoints.
center	Center the columns of X? Default: TRUE. Set to FALSE if already centered. Centered data is required to compute PCA.
Q	Number of latent dimensions to estimate. If NULL (default), estimated using PESEL (Sobczyka et al. 2020).
Q_max	Maximal number of principal components for automatic dimensionality selection with PESEL. Default: 100.
Vdim	Number of principal directions to obtain. Default: 0. Can also be "Q" to set equal to the value of Q. Note that setting this value less than Q does not speed up computation time, but does save on memory. Note that the directions will be with respect to X, not its covariance matrix.

Value

The decomposition: a list with the eigenvalues d, the eigenvectors u, and (if Vdim > 0) the unit-norm principal directions v.

Examples

```
U <- matrix(rnorm(900), nrow=300, ncol=3)
V <- matrix(rnorm(15), nrow=3, ncol=5)
PCA(U %*% V)
```

---

pct_sig *Convert data values to percent signal.*

Description

Convert data values to percent signal.

Usage

```
pct_sig(X, center = median, by = c("column", "all"))
```

Arguments

X	a T by N numeric matrix. The columns will be normalized to percent signal.
center	A function that computes the center of a numeric vector. Default: median. Other common options include mean and mode.
by	Should the center be measured individually for each "column" (default), or should the center be the same across "all" columns?

Value

X with its columns normalized to percent signal. (A value of 85 will represent a -15% signal change.)

plot_FC *Plot FC*

Description

Plot a functional connectivity matrix.

Usage

```
plot_FC(
  FC,
  zlim = c(-1, 1),
  diag_val = NULL,
  title = "FC matrix",
  cols = color_palette("Beach"),
  cleg_ticks_by = diff(zlim)/2,
  cleg_digits = NULL,
  labels = NULL,
  lines = NULL,
  lines_col = "black",
  lines_lwd = 1,
  cex = 0.8
)
```

Arguments

FC	The functional connectivity matrix, a square numeric matrix with values between -1 and 1.
zlim	The minimum and maximum range of the color scale. Default: `c(-1, 1)`. If in descending order, the color scale will be reversed.
diag_val	Set to `NA` for white, `1`, or `NULL` (default) to not modify the diagonal values in `FC`.
title	(Optional) Plot title.
cols	Character vector of colors for the color scale. Default: `color_palette("Beach")`.
cleg_ticks_by	Spacing between ticks on the color legend. Default: `range(zlim)/2`.
cleg_digits	How many decimal digits for the color legend. Default: `NULL` to set automatically.
labels	A character vector of length `length(lines)+1`, giving row/column labels for the submatrices divided by `lines`. If `NULL` (default), do not add labels.
lines	Add lines to divide the FC matrix into submatrices? Default: `NULL` (do not draw lines). Set to `"all"` to delineate each individual row and column.
lines_col, lines_lwd	Color and line width of the `lines`. Default: black lines of width `1`.
cex	Text size. Default: `0.8`.

plot_FC_gg *Plot FC with ggplot2*

Description

Plot a FC matrix.

Usage

```
plot_FC_gg(
  mat,
  colFUN = NULL,
  title = "FC Matrix",
  legTitle = "",
  group_divs = NULL,
  group_cols = RColorBrewer::brewer.pal(8, "Set2"),
  labs = NULL,
  uppertri_means = TRUE,
  divColor = "black",
  lim = 0.5,
  diagVal = 1,
  labs_margin_y = NULL,
  labs_margin_x = 0
)
```

Arguments

mat	The FC matrix
colFUN	A scale_fill function. If NULL, use a red-blue diverging palette if there are negative values in mat, and viridis' inferno sequential palette otherwise.
title	The plot title. Default: "FC Matrix".
legTitle	The legend title. Default: "".
group_divs, group_cols	Split the FC matrix into groups of contiguous rows/columns? Use group_divs to indicate the index of the first element in each group. For example, if the groups are 1-8, 9-15, and 16 to 25, set group_divs=c(1, 9, 16). Groups will be indicated by a color bar along the left and top sides of the plot. Use group_cols to change the colors. By default, group_divs is NULL (no groups).
labs	Labels to place along the y-axis? If is.null(group_divs), this should be a character vector labeling each row of mat, or a dot dot dot. If !is.null(group_divs), this may alternatively be a character vector labeling each group.
uppertri_means	Use the upper triangle of the FC matrix to show the mean of each group indicated by group_divs? Default: TRUE. Has no effect if group_divs is NULL.
divColor	Color of group dividers and outline of the FC matrix. Default: "black".

`lim` Length-two numeric vector indicating the limits for the color bar. Values beyond `lim` will be clipped. If `NULL`, the limits will be set based on the largest magnitude value in `mat` (no clipping). If length-one, the left limit will be 0 if there are no negative values, or `-lim` if there are. Default: `.5`.

`diagVal` On-diagonal values will be set to this value. (`uppertri_means` are calculated before `diagVal` is used.)

`labs_margin_y, labs_margin_x`
Margin value for labels. For the y-axis, a value of `NULL` (default) will set the margin value adaptively depending on the size of the FC matrix such that the labels are almost flush with the y-axis. The default for the x-axis is `0`, which also results in labels almost flush with the x-axis.

Value

The plot

`read_nifti` *Wrapper to functions for reading NIFTIs*

Description

Tries `RNifti::readNifti`, then `oro.nifti::readNIfTI`. If neither package is available an error is raised.

Usage

```
read_nifti(nifti_fname)
```

Arguments

`nifti_fname` The file name of the NIFTI.

Details

For `oro.nifti::readNIFTI` the argument `reorient=FALSE` will be used.

Value

The NIFTI

scale_design_mat *Scale a design matrix*

Description

Scale the columns of a matrix by dividing each column by its highest-magnitude value, and then subtracting its mean. Constant columns will not be de-meaned; all values will become 1.

Usage

```
scale_design_mat(x, doRows = FALSE)
```

Arguments

x	A $T \times K$ numeric matrix. In the context of a design matrix for a GLM analysis of task fMRI, T is the number of time points and K is the number of task covariates.
doRows	Scale the rows instead? Default: FALSE.

Value

The scaled design matrix

Examples

```
scale_design_mat(cbind(seq(7), 1, rnorm(7)))
```

scale_med *Robust scaling*

Description

Centers and scales the columns of a matrix robustly

Usage

```
scale_med(mat, TOL = 1e-08, drop_const = TRUE, doRows = FALSE)
```

Arguments

mat	A numeric matrix. Its columns will be centered and scaled.
TOL	Columns with MAD below this value will be considered constant. Default: 1e-8
drop_const	Drop constant columns? Default: TRUE. If FALSE, set to NA instead.
doRows	Center and scale the rows instead? Default: FALSE.

Details

Centers each column on its median, and scales each column by its median absolute deviation (MAD). If there are constant-valued columns, they are removed if `drop_const` or set to `NA` if `!drop_const`, and a warning is raised. If all columns are constant, an error is raised.

Value

The input matrix with its columns centered and scaled.

---

scale_timeseries *Scale the BOLD timeseries*

Description

Scale the BOLD timeseries

Usage

```
scale_timeseries(
  BOLD,
  scale = c("auto", "mean", "sd", "none"),
  transpose = TRUE
)
```

Arguments

`BOLD`	fMRI data as a locations by time ($V \times T$) numeric matrix.
`scale`	Option for scaling the BOLD response.
	`\code{"auto"} (default) will use \code{"mean"} scaling except if demeaned`
	data is detected (if any mean is less than one), in which case `"sd"` scaling will be used instead.
	`\code{"mean"} scaling will scale the data to percent local signal change.`
	`\code{"sd"} scaling will scale the data by local standard deviation.`
	`\code{"none"} will only center the data, not scale it.`
`transpose`	Transpose `BOLD` if there are more columns than rows? (Because we usually expect the number of voxels to exceed the number of time points.) Default: `TRUE`.

Value

Scale to units of percent local signal change and centers

sign_flip *Sign match ICA results*

Description

Flips all source signal estimates (S) to positive skew

Usage

```
sign_flip(x)
```

Arguments

x	The ICA results: a list with entries "S" and "M"

Value

x but with positive skew source signals

skew_pos *Positive skew?*

Description

Does the vector have a positive skew?

Usage

```
skew_pos(x)
```

Arguments

x	The numeric vector for which to calculate the skew. Can also be a matrix, in which case the skew of each column will be calculated.

Value

TRUE if the skew is positive or zero. FALSE if the skew is negative.

`sum_neighbors_vol` *Sum of each voxel's neighbors*

Description

For each voxel in a 3D logical or numeric array, sum the values of the six neighboring voxels.

Usage

```
sum_neighbors_vol(arr, pad = 0)
```

Arguments

`arr`	The 3D array.
`pad`	In order to compute the sum, the array is temporarily padded along each edge with the value of `pad`. `0` (default) will mean that edge voxels reflect the sum of 3-5 neighbors whereas non-edge voxels reflect the sum of 6 neighbors. An alternative is to use a value of `NA` so that edge voxels are `NA`-valued because they did not have a complete set of six neighbors. Perhaps another option is to use `mean(arr)`.

Details

Diagonal voxels are not considered adjacent, i.e. the voxel at (0,0,0) is not adjacent to the voxels at (1,1,0) or (1,1,1), although it is adjacent to (1,0,0).

Value

An array with the same dimensions as `arr`. Each voxel value will be the sum across the immediate neighbors. If `arr` was a logical array, this value will be between 0 and 6.

`temporal_filter` *Temporal filtering (bandpass, highpass, lowpass) with DCT or FFT*

Description

Temporal filtering (bandpass, highpass, lowpass) with DCT or FFT

Usage

```
temporal_filter(
  X,
  TR,
  hpf = 0.008,
  lpf = NULL,
  method = c("DCT", "FFT"),
  verbose = FALSE
)

detrend(X, TR, hpf = 0.008, method = c("DCT", "FFT"))
```

Arguments

X	A numeric matrix, with each column being a timeseries to filter For fMRI data, X should be T timepoints by V brain locations. Alternatively, a single integer giving the number of timepoints in data. The return value will be the suitable set of DCT bases. Only works with method == "DCT".
TR	The time step between adjacent rows of X, in seconds.
hpf	The frequency of the highpass filter, in Hertz. Default: .008.
lpf	The frequency of the lowpass filter, in Hertz. Default: NULL (skip lowpass filtering). If both are provided, lpf > hpf must be true.
method	"DCT" (default) or "FFT". FFT is not compatible with lpf yet.
verbose	Print messages? Default: FALSE.

Value

Filtered X, or if X was an integer, the set of DCT bases to use for nuisance regression (not including an intercept).

Examples

```
temporal_filter(matrix(rnorm(700), nrow=100), TR=.72)
```

---

unmask_mat *Unmask matrix data*

Description

Insert empty rows or columns to a matrix. For example, medial wall vertices can be added back to the cortex data matrix.

Usage

```
unmask_mat(x, mask, mask_dim = 1, fill = NA)
```

Arguments

x	The data matrix to unmask.
mask	The logical mask: the number of TRUE values should match the size of the (mask_dim)th dimension in dat.
mask_dim	Rows, 1 (default), or columns, 2.
fill	The fill value for the inserted rows/columns. Default: NA.

Value

The unmasked matrix.

---

unvec_mat *Transform vector data to image*

Description

From a $v \times p$ matrix of vectorized data and an $m \times n$ image mask with v in-mask locations, create a list of p $m \times n$ data arrays in which the mask locations are filled in with the vectorized data values.

Consider using abind::abind to merge the result into a single array.

Usage

```
unvec_mat(x, mask, fill_value = NA)
```

Arguments

x	$v \times p$ matrix, where v is the number of voxels within a mask and p is the number of vectors to transform into matrix images.
mask	$m \times n$ logical matrix in which v entries are TRUE and the rest are FALSE.
fill_value	Out-of-mask value in the output image. Default: NA.

Value

A list of masked values from x

Examples

```
x <- unvec_mat(
 cbind(seq(3), seq(2,4), seq(3,5)),
 matrix(c(rep(TRUE, 3), FALSE), ncol=2),
 0
)
y <- array(c(1,2,3,0,2,3,4,0,3,4,5,0), dim=c(2,2,3))
stopifnot(identical(x[[1]], y[,,1]))
stopifnot(identical(x[[2]], y[,,2]))
stopifnot(identical(x[[3]], y[,,3]))
```

unvec_vol *Convert vectorized data back to volume*

Description

Un-applies a mask to vectorized data to yield its volumetric representation. The mask and data should have compatible dimensions: the number of rows in `dat` should equal the number of locations within the `mask`.

Usage

```
unvec_vol(dat, mask, fill = NA)
```

Arguments

`dat`	Data matrix with locations along the rows and measurements along the columns. If only one set of measurements were made, this may be a vector.
`mask`	Volumetric binary mask. `TRUE` indicates voxels inside the mask.
`fill`	The value for locations outside the mask. Default: `NA`.

Value

The 3D or 4D unflattened volume array

UT2mat *Upper Triangular Vector to Matrix*

Description

Creates a square matrix from a vector which gives the values for the upper triangle. By default, the vector is expected to include the diagonal values, and the values in the upper triangle are copied to the lower triangle so that the result is symmetric.

Usage

```
UT2mat(x, diag = "x", LT = "x")
```

Arguments

`x`	A vector of values for the upper triangular elements of the desired square matrix.
`diag`	The values to put on the diagonal, or `"x"` (default) if `x` includes the diagonal values.
`LT`	The values to put on the lower triangle, or `"x"` (default) to use the upper triangular values such that the result is symmetric. (`LT` should not contain the diagonal values, which are provided with `diag` or `x`).

Value

A square matrix.

Examples

```
UT2mat(seq(10)) # defaults: diag="x", LT="x"
#      [,1] [,2] [,3] [,4]
# [1,]    1    2    4    7
# [2,]    2    3    5    8
# [3,]    4    5    6    9
# [4,]    7    8    9   10
UT2mat(seq(3), LT=8)
#      [,1] [,2]
# [1,]    1    2
# [2,]    8    3
UT2mat(seq(6), diag=0, LT=seq(7,12))
#      [,1] [,2] [,3] [,4]
# [1,]    0    1    2    4
# [2,]    7    0    3    5
# [3,]    8   10    0    6
# [4,]    9   11   12    0
UT2mat(rep(-1, 3), diag=c(4,5,6), LT=0)
#      [,1] [,2] [,3]
# [1,]    4   -1   -1
# [2,]    0    5   -1
# [3,]    0    0    6
```

---

validate_design_mat *Validate design matrix*

Description

Coerces `design` to a numeric matrix, and optionally checks that the number of rows is as expected. Sets constant-valued columns to 1, and scales all other columns.

Usage

```
validate_design_mat(design, T_ = NULL)
```

Arguments

`design`	The design matrix
`T_`	the expected number of rows in `design`. Default: `NULL` (no expected value to validate).

Value

The (modified) design matrix

var_decomp *Compute variance decomposition*

Description

Calculate the various ANOVA sums of squares for repeated measures data. For each variable, subjects with any missing measurement are excluded.

Usage

```
var_decomp(x, verbose = FALSE)
```

Arguments

x	The data as a 3D array: measurements by subjects by variables. (Alternatively, a matrix that is measurements by subjects, if only one variable exists.)
verbose	If TRUE, display progress of algorithm. Default: FALSE.

Value

The variance decomposition.

vox_locations *Get coordinates of each voxel in a mask*

Description

Made for obtaining voxel locations in 3D space from the subcortical metadata of CIFTI data: the volumetric mask, the transformation matrix and the spatial units.

Usage

```
vox_locations(mask, trans_mat, trans_units = NULL)
```

Arguments

mask	3D logical mask
trans_mat	Transformation matrix from array indices to spatial coordinates.
trans_units	Units for the spatial coordinates (optional).

Value

A list: coords and trans_units.

Index

all_binary, 3
all_integers, 4
as.matrix_ifti, 4

bandstop_filter, 5

carpetplot, 6
carpetplot_stack, 7
cheby2, *5*
colCenter, 8
color_palette, 8
CompCor, 9, *13, 14*
CompCor_clean, *11*, *13*
CompCor_HCP_apply, 11, *13*
CompCor_HCP_calc, *11, 12*, 12
coordlist_to_vol, 15
crop_vol, 15

dct2Hz *(*dct_convert*)*, 16
dct_bases, *11*, 16, *17*
dct_convert, 16
despike_3D, 17
despike_3D.basis, *17, 18*
despike_3D.interpolate, *18*
detrend *(*temporal_filter*)*, 47
dice_coef, 18
dilate_mask_vol, 19
dual_reg, 19
dual_reg_parc, 21

erode_mask_vol, 23
expand_RPs, 24

flags2spikes, 24
fmat_mult, 25
fMRItools, 26
fMRItools-package *(*fMRItools*)*, 26
fsl_bptf, *20*, *22*, 26, *37*

gaussian_hpf_mat, 27
gaussian_lpf_mat, 28

hat_matrix, 28
Hz2dct *(*dct_convert*)*, 16

infer_format_ifti, *29*, 29
infer_format_ifti_vec, 29
is_1, 30
is_constant, 30
is_integer, 31
is_posNum, 31

mask_BOLD, 32
mat2UT, 32
match.arg, *34*
match_exactly, 33
match_input, 33
match_nets, 34
mean_squares, 35
Mode, 36

noise_PCs, *11*, *13*
norm_BOLD, 36
nuisance_regression, 38

pad_vol, 39
PCA, 39
pct_sig, 40
plot_FC, 41
plot_FC_gg, 42

read_nifti, 43

scale_design_mat, 44
scale_med, 44
scale_timeseries, 45
sign_flip, 46
skew_pos, 46
sum_neighbors_vol, 47

temporal_filter, 47

uncrop_vol *(*pad_vol*)*, 39

unmask_mat, 48
unvec_mat, 49
unvec_vol, 50
UT2mat, 50

validate_design_mat, 51
var_decomp, 52
vox_locations, 52