

This article comprises the technical specifications for the Macintosh Duo MiniDock.

Macintosh Duo MiniDock

Logic Board	Ports	Power
Processor: none, PMMU: n/a FPU: none Data Path: , L1 Cache: n/a L2 Cache: none 2nd Processor: n/a Slots: none	USB: ADB: 1 Video: DB-15 Floppy: none SCSI: HDI-30 Geoports: Ethernet: none FireWire: Mic Type: Omni AirPort Ready: Other Ports: Printer Modem Speaker ,	Max Watts: Amps: BTU per Hr: 0 Voltage: n/a Freq Range: n/a Hz Battery Type: none Soft Power: yes
Memory	Video Memory	
Logic Board: none RAM Slots: 0, n/a Min - Max RAM: n/a - n/a Min RAM Speed: RAM Sizes: n/a Install in Groups of: n/a	Resolution 512 x 384 640 x 400 640 x 480 800 x 600 832 x 624 1024 x 768 1152 x 870 1280 x 1024	Video Memory 512K VRAM (built in) 8-bit n/a-bit 8-bit n/a-bit 8-bit n/a-bit n/a-bit n/a-bit
Physical	Software	Storage
Introduced: 10/19/1992 Discontinued: 8/5/1995 Form Factor: n/a Gestalt ID: Weight (lbs): 1.2 Dimensions (in): 2.1 H x 10.6 W x 3.2 D	Addressing Modes: n/a Orig SSW: n/a Orig Enabler: n/a ROM ID: n/a ROM Ver: n/a ROM Size: n/a AppleTalk Ver: n/a Mac OS Supported:	Floppy Size: none Floppy Inject: n/a Min. Int HD Size: none Int HD Interface: none Orig CD Speed n/a Int CD Support:

Document Information

Product Area: Computers
Category: General Topics
Sub Category: General Topics
Keyword: specsht kap keuro kla kcn kjp kus
Last Touched: 2004-09-10 18:58:28