Setting up a Packet–Internet Gateway

Warren Toomey VK1XWT – April 1994

Email: wkt@csadfa.cs.adfa.oz.au

Abstract

This paper discusses the reasons for setting up an amateur packet radio to Internet gateway, technical and hardware features of such a gateway, and security aspects of maintaining a gateway.

Several sections of this paper require some knowledge of amateur packet radio operation, Internet site operation, connecting hardware, and Internet security. These sections will be marked, and I will try to summarise each section in a manner that does not require this knowledge.

This paper is intended for people who have to install a packet-Internet gateway, people who must maintain a packet-Internet gateway (both at the software and hardware level), people who manage a set of Internet machines, and people who provide the facilities for a set of Internet machines (such as a University). This is a wide range of readers, so I apologise in advance if you find some of the material too far below or above your level of understanding.

1 Introduction

The Internet is a large network of academic and commercial computers in the United States that provide a number of communication services (such as electronic mail and file transfers) to its users, via the TCP/IP network protocols. This network is connected to other networks, such as the AARNet in Australia, and networks in Europe and Japan, to provide a global computer network.

The amateur radio service consists of a large number of individuals (known as amateurs or Hams) throughout the world who use radio communications to pass messages, chat, do research into aspects of radio communications and exchange information with other amateurs on several radio frequencies that are allocated for their use. To become an amateur, an individual must undergo an examination which tests the individual's knowledge of the technical operation of radio equipment, radio propagation, electronic theory, as well as legal and other aspects of amateur radio. Thus amateurs form a highly technical, capable and responsible group of people, who are able to provide communication during emergencies, natural disasters, as well as for their own use.

The amateur radio service is also actively involved in finding new and more efficient forms of radio communication - techniques such as single sideband radio and reduced spectrum radio were invented by amateurs. In the last decade or so, amateur radio operators have been involved in researching new forms of digital radio communications. This research has led several amateurs to experiment with different communication protocols for digital radio communications, including the TCP/IP protocols used on the Internet (see Appendix A).

The Internet protocols have been found to be very useful for radio networking, and are now used widely by amateurs. To this end, a block of 16,387,064 Internet addresses has been allocated to the worldwide amateur radio service.

Fast and effective digital radio communications is limited over large distances, due to the distortion and noise introduced by the atmosphere, and the curvature of the Earth. Amateurs have sought several methods to overcome these limitations, such as amateur satellites, which are designed and built by amateurs, and provide store and forward message capabilities as well as digital repeater services.

Another method of overcoming the distance limitation is to use the Internet itself to route digital messages between distant amateur stations. This is easy to accomplish as amateurs are able to use the same network protocols, TCP/IP, as used on the Internet. This method of long-distance amateur communication has been implemented at several places in the world: Australia, America, Switzerland, the Netherlands and Canada, and has been found to be very simple to set up and operate, and is very reliable.

There are two legal/policy aspects of these amateur radio–Internet gateways. The first is the amateur radio service enforces that amateur communications must be between two (or more) licensed amateurs: therefore, non-amateur Internet users must not be able to use the gateways to transmit messages. The second is that many AARNet/Internet sites' policy is to prevent non-registered users from accessing local/Internet resources: therefore amateurs may only pass messages to other amateur gateways. The software that controls the packet–Internet gateways has been written to solidly enforce these two conditions.

2 The Gateway

A packet–Internet gateway obviously must be able to communicate to both the Internet, and the amateurs in its local area. Therefore, it must have at least two **interfaces**, one to the Internet, and one to the amateur community. This is shown in Figure 1.



Figure 1: Packet–Internet Gateway Block Design

The gateway is a machine that runs the software that enables it to perform its function. Currently, this means that it must be an IBM PC computer or clone, running the latest version of the NOS software by Phil Karn, Gerard van der Grinten, and other flavours. The software itself is freely available, but is copyright by the software authors. For performance reasons, I would recommend a computer with at least the performance of a 10MHz IBM XT, with 640K or memory. An AT of course would be better. If you plan on providing file transfer or mail access, a hard disk is needed.

Each interface must have a unique IP address, so that both the local amateurs and the other gateways can communicate with it. The Internet interface's address is assigned by the AARNet/Internet administrator of the institution, and the amateur radio interface's address is assigned by the local amateur IP administrator.

Each interface must also have the appropriate hardware needed for it to communicate with its destination. On the amateur radio side, a **Terminal Node Controller**, a **transceiver** and an **antenna** convert the packets from the gateway into radio transmissions that can be received by amateur stations. On the Internet side, there are two main options: an **Ethernet card** connects the gateway to the local area network, which is part of the AARNet/Internet, or a **serial line** connects the gateway to another machine in the institution which is on the local area network, and hence is part of the AARNet/Internet. The serial line can run either the SLIP or PPP protocol to communicate with the other machine.

That completes the overview of the hardware setup of the gateway. This leads on to several considerations:

- The gateway and other hardware must be reliable, and be readily available to the maintainer of the gateway to fix unforseen problems.

- The gateway must be placed in a physical position to suit both its connection to the AARNet/Internet, and to the TNC/transceiver.
- The transceiver and antenna must be in a position to satisfy both the needs of the local amateur community, and the wishes of the institution where they are to be situated.
- If using Ethernet, the gateway's position must allow it to be physically connected to the local area network.

At this point, it should be mentioned that at least one of the people maintaining the gateway must have a current amateur radio license. The institution providing the Internet connection may also wish to appoint another person to ensure the gateway meets the policies of the institution; this of course may be the same person.

3 How the Gateway Works

At an elementary level, the gateway works as follows: Messages are broken up into **packets** when they are sent over the Internet. When the gateway receives a packet on one interface, it checks the destination IP address in the packet, and according to its table of **routes**, it retransmits that packet on the interface that will send the packet to its destination. For example, a packet from the local amateur radio community to a gateway in another country will be received by the local gateway, retransmitted by the gateway on its Internet interface, and will travel along the Internet to the destination gateway, where it will be received and retransmitted by the transceiver at that gateway.

In practice, this is not as simple, because of the following reason. Even though the global amateur community has been allocated a block of valid Internet addresses, none of the Internet machines in the world know how to send packets to these addresses. This is because up until recently, no amateur computers were connected to the Internet.

The easiest solution would be to advertise the routes to these addresses to all Internet machines, but this was not done for the following reasons:

- Amateur stations are not as geographically fixed as most Internet computers, as their computers are generally smaller, and the radio medium allows amateurs to move around and still communicate with each other, and
- Advertising amateur computer addresses to all Internet machines greatly increases the possibility of non-amateurs accessing amateur transmitters.

The solution adopted was to **encapsulate** amateur packets received by the gateways inside another packet, transmit this bigger packet to the destination gateway, which unwraps the packet and transmits the contents [Woodburn et al. 1991]. This is illustrated in Figure 2.

IP 44.136.0.25 to 44.14.1.2	data

IP 131.236.20.90 to 128.171.41.250	IP 44.136.0.25 to 44.14.1.2	data

IP 44.136.0.25 to 44.14.1.2	data

Figure 2: Amateur Packet Encapsulation

The first packet shown is the packet transmitted by an amateur and received by the local gateway. At this level, the source and destination address are both amateur addresses. The local gateway determines which remote gateway this packet must be passed to, and **encapsulates** the packet inside a new packet, with source and destination addresses being the Internet addresses of the local and remote gateway. The packet is then placed on the 2000Internet, where it is passed to the remote gateway.

This encapsulated packet (the second packet in Figure 2) is seen by the Internet to have a valid source and destination address, and can be passed to the remote gateway. The Internet sees the wrapped packet as data, which it ignores.

At the remote gateway, the packet is received and unwrapped; this is the third packet in Figure 2. The remote gateway determines which interface to transmit the unwrapped packet, according to the destination address. Reply messages are encapsulated in exactly the same manner.

4 AX.25 Encapsulation

One of the first digital protocols used by amateurs, and still the most widely used, is AX.25, a reliable protocol based on X.25. One of its limitations is that AX.25 packets cannot pass through more that 7 intermediate machines before reaching their destination. This limits the distance AX.25 packets can travel.

The latest versions of NOS include AX.25 encapsulation, which operates in exactly the same way as normal IP encapsulation, thereby allowing long distance AX.25 communication while still obeying the 7 step limit [Kantor 1991].

5 Preparing the Gateway Machine

This section discusses the aspects of preparing the gateway for the software that will make the gateway work. It is assumed that:

- You have a fairly good idea of the Internet and how it works.
- You have a reasonable understanding of the NOS software. If you don't, you can either obtain a 'plug 'n play' disk from me by mailing me a note to my email address at the beginning of the paper, or you can anonymous ftp to the machine `minnie.cs.adfa.oz.au`, cd to `hamradio/packet/plugplay`, and get the software from there.
- You have a copy of the NOS software. At the time of writing, the NOS flavour most used on gateways is Johan Reinalda's JNOS, and the current version is 1.07. Other NOS versions used are Phil Karn's KA9Q, and Gerard van der Grinten's PA0GRI. The latest version of these NOS flavours can be obtained from `ucsd.edu` or `grivel.une.oz.au`.
- You have a gateway that meets the hardware specifications given in the Introduction, and the hardware needed to form the interfaces – that is, a TNC, a transceiver, an antenna, and an Ethernet board or a serial link to a machine on the Internet that can talk SLIP or PPP. The gateway will also need around 1 Megabyte of free disk space if it is to provide file transfer or mail access.
- You have a local amateur IP address for the machine, and a local Internet IP address for the machine.

Your first step is to give the gateway two domain names, a name for the other gateways to know, and a name for the amateurs to know. Your Internet name should follow any rules specified for your institution. Your amateur domain name should be of the following form: `name.callsign.ampr.org` where the callsign is the callsign of the amateur that will be operating the gateway, and the name is whatever name you want to call the machine. An example of Internet and amateur domain names is `minnie.cs.adfa.oz.au` and `minnie.vk1xwt.ampr.org`.

You need to register the Internet name on the Domain Name Server for your local area network. You then need to register your amateur domain name with the Domain Name Server for the amateur service. This is the DNS server at `ucsd.edu`. To do this, send email to the following address: `ampraddr@ucsd.edu`. The subject line should be empty, and the email should have the following line:

```
name.callsign              IN    A    amateur.radio.ip.address
```

For example, the line I sent in for my gateway was:

```
minnie.vk1xwt              IN    A    44.136.7.129
```

Aside: For those who understand DNS records, `ucsd.edu` will also accept CNAME and MX records. Also, you can delete previous entries by sending the same line, with the last field on the line the word 'delete'. Additions and changes to the DNS at `ucsd.edu` usually take a few days to be entered, so make sure you get things right first.

6 Installing the NOS Software

Installing the NOS software can be done in three stages:

- Install the software, and set the gateway up as a local amateur radio station; this includes setting up the TNC, transceiver and antenna. This should not be too hard to do, as the local amateur community can provide information on how to do this.
- Alter the setup to include an interface to the AARNet/Internet, using either an Ethernet board, or a serial link running SLIP or PPP. You will need an appropriate Ethernet driver if you are using an Ethernet board – these can be obtained from `ucsd.edu` in the directory `hamradio/drivers`. Read the documentation that comes with the driver package.
- Finally, set up encapsulated routes to the other amateur gateways, and email their operators so that they will set up routes back to your gateway. Use the 'ping', 'telnet' and 'ftp' commands in NOS to ensure that the encapsulation is working.

Example setup files are given in the appendices , and are currently in use at the `minnie.cs.adfa.oz.au` gateway. This section will discuss aspects of a gateway's setup that I think need attention.

To begin with, the hostname of the gateway should be the gateway's amateur domain name, as it will be used mainly by amateurs. Ensure that the gateway has a valid amateur callsign. Every interface used by the 2000gateway should use the amateur IP address, except for the single interface to the Internet, which should use the Internet IP address. The default route should be the Internet interface, as badly addressed packets will not affect anybody there. Ensure that routes are as specific as possible: for example, if your local amateur address are of the form $44.136.0.x$, then you should add a route to `44.136.0/24`.

6.1 Adding Encapsulated IP Routes

Adding the encapsulated IP routes to other gateways is very easy, as is shown in the example setup file in the appendices. Note that you must specify the Internet IP address of the gateway, and not the amateur IP address.

6.2 Adding Encapsulated AX.25 Routes

Due to the implementation aspects of AX.25 encapsulation, each encapsulated AX.25 route appears as a new **interface** under NOS, and as such, needs to have a new **SSID** (Station Sequence ID), as well as a new interface name. For example, the pseudo-interfaces used by the `minnie` gateway have SSIDs vk1xwt-2, vk1xwt-3, vk1xwt-4, vk1xwt-5 and vk1xwt-6. These are different than the callsign used for the gateway, vk1xwt-1. According to the AX.25 protocol, this allows up to 15 pseudo-interfaces, with SSIDs of –1 to –15, as well as the local amateur interface.

For AX.25 encapsulation to work, you need to already have an encapsulated IP route defined to the destination gateway, and vice versa.

When using the encapsulated AX.25 service, you must remember that you need to use the SSID of the interface you want to connect through. For example, to connect to `minnie` locally, you would do:

```
net> connect vk1xwt-1
```

However, to connect to a machine in Hawaii through `minnie`, you need to use `minnie`'s SSID of –4:

```
net> connect ah6bw-1 vk1xwt-4
```

Similarly, a user in Hawaii connects **to** `vk1xwt-4`, but connects **through** `vk1xwt-1`.

7 Security Considerations – Packet Filtering

One obvious problem with a gateway is that packets from Internet machines may escape out onto amateur frequencies. This problem is usually minimised by not advertising routes to amateur frequencies to Internet machines. However, this is security through obscurity.

New versions of NOS have solved this problem by adding packet filtering, known as 'IP Access'. WIth IP access, the gateway can allow or refuse to transmit a packet on any interface according to the source IP address in the packet. Thus, access to amateur frequencies can be denied to all packets who have non-amateur IP addresses, i.e IP addresses that are not of the form 44.X.Y.Z.

IP Access is described more completely in the appendices and in the NOS documentation.

8 Security Considerations – Services

If you use your gateway with no services running, you can guarantee the security of your gateway. However, with several services, the mailbox, SMTP, RIP and the converse service, your security can be breached. Fortunately, these services can be secured as described below.

8.1 RIP

RIP is the routing protocol that is used to pass routing information around between machines on the Internet. Strictly speaking, a packet–Internet gateway does not need to run RIP, as all of its routes are statically defined. The only reason for a gateway to run RIP is to inform and/or learn from other gateways when new gateways become available.

If you think that using RIP is a good idea, you must ensure that:

- You do not broadcast your routing table to your local network; if you do, non-amateur machines will learn about routes to the amateur gateways, and may allow non-amateurs to use amateur transceivers.
- You refuse all RIP broadcasts from your local network; if you do not, amateurs will learn about the Internet addresses on your local network, which are non-amateur addresses.
- You only send your routing table to destination amateur gateways, as they are the only machines who are interested in your routes.

I would receommend **not** running RIP at all.

8.2 The Mailbox

The mailbox service can be accessed in two ways: by a local amateur connecting to your machine using the AX.25 protocol, or by an amateur or non-amateur connecting to your machine by the Telnet protocol.

The mailbox provides features that you do not want amateur or non-amateur users to access:

- A Telnet capability which can connect to both amateur and non-amateur machines.
- A Gateway capability which can connect using AX.25 to amateur machines.
- A Netrom capability which can connect using NETROM to amateur machines.
- A Remote operation capability which allows a user to change the current setup of the gateway.