An Introduction to the UNIX Shell

S. R. Bourne

Murray Hill, NJ

(Updated for 4.3BSD by Mark Seiden)

(Further updated by Perry E. Metzger)†

ABSTRACT

The *shell* is a command programming language that provides an interface to the UNIX® operating system. Its features include control-flow primitives, parameter passing, variables and string substitution. Constructs such as *while, if then else, case* and *for* are available. Two-way communication is possible between the *shell* and commands. String-valued parameters, typically file names or flags, may be passed to a command. A return code is set by commands that may be used to determine control-flow, and the standard output from a command may be used as shell input.

The *shell* can modify the environment in which commands run. Input and output can be redirected to files, and processes that communicate through 'pipes' can be invoked. Commands are found by searching directories in the file system in a sequence that can be defined by the user. Commands can be read either from the terminal or from a file, which allows command procedures to be stored for later use.

1.0 Introduction

The shell is both a command language and a programming language that provides an interface to the UNIX operating system. This memorandum describes, with examples, the UNIX shell. The first section covers most of the everyday requirements of terminal users. Some familiarity with UNIX is an advantage when reading this section; see, for example, "UNIX for beginners".[1] Section 2 describes those features of the shell primarily intended for use within shell procedures. These include the control-flow primitives and string-valued variables provided by the shell. A knowledge of a programming language would be a help when reading this section. The last section describes the more advanced features of the shell. References of the form "see *pipe* (2)" are to a section of the UNIX manual.[2]

1.1 Simple commands

Simple commands consist of one or more words separated by blanks. The first word is the name of the command to be executed; any remaining words are passed as arguments to the command. For example,

```
who
```

is a command that prints the names of users logged in. The command

```
ls –l
```

prints a list of files in the current directory. The argument *–l* tells *ls* to print status information, size and the creation date for each file.

---

† This paper was updated in 2010 to reflect most features of modern POSIX shells, which all follow the design of S.R. Bourne's original v7 Unix shell. Among these are ash, bash, ksh and others. Typically one of these will be installed as /bin/sh on a modern system. It does not describe the behavior of the c shell (csh). If it's the c shell (csh) you're interested in, a good place to begin is William Joy's paper "An Introduction to the C shell" (USD:4).

1.2 Input output redirection

Most commands produce output on the standard output that is initially connected to the terminal. This output may be sent to a file by writing, for example,

```
ls –l >file
```

The notation *>file* is interpreted by the shell and is not passed as an argument to *ls.* If *file* does not exist then the shell creates it; otherwise the original contents of *file* are replaced with the output from *ls.* Output may be appended to a file using the notation

```
ls –l >>file
```

In this case *file* is also created if it does not already exist.

The standard input of a command may be taken from a file instead of the terminal by writing, for example,

```
wc <file
```

The command *wc* reads its standard input (in this case redirected from *file*) and prints the number of characters, words and lines found. If only the number of lines is required then

```
wc –l <file
```

could be used.

1.3 Pipelines and filters

The standard output of one command may be connected to the standard input of another by writing the 'pipe' operator, indicated by |, as in,

```
ls –l | wc
```

Two commands connected in this way constitute a *pipeline* and the overall effect is the same as

```
ls –l >file; wc <file
```

except that no *file* is used. Instead the two *processes* are connected by a pipe (see *pipe*(2)) and are run in parallel. Pipes are unidirectional and synchronization is achieved by halting *wc* when there is nothing to read and halting *ls* when the pipe is full.

A *filter* is a command that reads its standard input, transforms it in some way, and prints the result as output. One such filter, *grep,* selects from its input those lines that contain some specified string. For example,

```
ls | grep old
```

prints those lines, if any, of the output from *ls* that contain the string *old.* Another useful filter is *sort*. For example,

```
who | sort
```

will print an alphabetically sorted list of logged in users.

A pipeline may consist of more than two commands, for example,

```
ls | grep old | wc –l
```

prints the number of file names in the current directory containing the string *old.*

1.4 Background commands

To execute a command (or pipeline) the shell normally creates the new *processes* and waits for them to finish. A command may be run without waiting for it to finish. For example,

```
cc pgm.c &
```

calls the C compiler to compile the file *pgm.c*. The trailing **&** is an operator that instructs the shell not to wait for the command to finish. To help keep track of such a process the shell reports its job number (see below) and process id following its creation. Such a command is said to be running in the *background*. By contrast, a command

executed without the **&** is said to be running in the *foreground*.†

A list of currently active processes, including ones not associated with the current shell, may be obtained using the *ps*(1) command.

1.5 File name generation

Many commands accept arguments which are file names. For example,

```
ls –l main.c
```

prints information relating to the file *main.c* .

The shell provides a mechanism for generating a list of file names that match a pattern. For example,

```
ls –l ∗.c
```

generates, as arguments to *ls,* all file names in the current directory that end in *.c* . The character ∗ is a pattern that will match any string including the null string. In general *patterns* are specified as follows.

- **∗** Matches any string of characters including the null string.
- **?** Matches any single character.
- **[. . .]** Matches any one of the characters enclosed. A pair of characters separated by a minus will match any character lexically between the pair.

For example,

```
[a–z]∗
```

matches all names in the current directory beginning with one of the letters *a* through *z.*

```
/usr/fred/test/?
```

matches all names in the directory **/usr/fred/test** that consist of a single character. If no file name is found that matches the pattern then the pattern is passed, unchanged, as an argument.

This mechanism is useful both to save typing and to select names according to some pattern. It may also be used to find files. For example,

```
echo /usr/fred/∗/core
```

finds and prints the names of all *core* files in sub-directories of **/usr/fred .** (*echo* is a standard UNIX command that prints its arguments, separated by blanks.) This last feature can be expensive, requiring a scan of all sub-directories of **/usr/fred .**

There is one exception to the general rules given for patterns. The character '**.**' at the start of a file name must be explicitly matched.

```
echo ∗
```

will therefore echo all file names in the current directory not beginning with '**.**' .

```
echo .∗
```

will echo all those file names that begin with '**.**' . This avoids inadvertent matching of the names '**.**' and '**..**' which mean 'the current directory' and 'the parent directory' respectively. (Notice that *ls* suppresses information for the files '**.**' and '**..**' .)

Finally, the tilde character, '~', may be used to indicate the home directory of a user. The '~' at the beginning of a path name followed by a non-alphabetic character expands to the current user's home directory. If the '~' is followed by a login name, it expands to the named user's home directory. For example:

```
ls ~
cd ~egbert/
```

† Even after execution, one may move commands from the foreground to the background, or temporarily suspend their execution (which is known as *stopping* a command. This is described in detail in section 3.10 on *Job Control***.**

will list the contents of the user's home directory and then change to the home directory of the user ''egbert''.

1.6 Quoting

Characters that have a special meaning to the shell, such as **< > * ? | & ,** are called metacharacters. A complete list of metacharacters is given in appendix B. Any character preceded by a **** is *quoted* and loses its special meaning, if any. The **** is elided so that

```
echo \?
```

will echo a single **?**, and

```
echo \\
```

will echo a single **\.** To allow long strings to be continued over more than one line the sequence **\newline** is ignored.

**** is convenient for quoting single characters. When more than one character needs quoting the above mechanism is clumsy and error prone. A string of characters may be quoted by enclosing the string between single quotes. For example,

```
echo xx'****'xx
```

will echo

```
xx****xx
```

The quoted string may not contain a single quote but may contain newlines, which are preserved. This quoting mechanism is the most simple and is recommended for casual use.

A third quoting mechanism using double quotes is also available that prevents interpretation of some but not all metacharacters. Discussion of the details is deferred to section 3.5 .

1.7 Prompting

When the shell is used from a terminal it will issue a prompt before reading a command. By default this prompt is '**$** ' . It may be changed by saying, for example,

```
PS1="yesdear$ "
```

that sets the prompt to be the string *yesdear$* . If a newline is typed and further input is needed then the shell will issue the prompt '**>** ' . Sometimes this can be caused by mistyping a quote mark. If it is unexpected then entering the interrupt character (typically CONTROL-C) will return the shell to read another command. This prompt may be changed by saying, for example,

```
PS2=more
```

Entering the interrupt character may also be used to terminate most programs running as the current foreground job.

(PS1 and PS2 are *shell variables*, which will be described in section 2.4 below.)

1.8 The shell and login

Following *login*(1) the shell is called to read and execute commands typed at the terminal. If the user's login directory contains the file **.profile** then it is assumed to contain commands and is read by the shell before reading any commands from the terminal.

(Most versions of the shell also specify a file that is read and executed on start-up whether or not the shell is invoked by login. The ENV shell variable, described in section 2.4 below, can be used to override the name of this file. See the shell manual page for further information.)

1.9 Summary

- **ls**
  Print the names of files in the current directory.

- **ls >file**
  Put the output from *ls* into *file.*
- **ls | wc –l**
  Print the number of files in the current directory.
- **ls | grep old**
  Print those file names containing the string *old.*
- **ls | grep old | wc –l**
  Print the number of files whose name contains the string *old.*
- **cc pgm.c &**
  Run *cc* in the background.

2.0 Shell scripts

The shell may be used to read and execute commands contained in a file. For example,

sh file [args **. . .**]

calls the shell to read commands from *file.* Such a file is called a *shell script.* Arguments may be supplied with the call and are referred to in *file* using the positional parameters **$1, $2, ...**

For example, if the file *wg* contains

who | grep $1

then

sh wg fred

is equivalent to

who | grep fred

UNIX files have three independent attributes, *read, write* and *execute.* The UNIX command *chmod*(1) may be used to make a file executable. For example,

chmod +x wg

will ensure that the file *wg* has execute status. Following this, the command

wg fred

is equivalent to

sh wg fred

This allows shell scripts and other programs to be used interchangeably. In either case a new process is created to run the command.

The '**#**' character is used as a comment character by the shell. All characters following the '#' on a line are ignored.

A typical modern system has several different shells, some with differing command syntax, and it is desirable to specify which one should be invoked when an executable script is invoked. If the special comment

#!/*path/to/interpreter*

appears as the first line in a script, it is used to specify the absolute pathname of the shell (or other interpreter) that should be used to execute the file. (Without such a line, **/bin/sh** is assumed.) It is best if a script explicitly states what shell it is intended for in this manner.

As well as providing names for the positional parameters, the number of positional parameters to a script is available as **$#.** The name of the file being executed is available as **$0.**

A special shell parameter **$*** is used to substitute for all positional parameters except **$0.** A typical use of this is to provide some default arguments, as in,

```
nroff −T450 −ms $∗
```

which simply prepends some arguments to those already given. (The variable **$@** also expands to ‘‘all positional parameters’’, but is subtly different when expanded inside quotes. See section 3.5, below.)

2.1 Control flow - for

A frequent use of shell scripts is to loop through the arguments (**$1, $2, ...**) executing commands once for each argument. An example of such a script is *tel* that searches the file **/usr/share/telnos** that contains lines of the form

```
...
fred mh0123
bert mh0789
...
```

The text of *tel* is

```
#!/bin/sh

for i
do
        grep $i /usr/share/telnos
done
```

The command

```
tel fred
```

prints those lines in **/usr/share/telnos** that contain the string *fred*.

```
tel fred bert
```

prints those lines containing *fred* followed by those for *bert.*

The **for** loop notation is recognized by the shell and has the general form

for *name* **in** *w1 w2* **...**
do *command-list*
done

A *command-list* is a sequence of one or more simple commands separated or terminated by a newline or semicolon. Furthermore, reserved words like **do** and **done** are only recognized following a newline or semicolon. *name* is a shell variable that is set to the words *w1 w2* **...** in turn each time the *command-list* following **do** is executed. If **in** *w1 w2* **...** is omitted then the loop is executed once for each positional parameter; that is, **in** *$∗* is assumed.

Another example of the use of the **for** loop is the *create* command whose text is

```
for i do >$i; done
```

The command

```
create alpha beta
```

ensures that two empty files *alpha* and *beta* exist and are empty. The notation *>file* may be used on its own to create or clear the contents of a file. Notice also that a semicolon (or newline) is required before **done.**

2.2 Control flow - case

A multiple way branch is provided for by the **case** notation. For example,

```
case $# in
    1)    cat ≫$1 ;;
    2)    cat ≫$2 <$1 ;;
    ∗)    echo ´usage: append [ from ] to´ ;;
esac
```

is an *append* command. When called with one argument as

```
append file
```

$# is the string *1* and the standard input is copied onto the end of *file* using the *cat* command.

```
append file1 file2
```

appends the contents of *file1* onto *file2*. If the number of arguments supplied to *append* is other than 1 or 2 then a message is printed indicating proper usage.

The general form of the **case** command is

case *word* **in**
    pattern **)** *command-list* **;;**
    ...
esac

The shell attempts to match *word* with each *pattern,* in the order in which the patterns appear. If a match is found the associated *command-list* is executed and execution of the **case** is complete. Since ∗ is the pattern that matches any string it can be used for the default case.

A word of caution: no check is made to ensure that only one pattern matches the case argument. The first match found defines the set of commands to be executed. In the example below the commands following the second ∗ will never be executed.

```
case $# in
    ∗) ... ;;
    ∗) ... ;;
esac
```

Another example of the use of the **case** construction is to distinguish between different forms of an argument. The following example is a fragment of a *cc* command.

```
for i
do case $i in
        −[ocs])    ... ;;
        −∗) echo "unknown flag $i" ;;
        ∗.c) /lib/c0 $i ... ;;
        ∗)   echo "unexpected argument $i" ;;
   esac
done
```

To allow the same commands to be associated with more than one pattern the **case** command provides for alternative patterns separated by a | . For example,

```
case $i in
    −x|−y)...
esac
```

is equivalent to

```
case $i in
    −[xy]) ...
esac
```

The usual quoting conventions apply so that

```
case $i in
    \?)    ...
```

will match the character **?** .

2.3 Here documents

The shell script *tel* in section 2.1 uses the file **/usr/share/telnos** to supply the data for *grep*. An alternative is to include this data within the shell script as a *here* document, as in,

```
for i
do grep $i <<!
   ...
   fred mh0123
   bert mh0789
   ...
!
done
```

In this example the shell takes the lines between **<<!** and **!** as the standard input for *grep*. The string **!** is arbitrary, the document being terminated by a line that consists of the string following << .

Parameters are substituted in the document before it is made available to *grep* as illustrated by the following script called *edg* .

```
ed $3 <<%
g/$1/s//$2/g
w
%
```

The call

```
edg string1 string2 file
```

is then equivalent to the command

```
ed file <<%
g/string1/s//string2/g
w
%
```

and changes all occurrences of *string1* in *file* to *string2* . Substitution can be prevented using \ to quote the special character **$** as in

```
ed $3 <<+
1,\$s/$1/$2/g
w
+
```

(This version of *edg* is equivalent to the first except that *ed* will print a **?** if there are no occurrences of the string **$1** .) Substitution within a *here* document may be prevented entirely by quoting the terminating string, for example,

```
grep $i <<'end'
...
end
```

The document is presented without modification to *grep*. If parameter substitution is not required in a *here* document this latter form is more efficient.

2.4 Shell variables†

The shell provides string-valued variables. Variable names begin with a letter and consist of letters, digits and underscores. Variables may be given values by writing, for example,

```
user=fred box=m000 acct=mh0000
```

which assigns values to the variables **user, box** and **acct.** A variable may be set to the null string by saying, for example,

```
null=
```

The value of a variable is substituted by preceding its name with **$** ; for example,

```
echo $user
```

will echo *fred.*

Variables may be used interactively to provide abbreviations for frequently used strings. For example,

```
b=/usr/fred/bin
mv pgm $b
```

will move the file *pgm* from the current directory to the directory **/usr/fred/bin .** A more general notation is available for parameter (or variable) substitution, as in,

```
echo ${user}
```

which is equivalent to

```
echo $user
```

and is used when the parameter name is followed by a letter or digit. For example,

```
tmp=/tmp/ps
ps a >${tmp}a
```

will direct the output of *ps* to the file **/tmp/psa,** whereas,

```
ps a >$tmpa
```

would cause the value of the variable **tmpa** to be substituted.

Except for **$?** the following are set initially by the shell. **$?** is set after executing each command.

$? The exit status (return code) of the last command executed as a decimal string. Most commands return a zero exit status if they complete successfully, otherwise a non-zero exit status is returned. Testing the value of return codes is dealt with later under **if** and **while** commands.

$# The number of positional parameters (in decimal). Used, for example, in the *append* command to check the number of parameters.

$$ The process number of this shell (in decimal). Since process numbers are unique among all existing processes, this string is frequently used to generate unique temporary file names. For example,

```
ps a >/tmp/ps$$
...
rm /tmp/ps$$
```

$! The process number of the last process run in the background (in decimal).

$– The current shell flags, such as **–x** and **–v .**

Some variables have a special meaning to the shell and should be avoided for general use.

$MAIL When used interactively the shell looks at the file specified by this variable before it issues a prompt. If the specified file has been modified since it was last looked at the shell prints the message *you have mail* before prompting for the next command. This variable is typically set in the file **.profile,**

---

† Also known as *environment variables*, **see** *environment*(**7**).

in the user's login directory. For example,

```
MAIL=/usr/spool/mail/fred
```

$HOME The default argument for the *cd* command. The current directory is used to resolve file name references that do not begin with a **/ ,** and is changed using the *cd* command. For example,

```
cd /usr/fred/bin
```

makes the current directory **/usr/fred/bin .**

```
cat wn
```

will print on the terminal the file *wn* in this directory. The command *cd* with no argument is equivalent to

```
cd $HOME
```

This variable is also typically set in the the user's login profile.

$PWD The current working directory. Set by the *cd* **command.**

$PATH A list of directories that contain commands (the *search path*). Each time a command is executed by the shell a list of directories is searched for an executable file. If **$PATH** is not set then the current directory, **/bin**, and **/usr/bin** are searched by default. Otherwise **$PATH** consists of directory names separated by **: .** For example,

```
PATH=:/usr/fred/bin:/bin:/usr/bin
```

specifies that the current directory (the null string before the first **:**), **/usr/fred/bin, /bin** and **/usr/bin** are to be searched in that order. In this way individual users can have their own 'private' commands that are accessible independently of the current directory. If the command name contains a **/** then this directory search is not used; a single attempt is made to execute the command.

$PS1 The primary shell prompt string, by default, '**$** '.

$PS2 The shell prompt when further input is needed, by default, '**>** '.

$IFS The set of characters used by *blank interpretation* (see section 3.5).

$ENV The shell reads and executes the commands in the file specified by this variable when it is initially started. Unlike the **.profile** file, these commands are executed by all shells, not just the one started at login. (Most versions of the shell specify a filename that is used if ENV is not explicitly set. See the manual page for your shell.)

2.5 The test command

The *test* command, although not part of the shell, is intended for use by shell programs. For example,

```
test –f file
```

returns zero exit status if *file* exists and non-zero exit status otherwise. In general *test* evaluates a predicate and returns the result as its exit status. Some of the more frequently used *test* arguments are given here, see *test*(1) for a complete specification.

test s	true if the argument *s* is not the null string
test –f file	true if *file* exists
test –r file	true if *file* is readable
test –w file	true if *file* is writable
test –d file	true if *file* is a directory

The *test* command is known as '**[**' and may be invoked as such. For aesthetic reasons, the command ignores a close bracket '**]**' given at the end of a command so

```
[ -f filename ]
```

and

```
test -f filename
```

are completely equivalent. Typically, the bracket notation is used when *test* is invoked inside shell control constructs.

2.6 Control flow - while

The actions of the **for** loop and the **case** branch are determined by data available to the shell. A **while** or **until** loop and an **if then else** branch are also provided whose actions are determined by the exit status returned by commands. A **while** loop has the general form

while *command-list*$_1$
do *command-list*$_2$
done

The value tested by the **while** command is the exit status of the last simple command following **while.** Each time round the loop *command-list*$_1$ is executed; if a zero exit status is returned then *command-list*$_2$ is executed; otherwise, the loop terminates. For example,

```
while [ $1 ]
do ...
   shift
done
```

is equivalent to

```
for i
do ...
done
```

shift is a shell command that renames the positional parameters **$2, $3, ...** as **$1, $2, ...** and loses **$1 .**

Another kind of use for the **while/until** loop is to wait until some external event occurs and then run some commands. In an **until** loop the termination condition is reversed. For example,

```
until [ –f file ]
do sleep 300; done
commands
```

will loop until *file* exists. Each time round the loop it waits for 5 minutes before trying again. (Presumably another process will eventually create the file.)

The most recent enclosing loop may be exited with the **break** command, or the rest of the body skipped and the next iteration begun with the **continue** command.

The commands *true*(1) and *false*(1) return 0 and non-zero exit statuses respectively. They are sometimes of use in control flow, e.g.:

```
while true
do date; sleep 5
done
```

is an infinite loop that prints the date and time every five seconds.

2.7 Control flow - if

Also available is a general conditional branch of the form,

if *command-list*
then *command-list*
else *command-list*
fi

that tests the value returned by the last simple command following **if.**

The **if** command may be used in conjunction with the *test* command to test for the existence of a file as in

```
if [ −f file ]
then  process file
else  do something else
fi
```

An example of the use of **if, case** and **for** constructions is given in section 2.10 .

A multiple test **if** command of the form

```
if ...
then  ...
else  if ...
      then  ...
      else  if ...
            ...
            fi
      fi
fi
```

may be written using an extension of the **if** notation as,

```
if ...
then  ...
elif  ...
then  ...
elif  ...
...
fi
```

The following example is an implementation of the *touch* command which changes the 'last modified' time for a list of files. The command may be used in conjunction with *make*(1) to force recompilation of a list of files.

```
#!/bin/sh

flag=
for i
do case $i in
        −c) flag=N ;;
        ∗)  if [ −f $i ]
            then  cp $i junk$$; mv junk$$ $i
            elif [ $flag ]
            then  echo file \'$i\' does not exist
            else  >$i
            fi
   esac
done
```

The **−c** flag is used in this command to force subsequent files to be created if they do not already exist. Otherwise, if the file does not exist, an error message is printed. The shell variable *flag* is set to some non-null string if the **−c** argument is encountered. The commands

```
cp ...; mv ...
```

copy the file and then overwrite it with the copy, thus causing the last modified date to be updated.

The sequence

```
if command1
then   command2
fi
```

may be written

```
command1 && command2
```

Conversely,

```
command1 || command2
```

executes *command2* only if *command1* fails. In each case the value returned is that of the last simple command executed.

Placing a '**!**' in front of a pipeline inverts its exit status, almost in the manner of the C operator of the same name. Thus:

```
if ! [ -d $1 ]
then
        echo $1 is not a directory
fi
```

will print a message only if $1 is not a directory.

2.8 Command grouping

Commands may be grouped in two ways,

{ *command-list* **; }**

and

(*command-list* **)**

In the first *command-list* is simply executed. The second form executes *command-list* as a separate process. For example,

```
(cd x; rm junk )
```

executes *rm junk* in the directory **x** without changing the current directory of the invoking shell.

The commands

```
cd x; rm junk
```

have the same effect but leave the invoking shell in the directory **x.**

2.9 Shell Functions

A function may be defined by the syntax

funcname() **{** *command-list* **; }**

Functions are invoked within a script as though they were separate commands of the same name. While they are executed, the positional parameters **$1, $2, . . .** are temporarily set to the arguments passed to the function. For example:

```
count() {
        echo $2 : $#
}

count a b c
```

would print 'b : 3'.

2.10 Debugging shell scripts

The shell provides two tracing mechanisms to help when debugging shell scripts. The first is invoked within the script as

```
set −v
```

(**v** for verbose) and causes lines of the script to be printed as they are read. It is useful to help isolate syntax errors. It may be invoked without modifying the script by saying

```
sh −v script ...
```

where *script* is the name of the shell script. This flag may be used in conjunction with the **−n** flag which prevents execution of subsequent commands. (Note that saying *set −n* at a terminal will render the terminal useless until an end-of-file is typed.)

The command

```
set −x
```

will produce an execution trace. Following parameter substitution each command is printed as it is executed. (Try these at the terminal to see what effect they have.) Both flags may be turned off by saying

```
set −
```

and the current setting of the shell flags is available as **$−** .

2.11 The man command

The following is a simple implementation of the *man* command, which is used to display sections of the UNIX manual on your terminal. It is called, for example, as

```
man sh
man −t ed
man 2 fork
```

In the first the manual section for *sh* is displayed.. Since no section is specified, section 1 is used. The second example will typeset (**−t** option) the manual section for *ed.* The last prints the *fork* manual page from section 2, which covers system calls.

```
#!/bin/sh

cd /usr/share/man

# "#" is the comment character
# default is nroff ($N), section 1 ($s)
N=n s=1

for i
do case $i in

        [1−9]∗)    s=$i ;;

        −t)  N=t ;;

        −n)  N=n ;;

        −∗) echo unknown flag \'$i\' ;;

        ∗)   if [ −f man$s/$i.$s ]
             then
                  ${N}roff −man man$s/$i.$s
             else   # look through all manual sections
                  found=no
                  for j in 1 2 3 4 5 6 7 8 9
                  do
                      if [ −f man$j/$i.$j ]
                      then
                           man $j $i
                           found=yes
                           break
                      fi
                  done
                  case $found in
                       no) echo \'$i: manual page not found\'
                  esac
             fi
   esac
done
```

Figure 1. A version of the man command

3.0 Keyword parameters

Shell variables may be given values by assignment or when a shell script is invoked. An argument to a command of the form *name=value* that precedes the command name causes *value* to be assigned to *name* before execution of the command begins. The value of *name* in the invoking shell is not affected. For example,

```
user=fred command
```

will execute *command* with **user** set to *fred*.

The *set* command may also be used to set positional parameters from within a script. For example,

```
set −− ∗
```

will set **$1** to the first file name in the current directory, **$2** to the next, and so on. Note that the first argument, −−, ensures correct treatment when the first file name begins with a − .

3.1 Parameter transmission

When a command is executed both positional parameters and shell variables may be set on invocation. Variables are also made available implicitly to a command by specifying in advance that such parameters are to be exported from the invoking shell. For example,

```
export user box=red
```

marks the variables **user** and **box** for export (setting **box** to "red" in the process). When a command is invoked copies are made of all exportable variables (also known as *environment variables*) for use within the invoked program. Modification of such variables within an invoked command does not affect the values in the invoking shell. It is generally true of a shell script or other program that it cannot modify the state of its caller without explicit actions on the part of the caller.

Names whose value is intended to remain constant may be declared *readonly*. The form of this command is the same as that of the *export* command,

```
readonly name[=value] ...
```

Subsequent attempts to set readonly variables are illegal.

3.2 Parameter substitution

If a shell parameter is not set then the null string is substituted for it. For example, if the variable **d** is not set

```
echo $d
```

or

```
echo ${d}
```

will echo nothing. A default string may be given as in

```
echo ${d:-.}
```

which will echo the value of the variable **d** if it is set and not null and '**.**' otherwise. The default string is evaluated using the usual quoting conventions so that

```
echo ${d:-'*'}
```

will echo * if the variable **d** is not set or null. Similarly

```
echo ${d:-$1}
```

will echo the value of **d** if it is set and not null and the value (if any) of **$1** otherwise.

The notation ${d:+.} performs the inverse operation. It substitutes '**.**' if **d** is set or not null, and otherwise substitutes null.

A variable may be assigned a default value using the notation

```
echo ${d:=.}
```

which substitutes the same string as

```
echo ${d:-.}
```

and if **d** were not previously set or null then it will be set to the string '**.**' .

If there is no sensible default then the notation

```
echo ${d:?message}
```

will echo the value of the variable **d** if it is set and not null, otherwise *message* is printed by the shell and execution of the shell script is abandoned. If *message* is absent then a standard message is printed. A shell script that requires some variables to be set might start as follows:

```
: ${user:?} ${acct:?} ${bin:?}
...
```

Colon (**:**) is a command that is built in to the shell and does nothing once its arguments have been evaluated. If any of the variables **user, acct** or **bin** are not set then the shell will abandon execution of the script.

3.3 Command substitution

The standard output from a command can be substituted in a similar way to parameters. The command *pwd* prints on its standard output the name of the current directory. For example, if the current directory is **/usr/fred/bin** then the commands

```
d=$(pwd)
```

(or the older notation d=`pwd`) is equivalent to

```
d=/usr/fred/bin
```

The entire string inside $(**...**) (or between grave accents `**...**`) is taken as the command to be executed and is replaced with the output from the command. (The difference between the $(**...**) and `**...**` notations is that the former may be nested, while the latter cannot be.)

The command is written using the usual quoting conventions, except that inside `**...**` a ` must be escaped using a ****. For example,

```
ls $(echo "$HOME")
```

is equivalent to

```
ls $HOME
```

Command substitution occurs in all contexts where parameter substitution occurs (including *here* documents) and the treatment of the resulting text is the same in both cases. This mechanism allows string processing commands to be used within shell scripts. An example of such a command is *basename* which removes a specified suffix from a string. For example,

```
basename main.c .c
```

will print the string *main*. Its use is illustrated by the following fragment from a *cc* command.

```
case $A in
    ...
    *.c)    B=$(basename $A .c)
    ...
esac
```

that sets **B** to the part of **$A** with the suffix **.c** stripped.

Here are some composite examples.

- **for i in `ls –t`; do ...**
  The variable **i** is set to the names of files in time order, most recent first.
- **set — `date`; echo $6 $2 $3, $4**
  will print, e.g., *1977 Nov 1, 23:59:59*

3.4 Arithmetic Expansion

Within a $((**...**)) construct, integer arithmetic operations are evaluated. (The $ in front of variable names is optional within $((**...**)). For example:

```
x=5; y=1
echo $(($x+3*2))
echo $((y+=x))
echo $y
```

will print '11', then '6', then '6' again. Most of the constructs permitted in C arithmetic operations are permitted though some (like '++') are not universally supported — see the shell manual page for details.

3.5 Evaluation and quoting

The shell is a macro processor that provides parameter substitution, command substitution and file name generation for the arguments to commands. This section discusses the order in which these evaluations occur and the effects of the various quoting mechanisms.

Commands are parsed initially according to the grammar given in appendix A. Before a command is executed the following substitutions occur.

- parameter substitution, e.g. **$user**
- command substitution, e.g. **$(pwd)** or **`pwd`**
- arithmetic expansion, e.g. **$(($count+1))**

  Only one evaluation occurs so that if, for example, the value of the variable **X** is the string *$y* then

  ```
  echo $X
  ```

  will echo *$y*.
- blank interpretation

  Following the above substitutions the resulting characters are broken into non-blank words (*blank interpretation*). For this purpose 'blanks' are the characters of the string **$IFS**. By default, this string consists of blank, tab and newline. The null string is not regarded as a word unless it is quoted. For example,

  ```
  echo ´´
  ```

  will pass on the null string as the first argument to *echo*, whereas

  ```
  echo $null
  ```

  will call *echo* with no arguments if the variable **null** is not set or set to the null string.
- file name generation

  Each word is then scanned for the file pattern characters ***, ?** and **[...]** and an alphabetical list of file names is generated to replace the word. Each such file name is a separate argument.

The evaluations just described also occur in the list of words associated with a **for** loop. Only substitution occurs in the *word* used for a **case** branch.

As well as the quoting mechanisms described earlier using **** and **´...´** a third quoting mechanism is provided using double quotes. Within double quotes parameter and command substitution occurs but file name generation and the interpretation of blanks does not. The following characters have a special meaning within double quotes and may be quoted using **\.**

$	parameter substitution
$()	command substitution
`	command substitution
"	ends the quoted string
****	quotes the special characters **$ ` " **

For example,

```
echo "$x"
```

will pass the value of the variable **x** as a single argument to *echo.* Similarly,

```
echo "$*"
```

will pass the positional parameters as a single argument and is equivalent to

```
echo "$1 $2 ..."
```

The notation **$@** is the same as **$*** except when it is quoted.

```
echo "$@"
```

will pass the positional parameters, unevaluated, to *echo* and is equivalent to

```
echo "$1" "$2" ...
```

The following table gives, for each quoting mechanism, the shell metacharacters that are evaluated.

	metacharacter					
	\	$	*	`	"	´
´	n	n	n	n	n	t
`	y	n	n	t	n	n
"	y	y	n	y	t	n

t	terminator
y	interpreted
n	not interpreted

Figure 2. Quoting mechanisms

In cases where more than one evaluation of a string is required the built-in command *eval* may be used. For example, if the variable **X** has the value *$y*, and if **y** has the value *pqr* then

```
eval echo $X
```

will echo the string *pqr*.

In general the *eval* command evaluates its arguments (as do all commands) and treats the result as input to the shell. The input is read and the resulting command(s) executed. For example,

```
wg=´eval who | grep´
$wg fred
```

is equivalent to

```
who | grep fred
```

In this example, *eval* is required since there is no interpretation of metacharacters, such as | , following substitution.

3.6 Error handling

The treatment of errors detected by the shell depends on the type of error and on whether the shell is being used interactively. An interactive shell is one whose input and output are connected to a terminal. A shell invoked with the **–i** flag is also interactive.

Execution of a command (see also 3.7) may fail for any of the following reasons.

- Input output redirection may fail. For example, if a file does not exist or cannot be created.
- The command itself does not exist or cannot be executed.
- The command terminates abnormally, for example, with a "bus error" or "memory fault". See Figure 2 below for a complete list of UNIX signals.
- The command terminates normally but returns a non-zero exit status.

In all of these cases the shell will go on to execute the next command. Except for the last case an error message will be printed by the shell. All remaining errors cause the shell to exit from a script. An interactive shell will return to read another command from the terminal. Such errors include the following.

- Syntax errors. e.g., if **...** then **...** done
- A signal such as interrupt. The shell waits for the current command, if any, to finish execution and then either exits or returns to the terminal.
- Failure of any of the built-in commands such as *cd.*

The shell flag **−e** causes the shell to terminate if any error is detected.

1	hangup
2	interrupt
3*	quit
4*	illegal instruction
5*	trace trap
6*	IOT instruction
7*	EMT instruction
8*	floating point exception
9	kill (cannot be caught or ignored)
10*	bus error
11*	segmentation violation
12*	bad argument to system call
13	write on a pipe with no one to read it
14	alarm clock
15	software termination (from *kill* (1))

Figure 3. UNIX signals†

Those signals marked with an asterisk produce a core dump if not caught. However, the shell itself ignores quit which is the only external signal that can cause a dump. The signals in this list of potential interest to shell programs are 1, 2, 3, 14 and 15.

3.7 Fault handling

shell scripts normally terminate when an interrupt is received from the terminal. The *trap* command is used if some cleaning up is required, such as removing temporary files. For example,

```
trap ´rm /tmp/ps$$; exit´ 2
```

sets a trap for signal 2 (terminal interrupt), and if this signal is received will execute the commands

```
rm /tmp/ps$$; exit
```

exit is another built-in command that terminates execution of a shell script. The *exit* is required; otherwise, after the trap has been taken, the shell will resume executing the script at the place where it was interrupted.

UNIX signals can be handled in one of three ways. They can be ignored, in which case the signal is never sent to the process. They can be caught, in which case the process must decide what action to take when the signal is received. Lastly, they can be left to cause termination of the process without it having to take any further action. If a signal is being ignored on entry to the shell script, for example, by invoking it in the background (see 3.7) then *trap* commands (and the signal) are ignored.

The use of *trap* is illustrated by this modified version of the *touch* command (Figure 4). The cleanup action is to remove the file **junk$$** .

† Additional signals have been added in modern Unix. See *sigvec*(2) or *signal*(3) for an up-to-date list.

```
#!/bin/sh

flag=
trap ´rm −f junk$$; exit´ 1 2 3 15
for i
do case $i in
        −c) flag=N ;;
        ∗)  if test −f $i
            then   cp $i junk$$; mv junk$$ $i
            elif test $flag
            then   echo file \'$i\' does not exist
            else   >$i
            fi
   esac
done
```

Figure 4. The touch command

The *trap* command appears before the creation of the temporary file; otherwise it would be possible for the process to die without removing the file.

Since there is no signal 0 in UNIX it is used by the shell to indicate the commands to be executed on exit from the shell script.

A script may, itself, elect to ignore signals by specifying the null string as the argument to trap. The following fragment is taken from the *nohup* command.

```
trap ´´ 1 2 3 15
```

which causes *hangup, interrupt, quit* and *kill* to be ignored both by the script and by invoked commands.

Traps may be reset by saying

```
trap 2 3
```

which resets the traps for signals 2 and 3 to their default values. A list of the current values of traps may be obtained by writing

```
trap
```

The script *scan* (Figure 5) is an example of the use of *trap* where there is no exit in the trap command. *scan* takes each directory in the current directory, prompts with its name, and then executes commands typed at the terminal until an end of file or an interrupt is received. Interrupts are ignored while executing the requested commands but cause termination when *scan* is waiting for input.

```
d=`pwd`
for i in ∗
do if test −d $d/$i
   then cd $d/$i
        while echo "$i:"
              trap exit 2
              read x
        do trap : 2; eval $x; done
   fi
done
```

Figure 5. The scan command

read x is a built-in command that reads one line from the standard input and places the result in the variable **x.** It

returns a non-zero exit status if either an end-of-file is read or an interrupt is received.

3.8 Command execution

To run a command (other than a built-in) the shell first creates a new process using the system call *fork.* The execution environment for the command includes input, output and the states of signals, and is established in the child process before the command is executed. The built-in command *exec* is used in the rare cases when no fork is required and simply replaces the shell with a new command. For example, a simple version of the *nohup* command looks like

```
trap \'\' 1 2 3 15
exec $*
```

The *trap* turns off the signals specified so that they are ignored by subsequently created commands and *exec* replaces the shell by the command specified.

Most forms of input output redirection have already been described. In the following *word* is only subject to parameter and command substitution. No file name generation or blank interpretation takes place so that, for example,

```
echo ... >*.c
```

will write its output into a file whose name is ***.c .** Input output specifications are evaluated left to right as they appear in the command.

> *word* The standard output (file descriptor 1) is sent to the file *word* which is created if it does not already exist.

>> *word* The standard output is sent to file *word.* If the file exists then output is appended (by seeking to the end); otherwise the file is created.

< *word* The standard input (file descriptor 0) is taken from the file *word.*

<< *word* The standard input is taken from the lines of shell input that follow up to but not including a line consisting only of *word.* If *word* is quoted then no interpretation of the document occurs. If *word* is not quoted then parameter and command substitution occur and **** is used to quote the characters **\ $ `** and the first character of *word.* In the latter case **\newline** is ignored (c.f. quoted strings).

>& *digit* The file descriptor *digit* is duplicated using the system call *dup* (2) and the result is used as the standard output.

<& *digit* The standard input is duplicated from file descriptor *digit.*

<&– The standard input is closed.

>&– The standard output is closed.

Any of the above may be preceded by a digit in which case the file descriptor created is that specified by the digit instead of the default 0 or 1. For example,

```
... 2>file
```

runs a command with message output (file descriptor 2) directed to *file.*

```
... 2>&1
```

runs a command with its standard output and message output merged. (Strictly speaking file descriptor 2 is created by duplicating file descriptor 1 but the effect is usually to merge the two streams.)

3.9 Invoking the shell

The following flags are interpreted by the shell when it is invoked. If the first character of argument zero is a minus, then commands are read from the file **.profile .**

–c *string*
If the **–c** flag is present then commands are read from *string* .

–s If the **–s** flag is present or if no arguments remain then commands are read from the standard input. Shell output is written to file descriptor 2.

–i If the **–i** flag is present or if the shell input and output are attached to a terminal (as told by *gtty*) then this shell is *interactive*. In this case TERMINATE is ignored (so that **kill 0** does not kill an interactive shell) and INTERRUPT is caught and ignored (so that **wait** is interruptable). In all cases QUIT is ignored by the shell.

3.10 Job Control

When a command or pipeline (also known as a *job*) is running in the foreground, entering the stop character (typically CONTROL-Z but user settable with the *stty*(1) command) will usually cause the job to stop.

The jobs associated with the current shell may be listed by entering the *jobs* command. Each job has an associated *job number*. Jobs that are stopped may be continued by entering

bg *%jobnumber*

and jobs may be moved to the foreground by entering

fg *%jobnumber*

If there is a sole job with a particular name (say only one instance of *cc* running), *fg* and *bg* may also use name of the command in place of the number, as in:

bg %cc

If no '**%**' clause is entered, most recently stopped job (indicated with a '+' by the *jobs* command) will be assumed. See the manual page for the shell for more details.

3.11 Aliases

The *alias* command creates a so-called shell alias, which is an abbreviation that macro-expands at run time into some other command. For example:

alias ls="ls -F"

would cause the command sequence **ls -F** to be executed whenever the user types **ls** into the shell. Note that if the user types **ls -a**, the shell will in fact execute **ls -F -a**. The command **alias** on its own prints out all current aliases. The *unalias* command, as in:

unalias ls

will remove an existing alias. Aliases can shadow pre-existing commands, as in the example above. They are typically used to override the interactive behavior of commands in small ways, for example to always invoke some program with a favorite option, and are almost never found in scripts.

3.12 Command Line Editing and Recall

When working interactively with the shell, it is often tedious to retype previously entered commands, especially if they are complicated. The shell therefore maintains a so-called *history*, which is stored in the file specified by the **HISTFILE** environment variable if it is set. Users may view, edit, and re-enter previous lines of input using a small subset of the commands of the *vi*(1) or *emacs*(1)† editors. Emacs style editing may be selected by entering

set -o emacs

and vi style editing may be selected with

set -o vi

The details of how command line editing works are beyond the scope of this document. See the shell manual page for details.

Acknowledgements

The design of the shell is based in part on the original UNIX shell[3] and the PWB/UNIX shell,[4] some features having been taken from both. Similarities also exist with the command interpreters of the Cambridge Multiple Access

† Technically, vi command editing is standardized by POSIX while emacs is not. However, all modern shells support both styles.

System[5] and of CTSS.[6]

I would like to thank Dennis Ritchie and John Mashey for many discussions during the design of the shell. I am also grateful to the members of the Computing Science Research Center and to Joe Maranzano for their comments on drafts of this document.

References

1.

2.

3.

4.

5.

6.

Appendix A - Grammar

Note: This grammar needs updating, it is obsolete.

item: *word*
input-output
name = *value*

simple-command: *item*
simple-command item

command: *simple-command*
(*command-list* **)**
{ *command-list* **}**
for *name* **do** *command-list* **done**
for *name* **in** *word* **. . . do** *command-list* **done**
while *command-list* **do** *command-list* **done**
until *command-list* **do** *command-list* **done**
case *word* **in** *case-part* **. . . esac**
if *command-list* **then** *command-list else-part* **fi**

pipeline: *command*
pipeline | *command*

andor: *pipeline*
andor **&&** *pipeline*
andor | | *pipeline*

command-list: *andor*
command-list **;**
command-list **&**
command-list **;** *andor*
command-list **&** *andor*

input-output: **>** *file*
< *file*
>> *word*
<< *word*

file: *word*
& *digit*
& **–**

case-part: *pattern* **)** *command-list* **;;**

pattern: *word*
pattern | *word*

else-part: **elif** *command-list* **then** *command-list else-part*
else *command-list*
empty

empty:

word: a sequence of non-blank characters

name: a sequence of letters, digits or underscores starting with a letter

digit: **0 1 2 3 4 5 6 7 8 9**

Appendix B - Meta-characters and Reserved Words

a) syntactic

|	pipe symbol
&&	'andf' symbol
||	'orf' symbol
;	command separator
;;	case delimiter
&	background commands
( )	command grouping
<	input redirection
<<	input from a here document
>	output creation
>>	output append

b) patterns

*****	match any character(s) including none
?	match any single character
[...]	match any of the enclosed characters

c) substitution

${...}	substitute shell variable
$(...)	substitute command output
`...`	substitute command output
$((...))	substitute arithmetic expression

d) quoting

****	quote the next character
´...´	quote the enclosed characters except for ´
"..."	quote the enclosed characters except for **$ ` \ "**

e) reserved words

if then else elif fi
case in esac
for while until do done
! { }